

List of Figures

List of Figures

Figure	Page
2.1 William Grove's drawing of an experimental gas battery	10
2.2 Schematics of MEA in single – cell testing apparatus	14
2.3 Terminal voltage versus current density	18
2.4 Cell Potential versus Current density plots for single cells of Nafion R 117 membrane with different thickness, operating at 95°C with H ₂ /O ₂ at 4/5 atm. Nafion thickness: 1 – 50 µm; 2 – 100 µm; 3 – 175 µm. Pt loading on each electrode: 0.45 mg/cm ²	35
2.5 The gas diffusion layer (not to scale)	43
2.6 Polarization curve for electrode fuel cell with diffusion and without Diffusion layer	46
3.1 Schematics of a SFCCVD reactor	67
3.2 Schematics of SFCCVD reactor for continuous production of CNTs	69
3.3 Schematics of the horizontal chemical vapour deposition reactor	70
3.4 Hot press equipment for the fabrication of membrane electrode assembly	82
4.1 (a) TEM image of a long and pure CNT sample obtained at 1000°C	86
(b) SEM image of clustered CNT samples	86
4.2 (a) TEM image of CNT sample showing the multi walls	87
(b) High magnification TEM image of CNT sample showing the diameter of the tube	87
4.3 XRD pattern of raw CNT sample	88
4.4 Effect of acetylene flow rate on the rate of production of CNTs	89

List of Figures

4.5	Effect of hydrogen flow rate of the rate of production of CNTs	91
4.6	Effect of acetylene/hydrogen flow ratio on the rate of production of CNTs	92
4.7	Effect of temperature on the rate of production of CNTs at different acetylene/hydrogen flow ratios	94
4.8	Effects of operating conditions on amount of CNTs produced	95
4.9	Mass of Fe–Co catalyst versus CNTs produced	97
4.10	(a-b) TEM images of as-produced clustered CNT samples synthesized by horizontal CVD reactor	98
	(c-d) High magnification TEM images of raw CNT samples synthesized by horizontal CVD reactor	98
4.11	EDX analysis of as-synthesized CNT sample showing the presence of Fe and Co	99
4.12	High magnification TEM image of CNT sample showing diameter of the nanotube and the thickness of the multiwalls	99
4.13	TEM images of (a-b) as-synthesized and (c-d) purified CNT samples	101
4.14	EDX analysis of the purified CNT sample	103
4.15	Raman spectra of purified and unpurified CNT samples	104
4.16	TGA curves of purified and unpurified CNT samples	106
5.1	FT IR spectra of functionalized CNT sample	108
5.2	Calibration curve for absorbance profile of Pt in CNT	109
5.3	Effect of stirring time on Pt adsorbed on CNTs	110
5.4	Effect of temperature on Pt adsorbed on CNTs	112

List of Figures

5.5	TEM images of Pt–CNT catalysts with (a) 10 wt% and (b) 20 wt% loading of platinum. The particle size distributions of metallic Pt in various loadings of the catalysts are located beside the TEM images	115
5.6	TEM images of Pt–CNT catalysts with (a) 30 wt% and (b) 40 wt% loading of platinum. The particle size distributions of metallic Pt in various loadings of the catalysts are located beside the TEM images	116
5.7	EDX analysis of the Pt–CNT catalyst sample confirming the presence of Pt.	117
5.8	Histograms for the Pt distribution in various loadings of the catalysts as shown in the TEM image	118
5.9	XRD pattern of Pt–CNT catalyst sample	121
5.10	TGA curves of (a) Pt–CNT catalyst and (b) purified CNT samples showing 10 wt% Pt loading	123
5.11	Cyclic voltammogram of 10 wt% Pt–CNT catalyst at a scan rate of 20 mV/s in nitrogen saturated 0.5 M H ₂ SO ₄	125
5.12	Cyclic voltammogram of 20 wt% Pt–CNT catalyst at a scan rate of 20 mV/s in nitrogen saturated 0.5 M H ₂ SO ₄	125
5.13	Cyclic voltammogram of 30 wt% Pt–CNT catalyst at a scan rate of 20 mV/s in nitrogen saturated 0.5 M H ₂ SO ₄ .	127
5.14	Cyclic voltammogram of 40 wt% Pt–CNT catalyst at a scan rate of 20 mV/s in nitrogen saturated 0.5 M H ₂ SO ₄ .	127
5.15	SEM images of carbon paper used in this study	128
5.16	SEM images of the electrode samples	129
5.17	Polarisation curve of a single cell operated at 25°C with H ₂ :O ₂ ratio of 1:2	131

List of Figures

5.18	Power density Vs current density for a single cell (25 cm ²) for electrodes operated at 25°C	133
5.19	Polarisation curve showing the open voltage for experimental and literature in a single cell operated with H ₂ :O ₂ ratio of 1:2	134
5.20	Performance durability of a single cell (25 cm ²) for electrode operated at 25°C	137
5.21	Tafel plot for overpotential of a single cell operated at 25°C	139
5.22	Experimental and simulated polarization of 40wt% Pt catalyst electrode	142
5.23	Hirschhofer's model of voltage of 40wt% Pt catalyst electrode	144