

TABLE OF CONTENTS

DECLARATION	ii
SIGNATURE OF CANDIDATE.....	ii
ABSTRACT	viii
DEDICATION	x
ACKNOWLEDGEMENTS	xi
1 INTRODUCTION.....	1
1.1 STATEMENT OF THE PROBLEM	3
1.2 JUSTIFICATION	5
1.3 APPROACH TO SOLVING THE PROBLEM.....	6
1.4 LIMITATIONS OF THE RESEARCH.....	7
1.5 DOCUMENT OVERVIEW	8
2 METHODOLOGIES	9
2.1 EXPERIMENTAL VERIFICATION OF THE NUMERICAL MODEL	9
2.1.1 THE EXPERIMENTAL SITUATION.....	10
2.1.2 RESULTS: MEASURED VERSUS THEORETICAL	10
2.2 CONVERGENT (OPTIMIZED) AND SPARSE LPDA ANTENNAS.....	13
2.2.1 CONVERGENCE (OR OPTIMISATION) CRITERIA FOR LPDA ANTENNAS	20
3 RESULTS.....	22
3.1 PROBABLE GAIN PERFORMANCE CHARACTERISTICS OF LPDA ANTENNAS (CONVERGENT/SPARSE).....	22
3.2 CONVERGENT (OR OPTIMISED) LPDA ANTENNAS.....	29
3.3 THE EFFECT OF BOOM-IMPEDANCE (Z_0) ON THE GAIN PERFORMANCE OF OPTIMISED (OR CONVERGENT) LPDA ANTENNAS.....	33
3.4 EFFECT OF LENGTH TO DIAMETER (L_n/D_n) RATIO ON THE GAIN PERFORMANCE OF	

	OPTIMISED (OR CONVERGENT) LPDA ANTENNAS.....	35
3.5	APPLICATIONS OF THE RESEARCH	36
4	CONCLUSION.....	41
APPENDIX A:	CONVERGENCE CRITERIA FOR LPDA ANTENNAS.....	44
APPENDIX B:	THE EFFECT OF BOOM-IMPEDANCE ON GAIN.....	61
APPENDIX C:	EFFECT OF LENGTH TO DIAMETER RATIO ON GAIN	64
	REFERENCES.....	68
	BIBLIOGRAPHY	69

LIST OF FIGURES

Figure	Page
1.1 The LPDA Antenna	2
2.1 Plot of real input impedance variation with Frequency, $L=1.5\text{m}$, $N=15$, $\tau = 0.89$ and $\sigma = 0.073$	12
2.2 Plot of imaginary input resistance variation with frequency $N = 15$, $L = 1.5\text{m}$, $\tau = 0.89$ and $\sigma = 0.073$	13
2.3 Variation of VSWR with frequency for fixed values of N	16
2.4 Variation of gain with frequency for fixed values of N	17
2.5 Variation of radiation pattern with changing N	17
3.1 Plot of the variation of average gain with number of elements for fixed boom-lengths and changing operating bandwidths	22
3.2 Average gain as a function of number of elements for fixed values of boom-lengths and changing operating bandwidths	23
3.3 Variation of Number of element with scale factor (τ) for fixed boom-lengths and changing operating bandwidths	24
3.4 Variation of Number of elements with scale factor for fixed boom- lengths and changing operating bandwidths	24
3.5 Number of element variation with scale factor for fixed boom- length and changing operating Bandwidths	25
3.6 Number of element variation with scale factor for fixed boom- length and changing operating Bandwidths	25
3.7 Number of element variation with space constant (σ) for fixed boom-length and changing operating bandwidths	26
3.8 Number of element variation with space constant for fixed boom- length and changing operating bandwidths	26
3.9 Number of element variation with space constant for fixed boom- lengths and changing operating bandwidths	27

3.10	Number of element variation with space constant for fixed boom-lengths and changing operating bandwidths.....	27
3.11	Variation of the space constant with scale factor for fixed boom-length and changing operating bandwidths	28
3.12	Variation of space constant with scale factor for fixed boom-length and changing operating boom-lengths.....	28
3.13	Convergent pair of $[N, G]$ for values of operating bandwidth neglecting the effects of 'L'	31
3.14	Convergent pair of $[G, L]$ for changing values of operating bandwidth neglecting the effects of 'N'.....	32
3.15	Convergent pair of $[N, L]$ for changing values of operating bandwidth.....	33
3.16	Effect of boom-impedance (Z_o) on the gain of convergent LPDA antennas.....	34
3.17	Effect of boom-impedance (Z_o) on the gains of convergent LPDA Antennas	34
3.18	Variation of average gain with length to diameter (L_n/D_n) ratio for optimised LPDA Antennas	35
3.19	Variation of average gain with length to diameter ratio for convergent LPDA Antennas	36

LIST OF TABLES

Table	Page
2.1	Values of measured and simulated results for the six models of antenna built.....11
2.2	Trends in pattern of variation of VSWR and gain for fixed values of N , for LPDA Antenna of $L = 1.5\lambda_{\max}$, $B = 1:5$18
3.1	Convergent LPDA Antennas30