

https://dspace.org/

Characteristics of the log periodic dipole array

Onwuegbuna, Leonard Ikemefuna

2007-02-28T13:01:19Z
http://hdl.handle.net/10539/2164

Downloaded from a DSpace repository. https://dspace.org/

TABLE OF CONTENTS

DECLARATION ii
SIGNATURE OF CANDIDATE ii
ABSTRACT viii
DEDICATION x
ACKNOWLEDGEMENTS xi

1 INTRODUCTION 1

1.1 STATEMENT OF THE PROBLEM 3
1.2 JUSTIFICATION 5
1.3 APPROACH TO SOLVING THE PROBLEM 6
1.4 LIMITATIONS OF THE RESEARCH 7
1.5 DOCUMENT OVERVIEW 8

2 METHODOLOGIES 9

2.1 EXPERIMENTAL VERIFICATION OF THE NUMERICAL MODEL 9
2.1.1 THE EXPERIMENTAL SITUATION 10
2.1.2 RESULTS: MEASURED VERSUS THEORETICAL 10
2.2 CONVERGENT (OPTIMIZED) AND SPARSE LPDA ANTENNAS 13
2.2.1 CONVERGENCE (OR OPTIMISATION) CRITERIA FOR LPDA ANTENNAS 20

3 RESULTS 22

3.1 PROBABLE GAIN PERFORMANCE CHARACTERISTICS OF LPDA ANTENNAS (CONVERGENT/SPARSE) 22
3.2 CONVERGENT (OR OPTIMISED) LPDA ANTENNAS 29
3.3 THE EFFECT OF BOOM-IMPEDANCE (Z_o) ON THE GAIN PERFORMANCE OF OPTIMISED (OR CONVERGENT) LPDA ANTENNAS 33
3.4 EFFECT OF LENGTH TO DIAMETER (L_n/D_n) RATIO ON THE GAIN PERFORMANCE OF

OPTIMISED (OR CONVERGENT) LPDA ANTENNAS 35
3.5 APPLICATIONS OF THE RESEARCH 36

4 CONCLUSION 41

APPENDIX A: CONVERGENCE CRITERIA FOR LPDA ANTENNAS 44
APPENDIX B: THE EFFECT OF BOOM-IMPEDANCE ON GAIN 61
APPENDIX C: EFFECT OF LENGTH TO DIAMETER RATIO ON GAIN 64

REFERENCES 68

BIBLIOGRAPHY 69

LIST OF FIGURES

Figure		Page
1.1	The LPDA Antenna	2
2.1	Plot of real input impedance variation with Frequency, L=1.5m, N=15, $\tau = 0.89$ and $\sigma = 0.073$	12
2.2	Plot of imaginary input resistance variation with frequency N = 15, L = 1.5m, $\tau = 0.89$ and $\sigma = 0.073$	13
2.3	Variation of VSWR with frequency for fixed values of N	16
2.4	Variation of gain with frequency for fixed values of N	17
2.5	Variation of radiation pattern with changing N	17
3.1	Plot of the variation of average gain with number of elements for fixed boom-lengths and changing operating bandwidths	22
3.2	Average gain as a function of number of elements for fixed values of boom-lengths and changing operating bandwidths	23
3.3	Variation of Number of element with scale factor (tau) for fixed boom-lengths and changing operating bandwidths	24
3.4	Variation of Number of elements with scale factor for fixed boom-lengths and changing operating bandwidths	24
3.5	Number of element variation with scale factor for fixed boom-length and changing operating Bandwidths	25
3.6	Number of element variation with scale factor for fixed boom-length and changing operating Bandwidths.	25
3.7	Number of element variation with space constant (σ) for fixed boom-length and changing operating bandwidths	26
3.8	Number of element variation with space constant for fixed boom-length and changing operating bandwidths.	26
3.9	Number of element variation with space constant for fixed boom-lengths and changing operating bandwidths.	27

3.10 Number of element variation with space constant for fixed boom-lengths and changing operating bandwidths. 27
3.11 Variation of the space constant with scale factor for fixed boom-length and changing operating bandwidths 28
3.12 Variation of space constant with scale factor for fixed boom-length and changing operating boom-lengths 28
3.13 Convergent pair of [N, G] for values of operating bandwidth neglecting the effects of 'L' 31
3.14 Convergent pair of [G, L] for changing values of operating bandwidth neglecting the effects of 'N' 32
3.15 Convergent pair of [N, L] for changing values of operating bandwidth....33
3.16 Effect of boom-impedance (Z_o) on the gain of convergent LPDA antennas....34
3.17 Effect of boom-impedance (Zo) on the gains of convergent LPDA Antennas 34
3.18 Variation of average gain with length to diameter (Ln/Dn) ratio for optimised LPDA Antennas 35
3.19 Variation of average gain with length to diameter ratio for convergent LPDA Antennas 36

LIST OF TABLES

Table		Page
2.1	Values of measured and simulated results for the six models of antenna built	11
2.2	Trends in pattern of variation of VSWR and gain for fixed values of N, for LPDA Antenna of L = 1.5λ_{max}, B =1:5	18
3.1	Convergent LPDA Antennas	30