

https://dspace.org/

The investigation of filter sands and the establishment of a criterion for the condition that a sand is a filter in itself

Blight, Geoffrey Eustace

2015-01-09
http://hdl.handle.net/10539/16311

Downloaded from a DSpace repository. https://dspace.org/

Sand	$\frac{G-1}{1+e}=b$	d CM.	k CM x10^{-3} SEC^{-1}	μ Poise x10^{-3}	$\pi_1 = \frac{b.\gamma_w.dk}{\mu}$	k^2 x 10^{-6}	i	$\pi_2 = \frac{d.i}{b.k^2}$ x10^{-6}
Artificial Sand No. 1	1.101	0.0307	3.49	12.1	.00976	12.2	14.1	.0322
	1.107		3.64	11.6	.0107	13.2	14.2	.0299
			3.74	11.8	.0108	14.0		.0282
			3.84	11.8	.0111	14.7		.0268
			3.92	11.8	.0113	15.3		.0258
			3.93	11.7	.0114	15.4		.0256
			4.04	11.8	.0116	16.3		.0242
			4.02	11.7	.0117	16.1		.0245
			4.05	11.7	.0118	16.4		.0240
			4.05	11.7	.0118	16.4		.0240
			4.03	11.6	.0117	16.2		.0243
			4.05	11.6	.0118	16.4		.0240
			3.95	11.6	.0115	15.6		.0253
			3.89	11.6	.0113	15.1		.0261

VALUES OF THE CONSTANT "n'" IN THE GENERAL RELATIONSHIP FOR THE FLOW OF WATER THROUGH SOILS

viz: $\pi_1 = a\pi_2^{-(n'+p)}$

Sand	Value of n'	$n'-\bar{n}'$	$(n'-\bar{n}')^2$
Crusher Sand 'A'	0.555	0.029	0.00084
E.R.P.M. Ash	0.505	-0.021	0.00044
E.R.P.M. Dump Sand	0.566	0.040	0.00160
Artificial Sand No. 1	0.430	-0.096	0.00918
Crusher Sand 'B'	0.577	0.051	0.00259
	2.633		0.01465

$\bar{n}' = \frac{2.633}{5} = 0.526$ $\qquad \hat{\sigma}_{n'}^2 = \frac{0.01465}{4} = 0.00366$

n' lies between $\bar{n}' \pm t_{(.95,\ 4)}\ \hat{\sigma}_{n'}/\sqrt{5}$ with 95% confidence

n' lies between $0.526 \pm \frac{2.78 \times 0.0606}{2.24}$

n' lies between 0.526 ± 0.075 with 95% confidence

SPECIFIC SURFACE AREA - AREA UNDER GRADING CURVE CORRELATION

Sand	x_1 MM.	x_2 MM.	C %	m+1	m
E.R.P.M. Ash	0.080	5.00	7.5	4.04	3.04
Crusher Sand 'A'	0.30	1.60	3.8	1.58	0.58
E.R.P.M. Dump Sand	0.033	0.170	0.43	0.639	-0.361
Bartlett's Pit Sand	0.050	0.600	9.4	1.86	0.86
Cullinan Sand	0.130	0.500	0.55	0.870	-0.130
Van Ryn Sand	0.084	1.300	0.31	0.926	-0.074
Decomposed Sandstone	0.300	5.00	11.2	3.14	2.14
Witbank Sand	0.070	0.300	0.86	0.781	-0.219
Witdeep Crusher Sand	0.150	2.00	5.8	2.31	1.31

$\frac{6(m+1)}{\rho m}$ a	x_2^m	x_1^m	$x_2^m - x_1^m$ b	x_2^{m+1}	x_1^{m+1}	$x_2^{m+1} - x_1^{m+1}$ c	$\frac{b}{c}$	$\frac{a.b}{c}$ $S_{x_1x_2}$ MM^2/GM	Area Under Grading Curve x_1 to x_2 CM^2
				670	-	670	0.199	633	38.9
3,190	133	.00056	133	670	0.149	1.952	0.417	2,540	29.6
6,080	1.313	0.498	0.815	2.101	0.113	0.209	-7.32	28,900	5.9
-3,950	1.896	3.43	-1.53	0.322	0.0038	0.419	1.355	6,660	28.2
4,920	0.644	0.076	0.568	0.413	0.169	0.378	-0.555	8,420	8.1
-15,160	1.094	1.304	-0.210	0.547	0.106	1.169	-0.188	5,540	8.7
-29,410	0.981	1.201	-0.220	1.275	0.0212	157	0.1994	668	38.3
3,300	31.4	0.0761	31.3	157	0.125	0.265	-1.850	15,110	12.1
-8,170	1.301	1.791	-0.490	0.390	0.0125	4.94	0.485	1,911	21.7
3,940	2.479	0.0834	2.396	4.93					

Calculation of Correlation Coefficient and Line of Best Fit

(i) $S_{x_1x_2}$

$S_{x_1x_2}$ CM^2/GM	$\text{Log}_{10} S_{x_1x_2}$ s	$s-\bar{s}$	$(s-\bar{s})^2$
6.33	0.801	-0.804	0.641
25.40	1.405	-0.200	0.040
289.0	2.461	0.856	0.729
66.60	1.820	0.215	0.046
84.20	1.926	0.321	0.102
55.40	1.743	0.138	0.019
6.68	0.825	-0.780	0.620
151.10	2.180	0.575	0.329
19.11	1.282	-0.323	0.104
	14.443		2.630

$\bar{s} = \frac{14.443}{9}$

$\bar{s} = 1.605$

$S_s^2 = \frac{2.630}{8}$

$S_s^2 = 0.329$

$S_s = 0.574$

(ii) $A_{x_1x_2}$

$A_{x_1x_2}$ CM^2	$\text{Log}_{10} A_{x_1x_2}$ a	$a-\bar{a}$	$(a-\bar{a})^2$	$(a-\bar{a})(s-\bar{s})$
38.9	1.590	0.353	0.124	-0.284
29.6	1.471	0.234	0.055	-0.047
5.9	0.771	-0.466	0.216	-0.400
28.2	1.450	0.213	0.045	+0.046
8.1	0.909	-0.328	0.107	-0.105
8.7	0.940	-0.297	0.088	-0.041
38.3	1.583	0.346	0.119	-0.270
12.1	1.083	-0.154	0.024	-0.089
21.7	1.336	0.099	0.010	-0.032
	11.133		0.788	-1.222

$\bar{a} = \frac{11.133}{9}$

$\bar{a} = 1.237$

$S_a^2 = \frac{0.788}{8}$

$S_a^2 = 0.0985$

$S_a = 0.314$

$S_{ab} = \frac{-1.222}{8}$

$S_{ab} = -0.153$

Correlation Coefficient: $r_{as} = \frac{S_{as}}{S_a . S_s} = \frac{-0.153}{0.574 \times 0.314}$

$r_{as} = -0.850$

Line of Best Fit: $c = \frac{-1.222}{2.630} = -0.465 \quad d = 1.24$

Line of Best Fit: $a = -0.465(s - 1.61) + 1.24$

$a = -0.465s + 1.99$

$\text{Log}_{10} A = -0.465 \text{ Log}_{10} S + 1.99$

$A = 98S^{-0.465}$

Calculation of Correlation Coefficient and Line of Best Fit

(i) $S_{x_1x_2}$

$S_{x_1x_2}$ CM^2/GM	$\text{Log}_{10} S_{x_1x_2}$ s	$s-\bar{s}$	$(s-\bar{s})^2$
6.33	0.801	-0.804	0.641
25.40	1.405	-0.200	0.040
289.0	2.461	0.856	0.729
66.60	1.820	0.215	0.046
84.20	1.926	0.321	0.102
55.40	1.743	0.138	0.019
6.68	0.825	-0.780	0.620
151.10	2.180	0.575	0.329
19.11	1.282	-0.323	0.104
	14.443		2.630

$\bar{s} = \frac{14.443}{9}$

$\bar{s} = 1.605$

$S_s^2 = \frac{2.630}{8}$

$S_s^2 = 0.329$

$S_s = 0.574$

(ii) $A_{x_1x_2}$

$A_{x_1x_2}$ CM^2	$\text{Log}_{10} A_{x_1x_2}$ a	$a-\bar{a}$	$(a-\bar{a})^2$	$(a-\bar{a})(s-\bar{s})$
38.9	1.590	0.353	0.124	-0.284
29.6	1.471	0.234	0.055	-0.047
5.9	0.771	-0.466	0.216	-0.400
28.2	1.450	0.213	0.045	+0.046
8.1	0.909	-0.328	0.107	-0.105
8.7	0.940	-0.297	0.088	-0.041
38.3	1.583	0.346	0.119	-0.270
12.1	1.083	-0.154	0.024	-0.089
21.7	1.336	0.099	0.010	-0.032
	11.133		0.788	-1.222

$\bar{a} = \frac{11.133}{9}$

$\bar{a} = 1.237$

$S_a^2 = \frac{0.788}{8}$

$S_a^2 = 0.0985$

$S_a = 0.314$

$S_{ab} = \frac{-1.222}{8}$

$S_{ab} = -0.153$

Correlation Coefficient: $r_{as} = \frac{S_{as}}{S_a . S_s} = \frac{-0.153}{0.574 \times 0.314}$

$r_{as} = -0.850$

Line of Best Fit: $c = \frac{-1.222}{2.630} = -0.465 \quad d = 1.24$

Line of Best Fit: $a = -0.465(s - 1.61) + 1.24$

$a = -0.465s + 1.99$

$\text{Log}_{10} A = -0.465 \text{ Log}_{10} S + 1.99$

$A = 98S^{-0.465}$

PARTICLE MIGRATION REPRESENTED BY CHANGES IN SPECIFIC SURFACE AREA

INITIAL				FINAL					
$i^{1/3}$	$q^{2/3}$	$\frac{1+e}{G-1}^{4/3}$	σ_i	$i^{1/3}$	$q^{2/3}$	$\frac{1+e}{G-1}^{4/3}$	σ_f	$\sigma_i-\sigma_f$	L CM^2
2.420	3.91	3.22	1.994	2.433	3.43	3.40	2.412	-0.418	-12.2
2.412	3.19	1.081	0.818	2.412	4.40	1.081	0.592	0.226	+3.2
2.409	2.29	1.161	1.227	2.423	2.62	1.155	1.067	0.160	+2.2
2.412	1.99	1.365	1.655	2.519	1.37	1.148	2.110	-0.455	-6.5
2.912	4.17	1.096	0.765	2.934	4.92	1.057	0.629	0.136	+2.1
2.918	4.97	1.186	0.696	2.918	4.77	1.199	0.733	0.037	+0.1
2.441	1.82	1.177	1.579	2.519	1.71	1.042	1.534	0.045	+1.7
2.500	1.72	1.196	1.739	2.556	1.89	1.097	1.484	0.255	+1.0
2.427	1.01	0.983	2.361	2.453	0.881	0.937	2.610	-0.249	-7.8

Calculation of Correlation Coefficient and Line of Best Fit

(i) $\sigma = \sigma_i - \sigma_f$

σ	$\text{Log}_{10}\frac{\sigma}{a}$	$a-\bar{a}$	$(a-\bar{a})^2$
0.418	-0.379	+0.400	0.160
0.226	-0.646	+0.134	0.018
0.160	-0.796	-0.017	0.000
0.455	-0.342	+0.437	0.191
0.136	-0.866	-0.087	0.008
0.037	-1.432	-0.653	0.425
0.045	-1.347	-0.568	0.321
0.255	-0.594	+0.185	0.034
0.249	-0.604	+0.175	0.031
	-7.006		1.188

$$\bar{a} = \frac{-7.006}{9} = -0.779$$

$$s_a^2 = \frac{1.188}{8} = 0.148 \qquad s_a = 0.386$$

(ii) L:

L	Log_{10} L / b	b-$\bar{b}$	$(b-\bar{b})^2$	$(b-\bar{b})(a-\bar{a})$
12.2	1.086	0.732	0.534	0.293
3.2	0.505	0.151	0.023	0.020
2.2	0.342	-0.012	0.000	0.000
6.5	0.813	0.459	0.210	0.200
2.1	0.322	-0.032	0.001	0.002
0.1	-1.000	-1.354	1.838	0.885
1.7	0.230	-0.124	0.015	0.071
1.0	0.000	-0.354	0.125	-0.066
7.8	0.892	0.538	0.289	0.094
	3.190		3.035	1.499

$$\bar{b} = \frac{3.190}{9} = 0.354 \qquad S_{a,b} = \frac{1.499}{8} = 0.187$$

$$S_b^2 = \frac{3.035}{8} = 0.379 \qquad S_b = 0.618$$

Correlation Coefficient: $r_{a,b} = \frac{S_{ab}}{S_a \cdot S_b} = \frac{0.187}{0.618 \times 0.386}$

$$r_{a,b} = 0.785$$

Line of Best Fit:

$$c = \frac{1.499}{1.188} = 1.26$$

$$d = 0.354$$

Line of Best Fit:

$$b = 1.26\ (a + 0.779) + 0.354$$

$$b = 1.26a + 1.337$$

$$\text{Log}_{10} L = 1.26\ \text{Log}_{10}\ (\sigma'_1 - \sigma'_f) + 1.337$$

$$L = 21.8\ (\sigma'_1 - \sigma'_f)^{1.26}$$

LIST OF REFERENCES

1. BERTRAM, G.E. "An Experimental Investigation of Protective Filters" Soil Mechanics Series No.7, Harvard University.

2. KARPOFF, K.P. "The Use of Laboratory Tests to Develop Design Criteria for Protective Filters" Proc. 58th Annual Meeting, A.S.T.M. 1955.

3. MUSKAT, M. "The Flow of Homogeneous Fluids Through Porous Media" McGraw-Hill, 1937.

4. RATCLIFFE. Proc. Inst. Mech. Eng.,V.162, N.378, 1950.

5. ANON. "Field and Laboratory Investigation of Design Criteria for Drainage Wells" T.M. 195-1., U.S.B.R.

Author Blight Geoffrey Eustace
Name of thesis The Investigation Of Filter Sands And The Establishment Of A Criterion For The Condition That A Sand Is A Filter In Itself. 1958

PUBLISHER:
University of the Witwatersrand, Johannesburg
©2013

LEGAL NOTICES:

Copyright Notice: All materials on the University of the Witwatersrand, Johannesburg Library website are protected by South African copyright law and may not be distributed, transmitted, displayed, or otherwise published in any format, without the prior written permission of the copyright owner.

Disclaimer and Terms of Use: Provided that you maintain all copyright and other notices contained therein, you may download material (one machine readable copy and one print copy per page) for your personal and/or educational non-commercial use only.

The University of the Witwatersrand, Johannesburg, is not responsible for any errors or omissions and excludes any and all liability for any errors in or omissions from the information on the Library website.