

Reference

References.

Arcement G.J., Jr. and V.R. Schneider, (1989) USGS “Guide for Selecting Manning's Roughness Coefficients for Natural Channels and Flood Plains” U.S. Geological Survey Water Supply paper no. 2339, U.S. Government Printing Office, Washington, D.C.

Baiamonte, G., and V. Ferro (1997), “The influence of roughness geometry and Shields parameter on flow resistance in gravel-bed channels”, *EarthSurf. Processes Landforms*, 22, 759–772.

Barnes, H. H., Jr., (1967), “Roughness characteristics of natural channels”: U. S. Geol. Survey Water-Supply Paper, 1849, 213 p.

Bazin, H. E., (1865), *Recherches hydrauliques*, “Memoires presentes par devers savants, science mathematiques et physiques”: Paris, ser. 2, V. 19.

Canovaro, F., E. Paris, and L. Solari (2007), “Effects of macro-scale bed roughness geometry on flow resistance”, *Water Resource. Res.*, 43, W10414, doi: 10.1029/2006WR005727

Chanson, H. (1994), “Hydraulic Design of Stepped Cascades, Channels, Weirs and Spillways”, 261 pp., Pergamon, Oxford, U. K.

Chanson, H., and L. Toombes (2002), “Experimental investigations of air entrainment in transition and skimming flows down a stepped chute”, *Can. J. Civ. Eng.*, 29(1), 145–156.

Chartrand, S. M., and P. J. Whiting (2000), “Alluvial architecture in headwater streams with special emphasis on step-pool topography”, *Earth Surf.: Processes Landforms*, 25, 583–600.

Reference

Church, M., and A. Zimmerman (2007), “Form and stability of step-pool channels”: Research progress, *Water Resour. Res.*, 43, W03415, doi: 10.1029/2006WR005037.

Comiti, F., A. Andreoli, L. Mao, and M. A. Lenzi (2008), “Wood storage in three mountain streams of the Southern Andes and its hydro-morphological effects, *Earth Surf*”. *Processes Landforms*, 33, 244–262, doi: 10.1002/ esp.1541.

Comiti, F., D. Cadol, and E. Wohl (2009), “Flow regimes, bed morphology, and flow resistance in self-formed step-pool channels”, *Water Resources.*, 45, W12804, doi:10.1029/2010WR009699.

Cowan, W.L., (1956), “Estimating hydraulic roughness coefficients”: *Agricultural Engineering*, v. 37, no. 7, p. 473-475

Curran, J. H., and E. E. Wohl (2003), Large woody debris and flow resistance in step-pool channels, Cascade Range, Washington, *Geomorphology*, 51, 141–157.

Darcy, H. P., (1854), “Sur des recherches experimentales relatives au mouvement des eaux dans les tuyaux”. (Experimental researches on the flow of water in pipes.) : *Acad. Sci. Comptesrendus*, v. 38, p. 1109-1121.

David, G. C. L., E. Wohl, S. E. Yochum, and B. P. Bledsoe (2011), “Comparative analysis of bed resistance partitioning in high-gradient streams”, *Water Resour. Res.*, 47, W07507, doi:10.1029/2010WR009540.pp1-22.

Reference

Depue, P.M. 1996. Variation of Manning's Roughness coefficient with Changes in Channel Geometry and Roughness Pattern. M.S. Thesis. Department of Civil Engineering, University of Illinois at Urbana-Champaign.

Einstein, H. A., and N. L. Barbarossa (1952), "River channel roughness", *Trans. Am. Soc. Civ. Eng.*, 117, 1121–1146.

Felkel, K. (1960). "Gemessene Abflüsse in Ginnen mit Weidenbewuchs. Mitteilungen der" BAW, Heft 15, Karlsruhe, German. (Cited from Yen, 1992b)

Ferguson, R. I. (2007), "Flow resistance equations for gravel- and boulderbed streams", *Water Resour. Res.*, 43, W05427, doi:10.1029/2006WR005422.

Ferguson, R. I. (2010), "Time to abandon the Manning equation?" *Earth Surf. Processes Landforms*, 35, 1873–1876.

Ferro, V. (2003), "Flow resistance in gravel-bed channels with large-scale roughness", *Earth Surf. Processes Landforms*, 28, 1325–1339, doi:10.1002/esp.589.

Gippel, C. J., I. C. O'Neill, and B. L. Finlayson (1992), "The Hydraulic Basis for Snag Management", Centre for Environmental Applied Hydrology, Department of Civil and Agricultural Engineering, University of Melbourne, Melbourne, Vic., Australia, 116 p.

Gippel, C. J., B. L. Finlayson, and I. C. O'Neill (1996), "Distribution and hydraulic significance of large woody debris in a lowland Australian river", *Hydrobiologia*, 318, 179–194.

Reference

Griffiths, G. A. (1989), “Form resistance in gravel channels with mobile beds”, *J. Hydraul. Eng.*, 115, 340–355.

Herschel, Clemens, (1897), “On the Origin of the Chezy formula and discussions” : Assoc. Eng. Soc. Jour., Jan.-June 1897, v. 18, p. 363-369.

Hirschowitz, P.M., James, C.S. (2009). Conveyance estimation in channels with emergent bank vegetation, *Water SA*, 35(5), 607-613.

Horton R.E (1933) “Separate roughness coefficient for channel bottom and sides”
Engineering News-Record Vol.111 No. 22 pg 652-653

HR Wallingford. (2004). Reducing uncertainty in river flood conveyance, Phase 2, Conveyance Manual. Defra/Environment Agency Project W5A-057, United Kingdom.

Hygelund, B., and M. Manga (2003), “Field measurements of drag coefficients for model large woody debris”, *Geomorphology*, 51, 175–185.

James, C.S (2012). “Partitioned resistance in channels with large emergent roughness elements”, School of Civil & Environmental Engineering, University of the Witwatersrand, Private Bag 3, Wits, 2050, South Africa.

James,C.S, A. A. Jordanova (2010) “Reach-Scale Resistance of Distributed Roughness in Channels” *River Flow 2010 - Dittrich, Koll, Aberle&Geisenhainer (eds) - © 2010 Bundesanstalt für Wasserbau* ISBN 978-3-939230-00-7 pp333-339

Reference

James, C.S., Goldbeck, U.K., Patini, A., Jordanova, A.J. (2008). “Influence of foliage on flow resistance of emergent vegetation”, *Journal of Hydraulic Research*, 46(4), 536-542.

James, C.S., Makoa, M. J. (2006). “Conveyance estimation for channels with emergent vegetation boundaries”, *Proceedings of the Institution of Civil Engineers, Water Management*, 159(WM4), 235-243.

Jarrett, R. D. (1984), “Hydraulics of high-gradient streams”, *J. Hydraul. Eng.*, 110(11), 1519–1539.

Kaiser, W. (1984). “Fließwiderstandsverhalten in Gerinnenmitdurchströmten Ufergehölzzonen”. *Wasserbau-Mitteilung der Technischen Hochschule Darmstadt*, Darmstadt, Germany, Vol. 23.

Keulegan, G. H. (1938), Laws of turbulent flow in open channels, *J. Res. Natl. Bur. Stand.*, 21, 707–741.

Lee, A. J., and R. I. Ferguson (2002), “Velocity and flow resistance in step pool streams”, *Geomorphology*, 46, 59–71.

Limerinos, J. T. (1970), “Determination of the Manning coefficient for measured bed roughness in natural channels”, *U.S. Geol. Surv. Water Supply Pap. 1898-B*, U.S. Geol. Surv., Washington, D. C.

Reference

Lotter, G.K (1933). “Consideration on hydraulic design of channels with different roughness of walls”. Transactions, All-Union scientific Research Institute of Hydraulic Engineering, Vol.9 Leningrad, Russia, pp238-241.

Magirl, C. S., J. W. Gartner, G. M. Smart, and R. H. Webb (2009), “Water velocity and the nature of critical flow in large rapids on the Colorado River, Utah”, *Water Resource. Res.*, 45, W05427, doi: 10.1029/ 2009WR007731.

Maxwell, A. R., and A. N. Papanicolaou (2001), “Step-pool morphology in high-gradient streams”, *Int. J. Sediment Res.*, 72, 99–108.

Meile, T., Boillat, J.-L., and Schleiss, A. J. (2011). “Water surface oscillations in channels with axi-symmetric cavities.” *J. Hydraul. Res.*, 49(1), 73–81.

Millar, R. G. (1999), “Grain and form resistance in gravel-bed rivers”, *J. Hydraul. Res.*, 37, 303–312.

Millar, R. G., and M. C. Quick (1994), “Flow resistance of high-gradient gravel channels”, in *Hydraulic Engineering '94 ASCE*, edited by G. V. Cotroneo and R. R. Rumer, pp. 717–721, Buffalo, N. Y.

Montgomery, D. R., and J. M. Buffington (1997), “Channel-reach morphology in mountain drainage basins”, *Geol. Soc. Am. Bull.*, 109, 596–611.

Morris, H. M., and Wiggert, J. M. (1972). “Applied hydraulics in engineering”, Ronald Press, New York.

Reference

Nelson, J. M., S. R. McLean, and S. R. Wolfe (1993), “Mean flow and turbulence fields over two-dimensional bed forms”, *Water Resour. Res.*, 29, 3935–3953, doi: 10.1029/93WR01932.

Pagliara, S., and P. Chiavaccini (2006), “Flow resistance of rock chutes with protruding boulders”, *J. Hydraul. Eng.*, 132, 545–552.

Parker, G., and A. W. Peterson (1980), “Bar resistance of gravel-bed streams”, *J. Hydraul. Div. Am. Soc. Civ. Eng.*, 106, 1559–1573.

Pavlovskii, N.N.(1931). “On a design formula for uniform movement in channels with nonhomogeneous walls”. Transactions, All-Union Scientific Research Institutes of Hydraulic Engineering, Vol.4, Leningrad, Russian, pp..157-164.

Prestegard, K. L. (1983), “Bar resistance in gravel bed streams at bankfull stage”, *Water Resource. Res.*, 19(2), 472–476, doi:10.1029/WR019i002p 00472.

Rouse, H. (1965), “Critical analysis of open-channel resistance”, *J. Hydraul. Div. Am. Soc. Civ. Eng.*, 91, 1–25.

Rouse, Hunter, and Ince, Simon, (1957), “History of hydraulics”: Iowa City, Iowa, Inst. Hydraulic Research, 269 p.

Shields, F. D., Jr., and C. J. Gippel (1995), “Prediction of effects of woody debris removal on flow resistance”, *J. Hydraulic. Eng.*, 121, 341–354.

Reference

Strickler, A. (1923). “Beitrage zur Frage der Geschwindigkeits-formel und der Rauhigkeitszahlen für strome”, Kanäle und geschlossene Leitungen [Some Contributions to the problems of the velocity formula and roughness factor for the rivers, canal and closed conduits. Mitteilungen des Eidgenössischen Amtes für Wasserwirtschaft nr.16

Tobias Meile; Jean-Louis Boillat; and Anton J. Schleiss (2011) “Flow resistance caused by Large –Scale Bank Roughness in a Channel” *Journal of hydraulic engineering* © asce pp1589-1590.

Wallerstein, N. P., C. V. Alonso, S. J. Bennett, and C. R. Thorne (2002), “Surface wave forces acting on submerged logs”, *J. Hydraulics. Eng.*, 128, 349–353.

Whatmore, S.J. and Landström, C. 2010 “Manning's n – Putting Roughness to Work “Cambridge University Press 111-135.

Young, W. J. (1991), Flume study of the hydraulic effects of large woody debris in lowland rivers, *Reg. Rivers Res. Manage.*, 6, 203–211.

Zimmerman, A. (2010), “Flow resistance in steep streams”: An experimental study, *Water Resour. Res.*, 46, W09536, doi: 10.1029/2009WR007913.

Zimmerman, A., and M. Church (2001), “Channel morphology, gradient profiles and bed stresses during flood in a step-pool channel”, *Geomorphology*, 40, 311–327.