

https://dspace.org/

Optimization of biodiesel production from waste cooking oil using a membrane reactor

Moyo, Langa B

2015-05-07
http://hdl.handle.net/10539/17677

Downloaded from a DSpace repository. https://dspace.org/

Optimization of Biodiesel production from waste cooking oil using a membrane reactor

Langa B Moyo

A research report submitted to the Faculty of Engineering and the Built Environment, University of the Witwatersrand, Johannesburg, in partial fulfilment of the requirements for the degree of Master of Science in Engineering

Johannesburg, 2014

DECLARATION

I declare that this report is my own unaided work, unless otherwise stated. It is being submitted to the Degree of Master of Science to the University of the Witwatersrand, Johannesburg. It has not been submitted before for any degree or examination to any other University.

_____

Langa B Moyo

23th day of June year 2014

Acknowledgements

My Supervisors, Prof Sunny Iyuke and Prof Aoyi Ochienga, for their insightful supervision and support which were outstanding to this study. Dr Daramola, for providing the membrane reactor and other necessary equipment for the experiments. Bavon Nkazi, for assisting with procurement of the chemicals for the experiment. Nikita Ranchod and Symon Grewan, for the detailed research on biodiesel production from waste cooking oil during their fourth year research project. CHIETA, for providing the financial resources for undertaking the study

Abstract

In view of the growing concerns over depleting energy resources, alternative renewable fuels such as biodiesel have been identified as a possible means of addressing the short fall in energy supply. The source of feedstock for biodiesel production has been an ongoing debate and waste cooking oil is seen as an ideal feedstock as it can be sourced from restaurants, schools, industry and homes unlike vegetable oils which are part of the food chain. The process of biodiesel production has been vastly studied and the use of membrane reactors has been identified as a viable option. The need to obtain biodiesel of high quality at minimal cost has driven the idea of using membrane reactors, which have the advantage of combining reaction and separation simultaneously.

In this work, design and optimization studies were conducted to the efficiency of the membrane reactor for commercial small scale production of biodiesel from waste cooking oil. A process was developed to simultaneously overcome the shortcomings of waste cooking oil and the use of homogenous catalysts with the aid of membrane technology and heterogeneous catalysts. Tax laws in South Africa encourage small batch scale production of biodiesel. Therefore, the aim of this study is to apply and optimize biodiesel production from waste cooking oil, on a small-scale production level using a membrane reactor and heterogeneous catalyst coupled with a pretreatment stage.

The pretreatment of waste cooking oil was effective in reducing the free fatty acid content to desired levels so as to avoid the saponification side reaction which hinders the effectiveness of the desired trans-esterification reaction. The yield of biodiesel upon reusing the catalyst was high and satisfactory. It is suggested to investigate the reusability of the catalyst further as only two runs did not show a significant change in the yield of biodiesel.

The central composite method of response surface methodology was utilized to investigate the effect of reaction temperature, catalyst concentration and circulation flow rate on biodiesel yield and also obtain the optimal operating conditions. A micro porous membrane packed with KOH catalyst adsorbed on activated carbon was used for the transesterification reaction. The reaction was allowed to continue for a fixed time of 60 minutes and a methanol to oil molar ratio of 23:1. Upon optimization, a biodiesel yield of 94.03 mol % was obtained at a temperature of 58.5 ℃, circulation flow rate of 18.78 ml/min and catalyst concentration of 1.24 wt %.