

Software Support for a Hand-held Bird Identification Aid

Victor Orooji-Heravi

A project report submitted to the Faculty of Engineering, University of the
Witwatersrand, Johannesburg, in partial fulfilment of the requirements for
the degree of Master of Science in Engineering

Johannesburg 1990

DECLARATIONS

I declare that this dissertation is my own, unaided work. It is being submitted for partial fulfillment in the Degree of Master of Science in Engineering in the University of the Witwatersrand, Johannesburg. It has not been submitted before for any degree or examination in any other university.

Sinter Orogj 17/10/90

ABSTRACT

In view of the recent breakthroughs in memory chips, electronic fieldguides are becoming more feasible, specially when they offer better portability and faster information access when compared to conventional fieldguides. In this report we discuss the importance of inexpensive electronic fieldguides which at the same time provide suitable user interface for maximum information transfer. The implications of software architecture are discussed during the course of designing the software model of a bird identifier fieldguide. This model is used to evaluate the behavioral performance and effectiveness of the user interface; both of which play a vital role in establishing the cost of the device. These observations are brought together in conclusion, where the potential role of electronic fieldguides in the domain of education and science are highlighted.

ACKNOWLEDGMENTS

I wish to express my gratitudes to my supervisor, Prof. A.J. Walker for his continuous support and encouragement during the course of this study.

<u>CONTENTS</u>	<u>Page</u>
DECLARATION	ii
ABSTRACT	iii
ACKNOWLEDGMENTS	iv
CONTENTS	v
LIST OF FIGURES	vii

1 APPLICATION OF ELECTRONIC FIELDGUIDES

1.1	Background	1
1.2	Objectives	3
1.3	The Challenge of Bird Identification	4
1.4	Summary	5

2 THE BIRD IDENTIFIER FIELDGUIDE

2.1	The Task at Hand	6
2.2	Architectural Design Strategy	7
2.3	Behavioral Specifications	9
2.4	Technical Specifications	11
2.4.1	Display Unit	13
2.4.2	Keyboard	14
2.4.2.1	Navigation Keys	16
2.4.2.2	Function Keys	16
2.5	Summary	17

3 DETAILED BEHAVIORAL DESCRIPTIONS

3.1	Introduction	18
3.2	Attributes Main Menu	18
3.2.1	Key Behavior in 'Attribute Main Menu'	20
3.3	Attribute Sub-Menus	21
3.3.1	Key Behavior in 'Attribute Sub-Menus'	22
3.4	Utilities Menu	23
3.4.1	Key Behavior in 'Utilities Menu'	24
3.5	Find Main Menu	25
3.5.1	Key Behavior in 'Find Main Menu'	26
3.6	Find Sub-Menus	27
3.6.1	List Found Birds	27
3.6.1.1	Key Behavior in 'List Found Birds'	27
3.6.2	Clear All Found Birds	29
3.6.2.1	Key Behavior in 'Clear All Found Birds'	29
3.6.3	List Attributes	30
3.6.3.1	Key Behavior in 'List Attributes'	30
3.6.4	Clear All Attributes	32
3.6.4.1	Key Behavior in 'Clear All Attributes'	32
3.6.5	List Matched Birds	33
3.6.5.1	Key Behavior in 'List Matched Birds'	33
3.6.6	Bird Count	34
3.6.6.1	Key Behavior in 'Bird Count'	35
3.6.7	Information on Bird	36
3.6.7.1	Key Behavior in 'Information on Bird'	36
3.6.8	Bird Image	37

3.6.8.1	Key Behavior in 'Bird Image'	37
3.6.9	Bird Call	38
3.7	Help Menu	38
3.8.1	Key Behavior in 'Help Menu'	38
3.9	Overview of The Bird Identifier Functions	39

4 ARCHITECTURAL DESIGN

4.1	Introduction	41
4.2	Process/Resource Implementation of Object-Oriented Design	42
4.3	Awareness of Design Level and Documentation	43
4.4	First-Level Design	44
4.5	Second-Level Design	46
4.5.1	The Attribute Process	46
4.5.2	The Find Process	48
4.6	Third-Level Design	50
4.6.1	System Processes	51
4.6.1.1	The Scheduler Process	51
4.6.1.2	The Help Process	52
4.6.1.3	Find Main Menu Process	53
4.6.1.4	List Found Birds Process	54
4.6.1.5	Clear Found Birds Process	56
4.6.1.6	List Attributes Process	57
4.6.1.7	Clear Attributes Process	59
4.6.1.8	Count Birds Process	61
4.6.2	System Resources	63
4.6.2.1	The Screen Resource	63
4.6.2.2	The Text Menu Resource	66
4.6.2.3	The Process Queue Resource	69
4.6.2.4	The Scroll Resource	71
4.6.2.5	Bird Database Resource	72
4.7	Summary	75

5- DISCUSSION AND CONCLUSIONS

5.1	Achievements	76
5.2	Implementation	77
5.3	Testing	78
5.4	Impact of Software Engineering Methodology	78
5.4.1	Object-Centered Approach to Design	78
5.4.2	Tool Support	79
5.4.3	Report of Design Cycle Time Scale	80
5.5	Conclusions	81

BIBLIOGRAPHY	82
------------------------	----

APPENDIX. A- LIST OF ATTRIBUTE SUB-MENUS	83
--	----

APPENDIX. B- PDL DOCUMENTATION OF THE BIRD IDENTIFIER	89
---	----

APPENDIX. C- LIST OF MODULES AND CODE SIZE	200
--	-----

LIST OF FIGURES

<u>FIGURE</u>	<u>Page</u>
2.1- Display unit of the bird identifier and it's allocated window segments	14
2.2- Depicted figure of the hand-held bird identifier	17
3.1- Attribute Main Menu	18
3.2- A typical display of the Attribute Main Menu	19
3.3- Full graphical description of the Attribute Main Menu	20
3.4- Attribute Sub-menu	21
3.5- A typical display of the Attribute Sub-menu	21
3.6- Full graphical description of the Attribute Sub-menus	22
3.7- Utilities Menu	23
3.8- Full graphical description of the utilities menu	24
3.9- Find Main Menu	25
3.10- A typical display of the Find Menu	25
3.11- Full graphical description of the Find Main Menu	26
3.12- A typical display of List Found Birds	27
3.13- Full graphical description of List Found Birds	28
3.14- A typical display of Clear All Found Birds	29
3.15- Graphical description of Clear All Found Birds	29
3.16- A typical display of the List Attributes	30
3.17- Full graphical description of List Attributes	31
3.18- Graphical description of Clear All Attributes	32
3.19- A typical display of List Matched Birds	33
3.20- Full graphical description of List Matched Birds	34
3.21- A typical display of Bird Count Menu	35
3.22- Full description of the Bird Count Menu	35
3.23- A typical display of the Information on Bird Menu	36

3.24-	Full graphical description of Information on Bird . . .	36
3.25-	Full graphical description of Bird Count Menu	37
3.26-	The graphical description of Bird Call	38
3.27-	Graphical description of the Help Menu	38
3.28-	State transition diagram of the bird Identifier . . .	40
4.1-	The levels of scope from the outside world to the heart of a process/resource system	42
4.2-	First-level description; bird identifier process . . .	45
4.3-	Second-level description; the attribute Process	47
4.4-	Second-level description; the find process	48
4.5-	Third-level description; the scheduler process	52
4.6-	Third-level description; the help process	52
4.7-	Third-level description; find main menu process	53
4.8-	Third-level description; list found birds process . . .	54
4.9-	Third-level description; clear found birds process . .	55
4.10-	Third-level description; list attributes process . . .	57
4.11-	Third-level description; clear attributes process . .	59
4.12-	Third-level description; count birds process	61

CHAPTER 1- APPLICATION OF ELECTRONIC FIELDGUIDES

1.1- BACKGROUND

A fieldguide as the name suggests is a means of providing guidance (knowledge or information) towards the process of making certain field decisions. Field environments are defined by those situations where the means of getting valid information are not favorable. The prevailing of such a situation is due to the lack of one, or several resources:-

- * Convenient access to domain expertise.
- * Efficient communication channel to provide rapid information access.

Depending on the complexity of the subject, fieldguide implementations can vary from a simple chart to a comprehensive manual. Naturally, the value of a fieldguide is directly related to the complexity of the subject, and therefore to the amount of stored information and catered functionality. Fieldguides of major significant are usually implemented in book form, using textual and graphical representations to compile domain expertise. But situations that warrant the use of these fieldguides, involve considerable amount of information processing. This results in two major inadequacies:-

- * Fieldguides become voluminous and inconvenient to carry around.
- * To speed up information retrieval, better communication channels must be catered for. In books this is done by

copying information in several search categories. This redundancy will further increase the size of the book and results in less portability.

Electronic fieldguides access domain expertise electronically. If designed properly, the communication channel can yield much faster information access, when compared to conventional fieldguides. Moreover, recent enhancements in the area of memory capacity[1], make electronic fieldguides more portable. The potential sound/image processing capability of these devices is a further advantage to certain applications, where sound and image information provide the most powerful, and sometimes the only, means of furnishing expert guidance.

Provided the mechanics of the software is completely decoupled from the database that it manages; the electronic fieldguide can readily be fed from a selection of databases to specify it's domain of expertise. Admittedly, due to the diversity of applications, some software adjustments will be necessary to cater for the new functions. But this modification can be minimized by carefully choosing applications that share these functionalities. For instance, all animal identification fieldguides share the size, color, and habitats specifications. But perhaps the most powerful means of employing this type of software-database independency is through database grouping. In other words, the database may be partitioned into several logical groups based on key application areas. For example in the domain of wild flowers one can partition the database into geographical areas such as Europe, Africa or Asia. This

technique can be used to overcome possible memory limitations associated with database storage.

The cost of any product is as important as the function it serves to provide; and fieldguides are no exception to this fact. It is therefore important that the cost of fieldguides be limited to certain feasible boundaries. These boundaries may differ from one application to the next, but it is vital to be aware of this context. The final cost of a fieldguide must be justified in the context of its application.

1.2- OBJECTIVES

The object of the following work is to investigate the feasibility of producing cost effective fieldguides, capable of storing significant size of information. Cost considerations demand that the trailing edge of the leading edge of technology be exploited. Further cost reductions may be achieved through coding techniques which serve to extract maximum technological benefit from available memory devices. However, whilst the issue of memory has great relevance here, this issue is not the theme of this work. The emphasis here is on the functional and architectural impact of the supporting software. The evaluation of this software model will provide the fundamental guidelines and valuable insight into the computational needs; and assessing the effectiveness of the man-machine interface (communication channel). Both the hardware engine and the Man-Machine Interface (MMI) have a profound impact on the cost of the device.

Due to relative availability of in-house expertise in the area of bird identification, this subject forms the environment for developing the envisaged software model. The bird identifier is an application of electronic fieldguides, in the domain of bird recognition and identification.

1.3- THE CHALLENGE OF BIRD IDENTIFICATION

Roberts[2] and Newman[3] are well known fieldguides in the domain of bird identification. They provide the user with comprehensive textual and graphical descriptions of different bird species. The identification process begins with concentrating on the known facts and clues about the cited bird. These initial search conditions help narrow down on the number of candidate species, and therefore speed up the identification process. This exercise, however, is not always trivial, when the database is large. For instance in South Africa alone, as many as 911 species have been registered. In North America this figure is in the order of 435.

Furthermore, amongst some bird species (warblers, pipits, larks) the degree of similarity in appearance is such that the only means of identification is the call sequences that they generate. The absence of visual contact is another situation where the bird call recognition becomes the only route to identification. Examples of such situations are wetlands and forests. Obviously, one can not hope to find any assistance from paper-based fieldguides such as Roberts, when faced with such situations. This type of shortcoming further justifies the need

for electronic fieldguides like the bird identifier. But in spite of the sound reproduction capability, the bird identifier should be viewed as a complementary tool to guides like Roberts, for they still carry a vast amount of detail information.

1.4- SUMMARY

Advantages of electronic fieldguides:-

- * Fast information access
- * Better portablility
- * Sound processing capability
- * Application context may be readily changed by replacing the database.

Guidelines for producing electronic fieldguides:-

- * Inexpensive final device
- * User-friendly communication channel which provides rapid information access.
- * Use of effective coding techniques.
- * Convenient choice of software architecture.

CHAPTER 2- THE BIRD IDENTIFIER FIELDGUIDE

2.1- THE TASK AT HAND

The bird identifier project is in fact a collection of three separate efforts.

- 1) The investigation in efficient methods of coding and storing graphical data.
- 2) The investigation of efficient methods of coding and regeneration of bird calls.
- 3) The producing of a personal computer model to develop and asses the implications of software architecture.

The fact that the first two endeavors are still under investigation, has forced us to restrict the software model to text type information only. As far as the objectives of this work is concerned, this choice will not have a great bearing on our investigations.

In this chapter we will start by discussing the architectural choice of the bird identifier. We will then continue with the system specifications, by considering the general and detailed behavior of the identifier and it's MMI. Although bird image and bird call are not implemented in the final model, for the sake of completeness these facilities will be included during behavioral descriptions.

2.2- ARCHITECTURAL DESIGN STRATEGY

From the point of view of software engineering discipline, software should be designed for the four fundamental goals of modifiability, efficiency, reliability and understandability.

The specifications will describe features and functional properties of the bird identifier which should be adequate in addressing the bird identification exercise. However, this design is regarded as a discovery design, and therefor it is more than likely that other functions and facilities will have to be incorporated to accommodate the features which have been overlooked from the present description. In such a situation where a clear functionality of final system is not realized, it is imperative that modification and growth should readily be absorbed by the software.

While functional decomposition methods provide the powerful and efficient "divide and conquer" notion, they are inherently fragile to change[6,7]. This is because the method gives rise to a hierarchical structure in which changes such as inclusion of new modules or deletion of existing ones, specially in the embedded levels of hierarchy, result in major architectural break-ups.

On the other hand an expert system approach does seem to be a natural solution to the present design. A closer examination of expert system properties will in fact reveal the contrary of this misconception. Expert systems are inherently highly interactive in the sense that almost every initiated activity is quarried in order to bring about user awareness and provide

clarification on the system status. This state of affairs may be convenient to the novice user, but this situation will soon become reversed as a reasonable level of competency is reached. At this stage the user has gained enough experienced to know how to perform a task, and realize it's implications. But the relentless interrogation scheme of the system will constantly get in the way of the user, providing a barrier between the task at hand and system capability. Recalling that fast information access is a prerequisite criteria for defining a fieldguide, it becomes evident that the expert system approach is inconvenient and even detrimental to this application.

In contrast, Object-Oriented Design (OOD) approach to systems design is not bound by such anomalies and it is also highly impervious to modifications[6]. This is because the system is formed from a group of objects that are highly independent and encapsulated, resulting in a flat hierarchy. The issue of modifiability is vital to the survival of the bigger systems and those of discovery designs, where the full behavioral specifications of the system is not clear, initially. In this regard the bird identifier is very much a discovery design, in as much as the full implications of the envisaged system behavior will only become manifest after device has been put into use.

The issue of understandability is also strongly addressed by the OOD approach, since objects directly emulate the real world model, and thus make a great contribution to the undestandability of the system.

Based on these observations it was decided that the OOD strategy was the most suitable architecture for the bird identifier.

2.3- BEHAVIORAL SPECIFICATIONS

Physical characteristics and bird call, form the two major means of bird identification. The bird identifier is a hand-held device that identifies the bird species that satisfy a set of user defined descriptions. The function of the identifier is to provide a set of user selectable features for defining descriptions of the cited bird. These selected features are then compared with the database to provide the user with a list of bird species that match the given descriptions. An example of features (or attributes), is bird size, bird coloring, etc.. A typical session would start by initializing all selected attributes; meaning that the entire database will be available for user inspection. However such a vast list can not possibly be of any help to the identification endeavor. So the user will continue to truncate this list by selecting the noted features of the cited bird. With each subsequent enabling of a feature the list of matched birds will be decreased from the maximum value corresponding to the full database.

Following the completion of the feature selection activity, the user will then initiate a scan and match activity to view the list of bird species that have matched the attributes constraints. In this manner the identification task will be simplified to a case of choosing from a handful of possible species rather than being faced with the entire database of birds.

In order to aid the process of final identification the user can be provided with a graphical description or a playback of the bird call. Once the user has identified the species of interest from the list of matched birds, additional information on other characteristics, such as migration habits, etc. can be furnished.

Other useful functions, such as bird counting, will be incorporated to complement the two main activities of attribute specification, attribute mode, and bird matching, find mode. Later in Section 3.4 we will discuss the role of these complementary functions. In the following Sections the terms features and attributes will be used interchangeably to denote the same bird characteristics.

It is vital that the impact of each attribute selection/deselection; on the number of qualifying species, be available to the user at the earliest possible opportunity. It seems natural to assume that such information should be furnished in the find mode following the scan and match activity. But this would necessitate the invocation of scan and match activity, each time an attribute parameter is changed. To avoid this unwarranted operation it was decided to display and update the number of matched birds, whilst still in the attribute mode. In this way the user is continuously advised of the effectiveness of his attribute selections, without having to view the actual list of matched birds.

2.4- TECHNICAL SPECIFICATIONS

The technical specifications are aimed at providing an acceptable performance (ie. speed of execution), low cost of the device and a simple but effective user interface. As far as the software model is concerned the issue of performance will have to be addressed in the implementation stage. We will therefore proceed to discuss the user interface and it's implications.

In the recent years it has become vividly clear that the user interface (or MMI), constitutes a significant component of a system[4]. In comparing the MMI of operating systems and adventure games, Bernice[5] identifies the following characteristics:-

* Tunnel vision Vs. World vision:

- The vast majority of operating systems are based on textual command-driven interfaces and therefore provide very little information on the system's structure and it's capabilities.
- Through graphics interfaces, adventure games convey a high-level picture of the system's structure and the tasks it supports.

* Rigid syntax Vs. Flexible syntax:

- In the operating systems environments there is no room for flexibility in syntax. There is only one way to issue a command, and it must be phrased just right.
- Adventure games often provide several alternatives for issuing commands. The user is provided with quick command format as well as a relatively longer but more descriptive format.

*** Insensitivity Vs. Context-awareness:**

- In operating systems, insufficient feedback, obscure messages and lack of contextual awareness projects a rather hostile environment to the user.
- Adventure games can play a collaborating role in getting clarification or confirmation from the user. Also in providing information or help to the user the context of the system's activity is considered.

*** Inconsistency Vs. Consistency:**

- Existence of multiple interface styles within the same product, results in confusion and discourages the user. A sever case of inconsistency can ultimately guarantee the failure of a product.
- The creators of adventure games being fully aware of these implications, have taken measures to ensure consistency throughout the package, and in most cases, this consistency has even been carried-out across the vendor products.

*** Copious Documentation Vs. Intrinsic documentation:**

- To compensate for the lack of communication between the system and the user, manuals of substantial volume are written. Generally there is a universal attitude towards the using of these manuals. Users like to start on the basics without having to resort to manuals to perform even the simplest of tasks. They rather spend their valuable time, getting results, and are only prepared to refer to the system manuals when using the more complicated and advanced features of the system.

- Attention to the elements of user interface can make extensive documentation unnecessary. Examples of these interfaces are abundantly available amongst adventure games.

In view of the above observations, conscious effort is made to adopt the MMI concepts of computer games. A key factor in achieving this is the need for graphical capability. Meanwhile to address the issue of cost, severe limitations on the graphical capabilities must be imposed. It was decided to adopt simpler graphics in favor of reducing costs, but at the same context sensitive help would be utilized to alleviate the reduced global vision. This was considered a necessary measure to ensure that the cost of the identifier would remain comparable with other conventional guides such as Robert's book of birds.

2.4.1- DISPLAY UNIT

In the light of our primary object of cost reduction, a modest two line liquid crystal display of twenty characters length is chosen as the display unit.

In order to exploit the full benefit of the display in creating a good MMI, it was partitioned into five windows.

- * W1 is eighteen characters long and serves to indicate the menu headings.
- * W2 window is one character long and is reserved for indicating that the text on window 4 continues to the right.(»)

- * W3 window is one character long and is reserved for indicating that the text on window 4 continues to the left.(«)
- * W4 is twenty characters long. It is the area where the current entry of the menu is written.
- * W5 is of four characters in length. This window normally supports the number of matched birds. It also serves to display the number of found birds when in the 'List Found Birds' Menu; number of selected attributes when in 'List Attributes' menu.




Figure 2.1- Display unit of the bird identifier and it's allocated window segments.

2.4.2- KEYBOARD

An early model of the bird identifier, developed in the department, provided the experience to crystallize other desired functions and a more improved system behavior. In this model a single key was dedicated to each category of features. Our experience from the use of this model showed that the mere abundance of keys, presented a barrier to the user as it was introducing an element of confusion. Furthermore, the growth of the number of attribute categories demanded that more keys be utilized, and therefore served to increase the cost of the device. Based on this experience it was decided to abort such an arrangement in the present model. Instead, a single Select key would serve to access these attribute clusters, through a

hierarchy of menus. A top level menu would support a list of the different available categories of attributes, where the Select key acts to activate the chosen category. In the same way that the Select key will transfer the system's activity down the hierarchy of menus/activities, an Escape key will transfer activity by ascending the hierarchy chain.

In Section 2.3 we identified the find and attribute modes as the two major areas of activity. All other functions may be classified as belonging to one of these two modes. In this regard the identifier may be viewed as performing two parallel but dependent tasks (modes). In the effort of creating an efficient and user-friendly means of switching between these modes, a Mode key was used. The function of the key is to toggle system activity from one mode to the other whilst conserving the context of the suspended activity. This approach will avoid the inherent impediment associated with unwinding nested menus. Thus, the member of the find or attribute mode. Functions associated with each mode are related through a hierarchy structure where the Select and Escape keys are the means of access. The Help key is the last member of the function keys, and provides the relevant explanation as to the behavior of the active function. Finally four keys are dedicated to navigational purposes.

2.4.2.1- NAVIGATION KEYS

- NORTH(^): a) Scrolls up through the menu items. At the first entry, the next depression will wrap around the list to display the last entry.
b) Increments the bird count, when in Bird Count menu.
- SOUTH(v): a) Scrolls down through the menu items. At the last entry, the next depression will wrap around the list to display the first entry.
b) Decrements the bird count, when in the bird Count menu.
- EAST(>): Scrolls a word to the right when displaying texts longer than the display width.
- WEST(<): Scrolls a word to the left when displaying texts longer than the display width.

2.4.2.2- FUNCTION KEYS

- SELECT: a) Provides access to subordinate menus.
b) Toggles an attribute.
c) Produces bird call, when in Bird Call menu
d) Produces bird information, when in Bird Information menu.
e) Zoom in, when in Bird Image menu.
- ESCAPE: a) Provides access to a higher level menu.
b) Aborts an action.
c) Zoom out, when in Bird Image menu.
- HELP: Provides context sensitive help.
- MODE: Provides a means of context switching between the
(A/F) attribute selection and listing of candidate bird species.

Notice that a power key is of no significance to the purposes of the software model, and has therefore been avoided. In fact it was envisaged that the actual device could automatically switch to a low-power standby mode following a predefined lapse of keyboard inactivity. It was decided to include a power-off key so that the context saving of the last active process could be tested upon re-entering the program.

2.5- SUMMARY

The major resolutions of this chapter are listed below:-

- * An Objetc-Centered approach will used for the design of the bird identifier.
- * Cost implications and MMI considerations determine the MMI choice.

Figure 2.2 shows the physical appearance of the identifier. Naturally, as far as the personal computer model is concerned the LCD and the keyboard will be emulated.




Figure 2.2- Depicted figure of the hand-held bird identifier

CHAPTER 3- DETAILED BEHAVIORAL DESCRIPTIONS

3.1- INTRODUCTION

To complete the behavioral specifications of Section 2.3, in this chapter we will describe the detailed behavior of all system activities. Key behaviors in the context of each activity and in relation to neighbouring activities are fully described. finally, these descriptions are brought together to exhibit an overview of the system behavior.

3.2- ATTRIBUTES MAIN MENU

Attribute Main Menu	
1 -	Countries
2 -	National Parks
3 -	Hiking Trails
4 -	Towns and Cities
5 -	Bird Sanctuaries
6 -	Habitats
7 -	Status
8 -	Bird Families
9 -	Size
10 -	Feeding Habits
11 -	Features
12 -	Coloring
13 -	Markings
14 -	Utilities

Figure 3.1- Attribute Main Menu

The attribute main menu supports categories of selectable features, in addition to the utilities menu. Features 1 to 5 form the long term attributes, since they would normally remain unchanged during a bird finding exercise, whilst features 6 to

13 are short termed attributes, in that rapid changes in these features is necessary to bring about final identification.

The utilities menu is a means of defining device features that may be specified by the user, such as response times of the key depressions.

The menu title is listed in window 2 of the display, and the current entry occupies window 4. Figure 3.2 shows a typical example of the display in the attribute menu, where the current menu item is item number 3 "Hiking Trails".

Attribute Menu
3-Hiking Trails

Figure 3.2- A typical display of the Attribute Main Menu

3.2.1- KEY BEHAVIOR IN ATTRIBUTE MAIN MENU

The Escape key is the only key that is not valid in this menu.

The Select key will invoke the attribute sub menus.




Figure 3.3- Full graphical description of the Attribute Main Menu.

- a) Relationship of the Attribute Main Menu and it's sub-menus.
- b) Relationship of the Attribute Main menu and it's help menu.
- c) Mode switching with Attribute Main Menu as the currently active menu.

3.3- ATTRIBUTE SUB-MENUS

The countries sub-menu is shown below as an example. Other sub-menus are listed in Appendix A.

Attribute Sub-Menu (Countries)	
1 -	South Africa and National States
2 -	Lesotho
3 -	Swaziland
4 -	Namibia
5 -	Zimbabwe

Figure 3.4- Attribute Sub-menu of Countries

The display format of this menu is consistent with the main menu, in the sense that the title of the current menu will always occupy the top line on window 1, and the menu item will occupy the bottom line on window 4. This consistency is vital to the M.M.I as discussed in chapter 2; and thus it is upheld throughout the entire design. Figure 3.4 shows a typical display situation.

Countries
5-Zimbabwe

Figure 3.5- A typical display of the Attribute Sub-menu

3.3.1- KEY BEHAVIOR IN ATTRIBUTE SUB-MENUS

All keys are valid in this menu. The Select key is used to activate/deactivate features.




Figure 3.6- Full graphical description of the Attribute Sub-menus

- a) Attribute selection/deselection
- b) Relationship of the Attribute Sub-menu and its help menu.
- c) Mode switching with the Attribute Sub-menu as the currently active menu.

3.4- UTILITIES MENU

Utilities Menu	
1 -	Set initial key delay
2 -	Set scroll rate
3 -	Enable counting in List Found Birds
4 -	Enable extraction in List Found Birds

Figure 3.7- Utilities Menu

Initially, this menu was designed to provide the user with a facility to adjust the keyboard response time and scroll rate of the navigation keys (items 1 and 2). The experience of an early version of the identifier proved that it was convenient to provide the two functions of bird counting and extraction within the List Found Birds. The latter function acts to drop an entry from the list of found birds.

Due to the limited keyboard, however, it was decided to employ the utilities menu to define which of the two functions would be available to the List Found Birds menu (items 3 and 4). Functions represented by items 1 and 2 do not have bearing on the purpose of this work and thus they were not implemented in the software model.

3.4.1- KEY BEHAVIOR IN UTILITIES MENU




Figure 3.8- Full graphical description of the utilities menu.

- a) Enable/disable function
- b) Relationship of the utilities menu and its help menu.
- c) Mode switching with utilities as the currently active menu.

3.5- FIND MAIN MENU

Find Main Menu	
1 -	List Found Birds
2 -	Clear All Found Birds
3 -	List Attributes
4 -	Clear All Attributes
5 -	List Matched Birds
6 -	Inc/Dec Bird Count
7 -	Information on Bird
8 -	Bird Image
9 -	Bird Call

Figure 3.9- Find Main Menu

Items 1 to 5 represent sub-menus, while items 6 to 9 are selectable items to define the type of function that can be accessed when in List Matched Birds menu. In other words, When viewing the list of candidates in List Matched Birds menu, one of four functions can be performed on the current listed bird;

- 1- Edit the bird count.
- 2- Obtain more information on bird.
- 3- View the image of the current listed bird.
- 4- Generate the call of the current listed bird.

Only one of these functions can be selected at any one time. Here is an example of the display format of this menu. Notice the text indicator of window 3, denoting that more text lies to the right and may be accessed through the right arrow key (East key) depressions.

Find Menu	»
2-Clear All Found Bi	

Figure 3.10- A typical display of the Find Menu

3.5.1- KEY BEHAVIOR IN FIND MAIN MENU




Figure 3.11- Full graphical description of the Find Main Menu

- a) Relationship of the Find Main Menu and its sub-menus; relevant to items 1 to 5.
- b) Selection feature of items 6 to 9.
- c) Relationship of the Find Main Menu and its help menu.
- d) Mode switching with the Find Main Menu as the currently active menu.

3.6- FIND SUB-MENUS

3.6.1- LIST FOUND BIRDS

This function is a very important facility of the identifier, as it is the mechanism that keeps track of the list of cited birds. This is done by attaching a non-zero count value to a bird species in the List Matched Birds menu. The List Matched Birds produces a list of birds that match the selected attributes, and is therefore a dynamic list, since the selected attributes keep changing from one session to the next. In order not to lose the bird of interest through modifying the selected attributes, a bird count serves to tag the bird. All tagged birds will then be available in List Found Birds.

Each entry in the list is identified by a family name, and a species name. Only one entry is displayed at any one time. The bird family is displayed at the top line in window 2 and the bird name at the bottom line in window 4. Here is an example of the display format of this menu.

Falcon
1-Lanner Falcon

Figure 3.12- A typical display of List Found Birds

3.6.1.1- KEY BEHAVIOR IN LIST FOUND BIRDS

The utilities menu specifies which of the two functions are accessible in this menu.

- A) Count Bird: Count value is changed using north/south keys.
- B) Extract Entry: The Select key extracts the current entry from the list following final confirmation.




Figure 3.13- Full graphical description of List Found Birds

- a) Relationship of List Found Birds and Extract Entry
- b) Relationship of List Found Birds and Count Birds.
- c) Relationship of List Found Birds and it's help menu.
- d) Mode switching with List Found Birds as the currently active menu.

3.6.2- CLEAR ALL FOUND BIRDS

This function clears the list of found birds following final confirmation. Once clearing has been initiated by the Select key, the next Select will confirm this operation while the Escape key will abort the clearing operation. Throughout this design where a clearing operation of any kind is involved, both the key behavior and the display format of the clearing operation are consistently copied. In this regard the key behavior and the display form a generic module, accessible to other clearing operations.




Figure 3.14- A typical display of Clear All Found Birds

3.6.2.1- KEY BEHAVIOR IN CLEAR ALL FOUND BIRDS

Select confirms the clearing operation and Escape aborts the operation.




Figure 3.15- Graphical description of Clear All Found Birds

3.6.3- LIST ATTRIBUTES

A list of the selected attributes are provided by this function. This alleviates the need for a manual inspection of each of the attribute sub-menus in order to confirm selected attributes. Here is an example of this menu, where it is assumed that item 2 of the features menu is the current item.

Features
2-Long beak

Figure 3.16- A typical display of the List Attributes

3.6.3.1- KEY BEHAVIOR IN LIST ATTRIBUTES

The Select key clears the current attribute pending a final confirmation. Once clearing has been initiated by the Select key, the next Select will confirm this operation while the Escape key will abort the clearing operation. The clearing operation is consistent with previous clearing operations.




Figure 3.17- Full graphical description of List Attributes

- a) Relationship of List Attributes and Clear Attribute.
- b) Relationship of List Attributes and it's help menu.
- c) Mode switching with List Attributes currently active.

3.6.4- CLEAR ALL ATTRIBUTES

In order to set out on a fresh identification exercise it is necessary that all attribute descriptions of the last session be removed so that new selections can be made as quickly as possible. This operation clears all the selected attributes after final confirmation. The display is that of the generic form shown in Figure 3.12.

3.6.4.1- KEY BEHAVIOR IN CLEAR ALL ATTRIBUTES

The Select key confirms the clearing operation, while the Escape aborts the operation.




Figure 3.18- Graphical description of Clear All Attributes

3.6.5- LIST MATCHED BIRDS

A list of bird species matching the selected attributes is furnished by this menu. The format of this list is consistent with that of found birds. That is the bird family will appear at the top line of display and the species name at the bottom line. Here is an example of the display format.

Vulture
1-Cape Vulture

Figure 3.19- A typical display of List Matched Birds

3.6.5.1- KEY BEHAVIOR IN LIST MATCHED BIRDS

The second level of this menu can be one of four possibilities,

- a) Increment/decrement bird count.
- b) Information on bird.
- c) Bird image.
- d) Bird call.

Items 6 to 9 of the Find Main Menu specify the accessible function in this menu.




Figure 3.20- Full graphical description of List Matched Birds

- a) Relationship of List Matched Birds and it's sub-ordinate menu.
- b) Relationship of List Matched Birds and it's help Menu.
- c) Mode switching with List Matched Birds currently active.

3.6.6- BIRD COUNT

This menu provides a counting facility, to increment/decrement the count of the selected bird. All bird species having a count value will then become available in List Found Birds.

Count: 19
1-Cape Vulture

Figure 3.21- A typical display of Bird Count Menu

3.6.6.1- KEY BEHAVIOR IN BIRD COUNT




Figure 3.22- Full description of the Bird Count Menu

- a) Increment and decrement facility through the North and South keys.
- b) Relationship of Bird Count and its help menu
- c) Mode switching with Bird Count currently active.

3.6.7- INFORMATION ON BIRD

Information on the current bird is displayed on window 2 of the display. This information may be several lines of text, but access to this text is made through the use of navigation keys. Here is an example of the display format of this menu. The content of text information is "Highly versatile bird". Notice the colon separator between window 1 and 5, and the text on the right indicator in window 3.




Figure 3.23- A typical display of the Information on Bird Menu

3.6.7.1- KEY BEHAVIOR IN BIRD INFORMATION




Figure 3.24- Full graphical description of Information on Bird
a) Relationship of Information on Bird and it's help menu.
b) Mode swithcing with Information on Bird currently active.

3.6.8- BIRD IMAGE

This menu is different from all other menus in two respects. Firstly, the display will serve to support the image of the of the bird instead textual descriptions. Secondly, the navigation keys take the role of panning across the full image in the four directions of North, South, East and West.

3.6.8.1- KEY BEHAVIOR IN BIRD IMAGE




Figure 3.25- Full graphical description of Bird Count Menu

- a) The zooming of the bird image.
- b) Relationship of Bird Image and It's help menu.
- c) Mode swithcing with Bird Image currently active.

3.6.9- BIRD CALL

In fact there is no definition of key behavior in this menu. Bird Call is really a function rather than a menu and therefore operates in a purely passive manner. This function is invoked from the List Matched Birds menu.




Figure 3.26- The graphical description of Bird Call

3.7- HELP MENU

This menu may be accessed at all levels of the system. The content of help depends on the context in which help has been requested.

3.7.1- KEY BEHAVIOR IN HELP MENU

The system consistency should render minimum help to be adequate. the help text is therefor limited to a single line, rendering the North/South keys redundant.




Figure 3.27- Graphical description of the Help Menu

3.9- OVERVIEW OF THE BIRD IDENTIFIER FUNCTIONS

The integration of all system activities is shown by the state transition diagram of Figure 3.26. This diagram separates the activities associated with the two operating modes of the identifier. It is important to realize that transferring of system activity from the Attribute mode to the Find mode and vice versa, is possible from any state with the exception of help states.

In this chapter we have completely defined the functional behavior of all system activities. The computer game concepts have strongly been adhered to, in order to accommodate the important issues of Section 2. These issues are listed below in the same order.

- * The keyboard has been reduced to a minimum size, thus making for a simple to use and cost effective device.
- * Considering the limitations of the display, a reasonable global vision has been provided by defining multiple display windows
- * Each activity is represented by a suitable title, which is unique to its environment. This in addition to the presence of clear messages serve to convey a clear status of the system.
- * The consistency of the clearing functions and it's associated keyboard responses ensure system consistency, which is helpful to the user.
- * The simplicity of the MMI and presence of context sensitive help makes lengthy documentation unnecessary.

የሰነድ አቅርቦት ማስፈጸም ለማድረግ የሚያስፈልጉትን ሰነዶች በዚህ ሰነድ ላይ ያስቀመጥሉ፡፡



CHAPTER 4- ARCHITECTURAL DESIGN

4.1- INTRODUCTION

The goal of this chapter is to apply our OOD architectural choice to the bird identifier model. A powerful way of implementing the OOD concept is through the process/resource classification of objects. After discussing the mechanics of process/resource method we will then apply the method to define the bird identifier system. In a systematic approach to this task, process/resource decomposition is carried-out at several levels of abstraction.

4.2- PROCESS/RESOURCE IMPLEMENTATION OF OBJECT-ORIENTED DESIGN

A process is formally defined as an actor object, and is responsible for management of the flow of data to and from resources. The access of data is furnished through well-defined operations supported by resources as an interface to the outside world. A resource is formally defined as a server object, responsible for the management of data in data aggregates[8].




Figure 4.1- The levels of scope from the outside world to the heart of a process/resource system

The process/resource method is basically an object-oriented system design approach in that processes and resources may be considered as objects in their own right. The process/resource strategy classifies objects on the bases of processes and resources, rather than more routine OOD method of identifying actor objects and server objects [7]. Nevertheless, these two methods are essentially equivalent. The former method, however, is more descriptive in that identification of process and

resource objects, serves to define the scope and environment of each object. This will result in a rapid identification of the major objects of the system. The shifting of attention from the outside view of the system to the inside view of major objects, and subsequent identification of subclasses of objects will follow naturally. We will now proceed to identify the objects (processes and resources) of the the system at the highest level of abstraction. But before embarking upon this task we must discuss the importance of isolating the conceptual stage of a design from it's implementation method.

4.3- AWARENESS OF DESIGN LEVEL AND DOCUMENTATION

It is not difficult to fall into the trap of combining 'what' is to be done with 'how' it is done. That is to say the conceptual stage is influenced by the implementation stage. An example in the context of programming is where the designer's thinking during the conceptual stage is conditioned by the employed implementation language. This confusion of interests can have undesirable consequences, the most serious of which is the impact on design documentation. It is well understood that design documentation goes a long way in providing for software management and growth[9]. In fact, Schneidewind [10] states that software should be regarded as a dynamic entity inasmuch as it undergoes change throughout its life, and there is no reason to distinguish between maintenance and initial development. But without good documentation it becomes impossible to manage growth and complexity.

One way of achieving good documentation is through the use of Program Description Language (PDL) [11]. PDL is a conceptual design language that uses the vocabulary of the english language in conjunction with syntax of a structured programming language to form a highly understandable and structured design tool. In de-coupling the concept (the "what") from the implementation (the "how"), the PDL tool can be used to focus efforts on producing sound conceptual designs prior to the implementation stage.

In this design we have employed a PDL[12] tool to concentrate on the architectural and conceptual issues without being affected by implementation issues. This PDL description will also form the backbone of our design documentation. Appendix B contains a full PDL description of the bird identifier model. Due it's powerful descriptive power, we will use a PDL syntax to describe the functionality of the system processes, at different levels of design.

4.4- FIRST-LEVEL DESIGN

At this level of abstraction the entire system is viewed as comprising of several classes of objects (high-level objects), where each class denotes a set of similar but unique objects. A class serves to factor the common properties of a set of objects. Here the interface, menu database and the bird database are identified as the major resources, or classes of objects, of the system. The bird identifier is defined as process object which employs these resources to manage the system data.

In the following demographics we will represent resource objects with oval shapes and the process objects with the rectangular shapes.




Figure 4.2- First-level description; bird identifier process

PDL description of the bird identifier process:-

Repeat:

Begin:

- * Sense the MMI for user commands *
- * Read menu database or bird database to process command *
- * Use the MMI to feedback results to the user *
- * Save dynamic data to bird database *

End:

4.5- SECOND-LEVEL DESIGN

Second-level process and resource decompositions are shown below

Resources:-

Man-Machine Interface (MMI):

- Keypad
- Screen
- Bird call output

Menu database:

- Attribute mode menus
- Find mode menus

Processes:-

Bird identifier process:

- Attribute process
- Find process

4.5.1- THE ATTRIBUTE PROCESS

This level of abstraction serves to discriminate between the two major activities of the system, namely that of the Attribute Mode and the Find Mode. In Figure 4.3 the Attribute Mode is represented by the attribute process, and resources of keypad, screen, attribute menus and selected attributes which provide the necessary data to this process. Notice that the keypad and screen objects are sub-classes of the MMI class, while the attribute menu resource is a sub-class of the menu database.




Figure 4.3- Second-level description; the attribute process

PDL description of the attribute process:-

Begin:

Repeat:

* Access the menu and write the current item to screen *
 * Sense the keyboard for user commands *
 Case * Request of *

Scroll: * Scroll up and down within the current menu or
 right and left within the current item *

Menu level: * Move up or down the menu hierarchy *

Attribute toggle: * Toggle the attribute of the current
 item *

Mode switching: * Terminate process *

Help: * Provide relevant help information *

End: Case:

Until: * Process is terminated *

End:

4.5.2- THE FIND PROCESS

This description is the counter-part of the previous Section, but occupies the same level of abstraction. Figure 4.4 shows the find process surrounded by a series of resources relevant to the Find Mode. Here the find menus resource is a sub-class of the menu database, and the bird call output is a sub-class of the MMI resource. Furthermore, the bird database resource has been decomposed into five sub-classes of objects.




Figure 4.4- Second-level description; the find process

PDL description of the find process:-

Begin:

Repeat:

* Access the menu and write the current item to screen *

* Sense the keyboard for user commands *

Case * Request of *

Scroll: * Scroll up and down within the current menu or
right and left within the current item *

Menu level: * Move up or down the menu hierarchy *

Mode switching: * Terminate process *

Help: * Provide relevant help information *

End: Case:

Until: * Process is terminated *

End:

4.6- THIRD-LEVEL DESIGN

Having identified the major objects of the system, we will now proceed to shift our attention to the inside view of these objects.

Third-level process and resource decompositions are shown below

Resources:-

Man-Machine Interface(MMI):

- Keypad
- Screen
- Bird call output

Menu database:

- Attribute mode menus:
 - Selected attributes
- Find mode menus

Bird database:

- Possessed attributes
- Bird names
- Bird information
- Bird count
- Bird list

Process queue

Processes:-

Bird identifier process:

Scheduler process:

- Help process
- Attribute process
- Find proces:

- Find main menu process
- List Found Birds process
- Clear Found Birds process
- List Attributes process
- Clear Attributes process
- Count Birds process

Since the activities of systems are centered around the data that they support, it seems logical to start by defining the system resources and their operations. However, for the sake of continuity, resources will be dealt with after describing the system processes

4.6.1- SYSTEM PROCESSES

4.6.1.1- THE SCHEDULER PROCESS

The purpose of this object is to schedule the system activities. Since our implementation is based on a flat hierarchy, the nested menus of the system (see Figure 3.26) will be achieved by means of a queuing operation. In fact all activities are scheduled by dequeuing from the queue, where the ready processes await execution. The queue structure will be supported by a queue resource as shown in Figure 4.6. The exact relationship of the nested menus are defined within the disc file containing the menu texts.

The dual mode operation of the identifier was stated earlier as the Find and Attribute mode. The switching between the modes is the function of the Mode key (A/F key), and is achieved through the EXCHANGE-Q-BLOCKS operation of the process queue resource, where activities related to the find and attributes are kept in different queues.




Figure 4.5 Third-level description: the scheduler process

PDL description of the scheduler process:-

```

Begin:
Repeat:
  * Dequeue a process from the queue *
  * Identify the waiting process *
  * Execute the process *
Until: * System is turned off *
End:
  
```

4.6.1.2- THE HELP PROCESS




Figure 4.6 Third-level description: the help process

PDL description of the help process:-

```

Begin:
Repeat:
  Case: * Request of *
    Scroll: * Scroll right and left within the help line *
    Exit help: * Terminate process *
  End: Case:
Until * Process is terminated *
End:
  
```

4.6.1.3- FIND MAIN MENU PROCESS




Figure 4.7 Third-level description: find main menu process

PDL description of find main menu process:-

Begin:

Repeat:

- * Access the menu and write the current item to screen *
- * Sense the keyboard for user commands *
- Case * Request of *

- Scroll: * Scroll up and down within the current menu or right and left within the current item *

- Menu level: * Terminate process *

- Mode switching: * Put the current process in the queue *
 - * Terminate process *

- Help: * Provide relevant help information *

End: Case:

Until: * Process is terminated *

End:

4.6.1.4- LIST FOUND BIRDS PROCESS




Figure 4.8 Third-level description; list found birds process

PDL description of list found birds process:-

Begin:

Repeat:

- * Write number of found birds to window 5 *
- * Write bird name to window 4 *
- * Write count number of current bird to window 1 *
- * Sense the keyboard for user commands *
- Case * Request of *

- Scroll: * Scroll up and down within the list
right and left within the current item *

- Change count: * Increment or decrement the count of the
current listed bird *

- Extract bird: * Extract the currently listed bird from
the list of found birds *

- Mode switching: * Put the current process in the queue *
- * Terminate process *

- Terminate process: * Terminate process *

- Help: * Provide relevant help information *

End: Case:

Until: * Process is terminated *

End:

4.6.1.5- CLEAR FOUND BIRDS PROCESS




Figure 4.9 Third-level description; clear found birds process

PDL description of clear found birds process:-

Begin:

Repeat

* Sense the keyboard for user commands *

Case * Request of *

Confirm: * Clear the list of found birds *

Abort: * Abort the clearing operation *

Mode switching: * Put the current process in the queue *
* Terminate process *

Help: *. Provide relevant help information *

End: Case:

Until: * Process is terminated *

End:

4.6.1.6- LIST ATTRIBUTES PROCESS




Figure 4.10 Third-level description; list attributes process

PDL description of list attributes process:-

Begin:

Repeat:

- * Write number of selected attributes to window 5 *
- * Write title of selected attribute to window 1 *
- * Write name of selected attribute to window 4 *
- * Sense the keyboard for user commands *
- Case * Request of *

- Scroll: * Scroll up and down within the list
 right and left within the current item *

- Extract: * Extract the attributes from the selection list *
- * Recompile the list of matched birds *

- Mode switching: * Put the current process in the queue *
- * Terminate process *

- Terminate process: * Terminate process *

- Help: * Provide relevant help information *

End: Case:

Until: * Process is terminated *

End:

4.6.1.7- CLEAR ATTRIBUTES PROCESS




Figure 4.11 Third-level description; clear attributes process

PDL description of clear attributes process:-

Begin:

Repeat:

* Sense the keyboard for user commands *

Case * Request of *

Confirm: * Clear all selected attributes *

* Recompile the list of matched birds *

Abort: * Abort the clearing operation *

Mode switching: * Put the current process in the queue *

* Terminate process *

Help: * Provide relevant help information *

End: Case:

Until * Process is terminated *

End:

4.6.1.8- COUNT BIRDS PROCESS




Figure 4.12 Third-level description: count birds process

PDL description of count birds process:-

Begin

* Write bird name to window 4 *

Repeat:

* Write count number of current bird to window 1 *

* Sense the keyboard for user commands *

Case * Request of *

Change count: * Increment or decrement the count of the
current listed bird *

Mode switching: * Put the current process in the queue *
* Terminate process *

Terminate process: * Terminate process *

Help: * Provide relevant help information *

End: Case:

Until: * Process is terminated *

End:

4.6.2- SYSTEM RESOURCES

In the first-level design, system resources were broadly identified. In the following Sections we will discuss the role of each resource and the operations that they support. These operations are well-defined interfaces to the outside environment. They are the tools with which the system processes manage the flow of system data. This formulation of resources will furnish the OOD concepts of encapsulation and abstraction.

The function of each operation is described together with the passed parameters. Each operation is represented by an operation name followed by a list of passed-in parameter which are surrounded by a set of parenthesis, followed by a list of passed-out parameters.

4.6.2.1- THE SCREEN RESOURCE

This resource provides the display interface of the bird identifier in addition to the writing and clearing operations associated with it's management.

Data usage:-

Public:

Variable:

- REV_W4 is the reverse video indicator of window 4
- W1_SIZE is the physical size of window 1
- W4_SIZE is the physical size of window 4
- GUIDE_ARROW_L is the text indicator of window 2
- GUIDE_ARROW_R is the text indicator of window 3

Private:

Variables:

- W1_X horizontal position of left most corner of window 1
- W1_Y vertical position of left most corner of window 1
- W4_X horizontal position of left most corner of window 4
- W4_Y vertical position of left most corner of window 4

Constant:

- W2_X horizontal position of left most corner of window 2
- W2_Y vertical position of left most corner of window 2

W3_X horizontal position of left most corner of window 3
 W3_Y vertical position of left most corner of window 3
 W5_X horizontal position of left most corner of window 5
 W5_Y vertical position of left most corner of window 5
 W2_SIZE length of window 2
 W3_SIZE length of window 3
 W5_SIZE length of window 5

List of Operations:-

- 1) O-SCREEN-FORMAT ()
 Behavior:
 This operation serves to emulate the screen display and the keypads of the identifier.
 Interface:
 Input: none
 Output: none
- 2) O-EXCH-W1-W4 ()
 Behavior:
 This operation will switch the physical position of window 1 with that of window 4. Effectively the text on the top line of display is exchanged with the text on the bottom line of display.
 Interface:
 Input: none
 Output: none
- 3) O-WRT-W1 (TEXT_DISPLAY)
 Behavior:
 This operation writes the passed in text parameter to window 1
 Interface:
 Input: TEXT_DISPLAY is the text that is written to window 1
 Output: none
- 4) O-WRT-W2 (W2_CHAR)
 Behavior:
 Indication of text lying to the left of the current window, (normally W4), is written into this single character window.
 Interface:
 Input: W2_CHAR is the character assigned to window 2
 Output: none
- 5) O-WRT-W3 (W3_CHAR)
 Behavior:
 Indication of text lying to the right of the current window, (normally W4), is written into this single character window.
 Interface:
 Input: W3_CHAR is the character assigned to window 3
 Output: none

- 6) O-WRT-W4 (TEXT_DISPLAY)
Behavior:
The passed in parameter, TEXT_DISPLAY, is written to window 4
Interface:
Input: TEXT_DISPLAY
Output: none
- 7) O-WRT-W5 (TEXT_DISPLAY)
Behavior:
The passed in parameter, TEXT_DISPLAY, is written to window 5. This window displays the number of matched birds, or the number of entries in list, when in sub-menus that support a list of birds.
Interface:
Input: TEXT_DISPLAY is the text that is written to window 5
Output: none
- 8) O-CLR-W1 ()
Behavior:
Clears the content of window 1.
Interface:
Input: none
Output: none
- 9) O-CLR-W2 ()
Behavior:
clears the content of window 2.
Interface:
Input: none
Output: none
- 10) O-CLR-W3 ()
Behavior:
clears the content of window 3.
Interface:
Input: none
Output: none
- 11) O-CLR-W4 ()
Behavior:
clears the content of window 4.
Interface:
Input: none
Output: none
- 12) O-CLR-W5 ()
Behavior:
clears the content of window 5.
Interface:
Input: none
Output: none

4.6.2.2- THE TEXT MENU RESOURCE

This resource supports the data structure of the text within the various menus, including help information relevant to each menu. This data structure is stored in a disc file. The operations of this resource provide access to the various menus.

As far as system processes are concerned all menus consist of a menu title, menu item, and relevant help information. Some operations return a status data item to indicate the outcome of the operation.

Data Usage:-

Public:

Variable:

MENU_ID is the menu-id of the current/invoked process

Private:

Variable:

TXT_ARY is the array containing the text of the menus

FLAG_ARY is the array containing select flag /menu id of next process

FLAG_NO_ARY is the array containing flag numbers. This information is used to indicate if the feature belongs to a group which does not allow multiple selections.

NEXT_ID is id of the next menu to which the current item is pointing

KEY_ARY array of type record; it serves to conserve the context of each process.

MENU_ID is the id of current menu

MENU_TITLE is the title of the current menu

HELP is a string of text containing help information

C_POINTER is the pointer to the current menu item supported by TXT_ARY

F_POINTER is the pointer to the first menu item supported by TXT_ARY

L_POINTER is the pointer to the last menu item supported by TXT_ARY

NO_OF_SELECTED_ATTRIBUTES stores the number of selected attributes

LIST_FOUND_POINTER is pointer to manage the list of found birds

List of Operations:-

- 1) O-READ-MENU-FILE () STATUS_
Behavior:
 This operation retrieves and loads the menu text structure from a disc file.
Interface:
 Input: none
 Output: STATUS_ has the outcome of operation successful, or operation failed.
- 2) O-WRITE-MENU-FILE ()
Behavior:
 This operation will write the selected attributes to the menu disc file before terminating program.
Interface:
 Input : none
 Output : none
- 3) O-READ-MENU-TITLE () MENU_TITLE, STATUS_
Behavior:
 This operation reads the title of the current menu and returns the text via MENU_TITLE.
Interface:
 Input: none
 Output: MENU_TITLE captures the title of the current menu and returns it to the invoking process.
 STATUS_ has the outcome of successful or unsuccessful
- 4) O-READ-TXT-ITEM (DISPLACEMENT_) TEXT_ITEM, STATUS_
Behavior:
 This operation reads the line of text at the current/above/below text position. The relative displacement is defined by the value of DISPLACEMENT_. This text is then returned to the invoking process via TEXT_ITEM.
Interface:
 Input: DISPLACEMENT_ specifies the requested text is at current position/above current position/below current position
 Output: TEXT_ITEM returns the line of text from the data structure.
 STATUS_ has the outcome of successful or fail
- 5) O_UPDATE_ATTR_FLAG () STATUS_
Behavior:
 This operation has a dual function
 A) It toggles the state of selectable features (attributes).
 B) It serves to activate sub-menus from the higher level menus.
Interface:
 Input: none
 Output: STATUS_ has the outcome of
 - selected menu item was of the selectable type
 - selected menu item was of a menu type

- 6) O_READ_NO_OF_SELECTED_ATTRIBUTES () NO_OF_S_ATTR
 Behavior:
 The function of this operation is to retrieve the number of attributes that have been selected, from the resource.
 Interface:
 Input: none
 Output: NO_OF_S_ATTR is the number of selected attributes
- 7) O-CLEAR-ALL-ATTRIBUTES ()
 Behavior:
 All selected attributes are cleared through this operation.
 Interface:
 Input: none
 Output: none
- 8) O_CLEAR_ATTRIBUTE;
 Behavior:
 Clears the current attribute from the list of attributes.
 Interface:
 Input: none
 Output: none
- 9) O-LIST-SELECTED-ATTRIBUTES (DISPLACEMENT_) MENU_TITLE, MENU_ITEM
 Behavior:
 This operation will provide the list of selected attributes. The passed-in parameter, DISPLACEMENT_, specifies whether current attribute/last attribute/next attribute will be returned for display.
 Interface:
 Input: DISPLACEMENT_ defines the direction of search
 Output: MENU_TITLE returns the menu title of the selected attribute.
 MENU_ITEM returns the the selected item.
- 10) O-READ-LIST-FOUND-METHOD () METHOD_
 Behavior:
 This operation identifies whether extraction or bird count has been enabled in List Found Birds.
 Interface:
 Input: none
 Output: METHOD_ indicates whether bird count or item extraction has been enabled in List Found Birds
- 11) O_READ_LIST_MATCHED_METHOD () LIST_MATCHED_METHOD
 Behavior:
 This operation which of the four sub-menus have been enabled in List Matched Birds.
 Interface:
 Input: none
 Output: LIST_MATCHED_METHOD indicates which one of four functions has been enabled during List Matched Birds

12) O-FILL-FILTER ()

Behavior:

The role of this operation is to compile a searching filter based on the selected attributes. This filter which is basically a short list of the selected attributes will be employed in the searching of the birds data base. Instead of returning the filter back through the interface it is placed in the global environmental module. In this way redundant data flow is avoided.

Interface:

Input: none

Output: none

4.6.2.3- THE QUEUE RESOURCE

This resource provides the facility of querying the main activities of ATTRIBUTE and FIND.

Data Usage:-

Public:

Variable:

MENU_ID is the id of the current menu.

Private:

Variable:

STATUS is the status report of procedures and functions.

Q_ARY is the array emulating the queue

Q_TMP_ARY is the temporary queue array, used for context switching

Q_MIDL is the marker separating the find and attribute activities

Q_TAIL is the pointer marking the position of the last item in the queue

Constant:

Q_SIZE is the size of the queue set at 10

List of Operations:-

1) O-READ-Q-FILE ()

Behavior:

this operation retrieves the queue information from a disc file, Q_DAT.TXT, when the main program is first run

Interface:

Input: none

Output: none

- 2) O-WRITE-Q-FILE ()
 Behavior:
 This operation will write the queue data into file Q_DAT.TXT when quitting the program
 Interface:
 Input: none
 Output: none
- 3) EXCHANGE-Q-BLOCKS ()
 Behavior:
 This operation will swap the segments of queue corresponding to the Attribute mode with segment corresponding to the Find mode, thus putting the relevant menu-id at the head of the queue
 Interface:
 Input: none
 Output: none
- 4) O-FRONT-ENQ () STATUS_
 Behavior:
 This operation will enqueue the MENU_ID at the head of the queue
 Interface:
 Input: none
 Output: STATUS_ has the outcome of
 0 - successful
 1 - unsuccessful / queue is full
- 5) O-DEQ () STATUS_
 Behavior:
 This operation will consume the item at the head of the queue, and writes it to the MENU_ID
 Interface:
 Input: none
 Output: STATUS_ has the outcome of
 0 - successful
 1 - unsuccessful / queue empty
- 6) INITIALIZE_Q_FILE () Q_FILE
 Behavior:
 This operation checks the default drive for the queue file. If it is not found then a second predefined path will be checked, before aborting.
 Interface:
 Input: none
 Output: Q_FILE is the directory path where the queue file was found. This is the path where queue is saved before exiting from the program

4.6.2.4- THE SCROLL RESOURCE

This resource facilitates the function of word scrolling within the current line of text, which is stored in the variable TEXT_ITEM. This is achieved by displaying a segment of the text at any one time.

Data Usage:-

Public:

Variable:

TEXT_ITEM is the string text of the current menu item
REV_W4 is the reverse video indicator of window 4
W1_SIZE is the size of window 1
W4_SIZE is the size of window 4
GUIDE_ARROW_R
GUIDE_ARROW_L
W_NO is the window number of the active window, either 1 or 4

Private:

Variables:

W_L_POINTER is the window left pointer.
W_R_POINTER is the window right pointer.
TEXT_DISPLAY is the portion of text from the TEXT_ITEM to be displayed on the screen.
TEXT_LENGTH is the length of text in TEXT_ITEM.

List of operations:-

1) O-INITIAL-TEXT (TEXT_ITEM) TEXT_DISPLAY

Behavior:

This operation extracts the first x characters in the text contained in TEXT_ITEM and writes it to TEXT_DISPLAY

Interface:

Input: TEXT_ITEM contains the current line of text in the data structure

TEXT_DISPLAY contains a sub-string of text within TEXT_ITEM, for displaying on the screen

Output: TEXT_DISPLAY is the truncated text from the current line to be displayed on the current window

2) O-MOVE-TEXT-LEFT (TEXT_ITEM) TEXT_DISPLAY

Behavior:

This operation moves the displayed window of the text in MENU_ITEM one word to the left.

Interface:

Input: MENU_ITEM contains the current line of text in the data structure

Output: TEXT_DISPLAY contains a sub-string of text within MENU_ITEM, for displaying on the screen

3) O-MOVE-TEXT-RIGHT (MENU_ITEM) TEXT_DISPLAY

Behavior:

This operation moves the displayed window of the text in MENU_ITEM one word to the right

Interface:

Input: MENU_ITEM contains the current line of text in the data structure.

Output: TEXT_DISPLAY; contains a sub-string of text within MENU_ITEM for displaying on the screen

4.6.2.5- BIRD DATABASE RESOURCE

Bird attributes, bird information, bird name, bird family, bird S.A number, bird code and bird count data structures are managed in this resource. Operations of the resource allow access to bird data including the scan and compare mechanism required for short listing and generation of the list of matched birds. The static part of the database includes bird attributes, bird information, bird name, bird S.A number, bird code and bird family; and are stored on a disc file. The dynamic part of this database comprising of the bird count is stored in a separate disc file.

Data Usage:-

Public:

Variable:

MENU_ID is the id of the current menu.

BIRD_FAMILY is the family to which the current bird belongs

BIRD_NAME is the name of the current bird

BIRD_COUNT is the count number of the current bird

Private:

Variable:

STRATEGY is the search and compare strategy of selected attributes against the bird attributes; four possible values. a) no attribute is selected; compile all birds for display b) only bird family is selected c) a flag type attribute is selected; bird family is not selected d) both family and flag type attributes have been selected

NO_OF_MATCHED_BIRDS is the number of birds matching the selected attributes

MATCH_LIST_NO identifies which of the four possible

functions of a)bird count, b)bird information, c)bird image or d)bird call have been enabled
 NO_FOUND_BIRDS is the number of birds with a bird count greater than zero
 FOUND_LIST_NO identifies whether extraction or bird count are enabled during the list found birds
 DATA_ARY is of the type record; this is the bird database
 BIR_NAME is the name bird
 FAMILY is the family of the bird
 SAOS is the South African bird number
 FR_CODE is the bird habitat code
 BIRD_ATTR contains the flag type attributes of the bird
 BIRD_COUNT is the count number of the bird
 MATCH indicates if the current record has matched attribute specifications
 BIRD_REC is the DATA_ARY record pointer

List of operations:-

- 1) O-READ-BIRD-DATA ()
 Behavior:
 This operation retrieves the static (read-only) segment of the bird database, from a disc file.
 Interface:
 Input: none
 Output: none
- 2) O-SCAN ()
 Behavior:
 The bird data base will be scanned and compared against the selected attributes, to generate a short list of the matched birds. This operation
 Interface:
 Input: none
 Output: none
- 3) O-LIST-MATCHED-BIRDS (DISPLACEMENT_)
 Behavior:
 The retrieval of bird species from the short list of matched birds is achieved through this operation. The passed-in parameter, DISPLACEMENT, specifies whether current/next/previous entry will be retrieved. The name and family of the retrieved bird species will then be written to the display from the calling process. To prevent the redundant flow of data this information is placed into the global environmental module, rather than being returned to the calling process.
 Interface:
 Input: DISPLACEMENT_ defines the direction of retrieval
 Output: none

- 4) O-READ-COUNT-FILE ()
 Behavior:
 The bird count information is read from a disc file.
 Interface:
 Input: none
 Output: none

- 5) O-WRITE-COUNT-FILE ()
 Behavior:
 The bird count information is written to a disc file
 Interface:
 Input: none
 Output: none

- 6) O-CHANGE-BIRD-COUNT (DISPLACEMENT_)
 Behavior:
 Bird counts are adjusted through this operation. The
 passed-in parameter, DISPLACEMENT_, specifies whether the
 count should be incremented or decremented.
 Interface:
 Input: DISPLACEMENT_ defines if count should be incremented
 or decremented.
 Output: none

- 7) O-READ-FOUND-BIRDS () NO_OF_FOUND_BIRDS
 Behavior:
 This operation retrieves the number of birds which have a
 count value greater than zero. This is necessary to
 display the total number of found birds, when in List Found
 Birds.
 Interface:
 Input: none
 Output: NO_OF_FOUND_BIRDS is the number of found birds

- 8) O-LIST-FOUND-BIRDS (DISPLACEMENT_)
 Behavior:
 The retrieval of bird species that have a count value of
 greater than zero is achieved through this operation. The
 passed-in parameter, DISPLACEMENT_, specifies whether
 current/next/previous entry will be retrieved. The name and
 family of the retrieved bird species will then be written
 to the display from the calling process. To prevent the
 redundant flow of data this information is placed into the
 global environmental module, rather than being returned to
 the calling process.
 Interface:
 Input: DISPLACEMENT_ defines the direction of retrieval.
 Output: none

- 9) O-CLEAR-FOUND-BIRDS ()
 Behavior:
 clears the list of found birds.
 Interface:
 Input: none
 Output: none

10) O-CLEAR-BIRD ()

Behavior:

Clears the current bird from the list of found birds.

Interface:

Input: none

Output: none

11) O-READ-NO-OF-MATCHED-BIRDS () NO_OF_MATCHED_BIRDS

Behavior:

This operation retrieves the number of birds which match the selected attributes. This is necessary to display the total number of matched birds, when in List Matched Birds.

Interface:

Input: none

Output: NO_OF_MATCHED_BIRDS is the number of matched birds

4.7- SUMMARY

During the course of this chapter we have covered the powerful method of process/resource decomposition of OOD objects. The importance of divorcing the conceptual design from the implementation method was next discussed. To complement this discipline a PDL documentation method was adopted. By partitioning the object identification and classification exercise into three progressive high to low level stages, the system processes and resources were described.

CHAPTER 5- DISCUSSION AND CONCLUSION

5.1- ACHIEVEMENTS

A personal computer software model has been developed. This model provides all the prescribed facilities of the identifier except the bird image and bird call facilities. In spite of this, bird identification is still very much possible. In fact except for those situations where bird image and call remain as the final means of identification, the simple model has proved to be very practical and efficient. We have provided the bird identifier model with a bird database of 742 bird species containing 194 attributes (bird family through to markings; see Appendix A) . In the interest of simplicity and modifiability this database is stored in disc file without any compression or optimizing schemes. Despite this lack of efficiency the scan and compare mechanism of 'List Matched Birds' activity is hardly noticeable to the user. Recall that the result of each attribute selection is immediately fed back to the user by recompiling the list through the List Matched Birds operation and displaying the number of birds in the list, on window 5.

5.2- IMPLEMENTATION

Turbo Pascal V5.5 was used to implement the PDL descriptions. The reason for this choice was due to the structured syntax of Pascal. It furnished a High-level programming platform, on which one could concentrate on producing a sound system, without being hampered with language barriers. Conscious effort was made to avoid the use of complex data structures such as pointers, in anticipation of making the code more portable. This was considered necessary as the personal computer model would eventually be imported into a hand-held environment such as a microcontroller. With this in mind we have further restricted our OOD realization to the use of Turbo Pascal 'Units', rather than Turbo 'Objects'.

The entire size of the bird identifier code is 36 Kb and the uncoded birds database is 67 Kb. (A list modules and their corresponding code size is listed in Appendix.C.). The programme code includes extensive status checking of most operations, indicating the precise outcome of the operation. This was done to build some degree of self testing into the model; thus making for simpler debugging procedure. Once the employed databases are successfully employed by the software model, the checking operations may be removed from the code to ensure that the final code volume can be comfortably accommodated by a hand-held device. However, even in the present form, the database together with the program can be supported by a 8051 microcontroller environment, without difficulty.

5.3- TESTING

Testing is a vital and necessary part of any software development. To ensure efficient debugging, the testing effort was systematically divided into two separate stages; the testing of individual processes and the final testing of the integrated system. All modules were tested individually, prior to system integration. The validation of the 'List Matched Birds' module was by far the most important exercise at this level of testing. This was done by truncating the bird database to eleven birds. Several combinations of features were selected and the list of generated matched birds were cross-checked with those of the database. Final testing stage involved the testing of the functional behavior of the entire system. Due to the simplicity of the model and it's user-interface, extensive generation of test vectors was not necessary. In fact the final functional testing was carried-out in less than thirty minutes.

5.4- IMPACT OF SOFTWARE ENGINEERING METHODOLOGY

In conforming with the objectives of this work we will discuss the software engineering implications of design architecture and development tools of the bird identifier fieldguide.

5.4.1- OBJECT-CENTERED APPROACH TO DESIGN

Although the architectural design does not exploit all OOD concepts such as inheritance, but it does conform to a system decomposition that is based on the idea of real world objects. We experienced that this discipline goes a long way in promoting

the understandability of the system, it's testing and maintenance. Firstly the object decomposition exercise followed the behavioral descriptions naturally. In this regard the Attribute and Find Mode descriptions played a two-fold role of providing fast and efficient access to the system functions as well as furnishing a reasonable model on which object decomposition could be based. Secondly, the effort of testing and modifications was much simplified, since the scope of activity was very much localized. Thirdly, because of the encapsulation property of objects, integration was achieved with very little difficulty.

5.4.2- TOOL SUPPORT

In spite of abundance of Computer Aided Software Engineering tools (CASE), users of these tools feel that it will be sometimes before a comprehensive and yet simple to use CASE tool package, is made available. In the case of the bird identifier design, the degree of complexity did not warrant a powerful development tool. A PDL formatter was used to develop the architectural concepts of the design and was later expanded to a more detailed level in order to furnish the documentation needs of the design. As far as implementation is concerned Turbo Pascal was used to perform the editing, running and debugging of code, all within the same environment.

5.4.3- REPORT OF DESIGN CYCLE TIME SCALE

Table below shows the different design stages and associated hours of activity. It is important to state that the figures in this table represent the lump amount of time spent in each stage; as this design cycle was reiterated several times to completion.

Activity	Used Hours	% of Total Hours
Architectural Design	100	11.8
Detailed Design (PDL)	200	23.5
Coding	180	21.2
Testing	70	8.2
Documentation	300	35.3
Total	850	100.0

5.5- CONCLUSIONS

Even with best coding techniques available today, storing of sound and picture information places considerable demands on the required memory space. With rapid advances in the field of memory chips and display units, however, electronic fieldguides offering sound and picture information as well as text are becoming more feasible. Notwithstanding these powerful capabilities, the electronic fieldguide remains the fastest means of information access; and therefore it is far superior to the conventional implementations. As we have previously indicated response time is a fundamental measure of capability and usefulness. A good example of such a situation is in the field of medical science, where the process of a swift diagnosis is of major importance. Electronic fieldguides can also play a major role in the educational field, where encouragement by the way of providing quick solutions, will serve to sustain the level of interest and will ultimately result in uplifting the knowledge of the student. This is particularly true in the case of the younger user, where it is well accepted that youngsters are quite fearless of the electronic technology. In fact as the electronic game market indicates, the sheer element of curiosity which is shared by most teen-agers, is the first and foremost advocate. By tapping into this tremendous facet of the younger generation, electronic fieldguides can provide a significant contribution towards the promotion of science.

BIBLIOGRAPHY

1. Cole B.C, "A 16-Mb DRAM Grabs The Spotlight", Electronics Week, Vol.60, No.5, pp59-60 1987
2. Maclean K.N "Roberts' Birds of Southern Africa", John Voelcker, Cape Town, 1985
3. Newman k, "Birds of South Africa", Macmillan, South Africa, 1983
4. Stephen W.D and Donald A.N, "Software Engineering for User Interface", IEEE Transactions on Software Engineering, Vol.SE-11, No.3, pp252-258, March 1985
5. Bernice E.C., "A Games Approach to System Interface Design", IEEE Transactions on Professional Communications VOL.PC 29, No.4, pp65-71, December 1986
6. Stonebraker M, Allman E, "Observations on The Evolution of a Software System", IEEE Computer, pp27-32, June 1982
7. Booch G, "Object-Oriented Development", IEEE Transactions, Software Eng, Vol.SE-12, No.2, pp211-221, Feb 1986
8. Walker A.J, "Structured Information Processing System Design", Software engineering notes, University of the Witwatersrand, pp3.2, 1986
9. Allman E. and Stonebraker M, "Observation on the Evolution of a Software System", IEEE Computer, pp27-32, June 1982
10. Schneidewind W.F, "The State of Software Maintenance", IEEE Transactions on Software Engineering, Vol.SE-13, No.3, pp303-309, March 1987
11. Caine H.S and Gordon E.K, "PDL - A tool for Software Design" reprinted in Tutorial on Software Design, edited by P.Freeman and A Wasserman, IEEE Press, pp380-385, 1975
12. Walker A.J, Dinkelacker A.M, "PDL Formatter" Software Engineering Applications Lab. University of the Witwatersrand, 1988

APPENDIX. A- LIST OF ATTRIBUTE SUB-MENUS

A - National Parks (provides a single flag for selection)

- A2.1 - Kruger National Park
- A2.2 - Mountain Zebra National Park
- A2.3 - Karoo National Park
- A2.4 - Addo Elephant National Park
- A2.5 - Langebaan National Park
- A2.6 - Swartvlei
- A2.7 - Tsitsikamma Forest National Park
- A2.8 - Golden Gate Highlands National Park
- A2.9 - Augrabies Falls National Park
- A2.10 - Bontebok National Park
- A2.11 - Kalahari Gemsbok National Park

A3 - Hiking Trails (provides a single flag for selection)

- A3.1 - Fanie Botha
- A3.2 - Soutspansberg
- A3.3 - Otter
- A3.4 - Outeniqua

A4 - Towns and Cities (provides a single flag for selection)

- A4.1 - Johannesburg
- A4.2 - Pretoria
- A4.3 - Cape Town
- A4.4 - Port Elizabeth
- A4.5 - East London
- A4.6 - Durban

A5 - Bird Sanctuaries (provides a single flag for selection)

- A5.1 - Barberspan
- A5.2 - Rondebult
- A5.3 - Marievale
- etc

A6 - Habitats (provides a single flag for selection)

- A6.1 - Towns, Parks and Gardens
- A6.2 - Roadside Birds
- A6.3 - Cultivation and Grasslands
- A6.4 - Fynbos
- A6.5 - Karoo
- A6.6 - Semi-desert
- A6.7 - Thorn Trees in Grassveld
- A6.8 - Broadleaved Bushveld and Woodland

- A6.9 - Riverine and Coastal Bush: River Edge
- A6.10 - Evergreen Forest
- A6.11 - Wetlands
- A6.12 - Estuaries and Seashores
- A6.13 - Oceans
- A6.14 - Mountains, Rocky and Grassy Slopes

A7 - Status (max. of 3 logically ANDed options)

- | | |
|-----------------------|-----------|
| A7.1 - Abundant | --flag #1 |
| A7.2 - Common | --flag #1 |
| A7.3 - Uncommon | --flag #1 |
| A7.4 - Rare | --flag #1 |
| A7.5 - Vagrant | --flag #2 |
| A7.6 - Summer visitor | --flag #2 |
| A7.7 - Winter visitor | --flag #2 |
| A7.8 - Resident | --flag #2 |
| A7.9 - Diurnal | --flag #3 |
| A7.10 - Nocturnal | --flag #3 |

A8 - Bird Families (provides a single flag for selection)

- A8.1 - Albatrosses
- A8.2 - Alethe
- A8.3 - Apalis
- A8.4 - Avocet
- A8.5 - Babblers
- A8.6 - Barbets
- A8.7 - Batis
- A8.8 - Bee-eaters
- A8.9 - Bishops
- A8.10 - Booby
- A8.11 - Broadbill
- A8.12 - Bulbuls
- A8.13 - Buntings
- A8.14 - Bush Shrikes
- A8.15 - Bustards
- A8.16 - Buttonquails
- A8.17 - Buzzards
- A8.18 - Canaries
- A8.19 - Chaffinches
- A8.20 - Chats
- A8.21 - Cisticolas
- A8.22 - Coot
- A8.23 - Cormorants
- A8.24 - Coucals
- A8.25 - Coursers
- A8.26 - Crakes
- A8.27 - Cranes
- A8.28 - Crimsonwing
- A8.29 - Crombecs
- A8.30 - Crows
- A8.31 - Cuckoo Finches
- A8.32 - Cuckoohawk

A8.33 - Cuckoos
A8.34 - Cuckooshrikes
A8.35 - Curlew
A8.36 - Dartar
A8.37 - Dikkops
A8.38 - Doves
A8.39 - Drongos
A8.40 - Ducks
A8.41 - Eagles
A8.42 - Egrets
A8.43 - Falcons
A8.44 - Finches
A8.45 - Finfoot
A8.46 - Fire Finches
A8.47 - Flamingos
A8.48 - Flufftails
A8.49 - Flycatchers
A8.50 - Francolins
A8.51 - Frigate Birds
A8.52 - Gallinules
A8.53 - Gannets
A8.54 - Geese
A8.55 - Godwits
A8.56 - Goshawks
A8.57 - Grassbird
A8.58 - Guineafowl
A8.59 - Gulls
A8.60 - Gymnogene
A8.61 - Hamerkop
A0.62 - Harriers
A8.63 - Helmet Shrikes
A8.64 - Herons
A8.65 - Honeyguides
A8.66 - Hoopoes
A8.67 - Hornbills
A8.68 - Hyliotas
A8.69 - Ibises
A8.70 - Jacanas
A8.71 - Kestrels
A8.72 - Kingfishers
A8.73 - Kites
A8.74 - Korhaans
A8.75 - Larks
A8.76 - Longclaws
A8.77 - Louries
A8.78 - Lovebirds
A8.79 - Manikins
A8.80 - Martins
A8.81 - Moorhens
A8.82 - Mousebirds
A8.83 - Nicator
A8.84 - Nightjars
A8.85 - Orioles
A8.86 - Ostrich
A8.87 - Owls
A8.88 - Oxpeckers

A8.89 - Oystercatchers
A8.90 - Palm Thrushes
A8.91 - Parrots
A8.92 - Penduline Tits
A8.93 - Penguins
A8.94 - Petrels
A8.95 - Phalaropes
A8.96 - Pigeons
A8.97 - Pipits
A8.98 - Pitta
A8.99 - Plovers
A8.100 - Pratincoles
A8.101 - Prinias
A8.102 - Pytilias
A8.103 - Quails
A8.104 - Queleas
A8.105 - Rails
A8.106 - Raven
A8.107 - Robins
A8.108 - Rockjumpers
A8.109 - Rockrunner
A8.110 - Rollers
A8.111 - Sandgrouse
A8.112 - Sandpipers
A8.113 - Secretary Bird
A8.114 - Seedcrackers
A8.115 - Shearwaters
A8.116 - Shrikes
A8.117 - Siskins
A8.118 - Skimmer
A8.119 - Skuas
A8.120 - Snipes
A8.121 - Sparrowhawks
A8.122 - Sparrows
A8.123 - Starlings
A8.124 - Stilt
A8.125 - Stints
A8.126 - Storks
A8.127 - Sugarbirds
A8.128 - Sunbirds
A8.129 - Swallows
A8.130 - Swan
A8.131 - Swifts
A8.132 - Tchagras
A8.133 - Terns
A8.134 - Thrushes
A8.135 - Titbabbler
A8.136 - Tits
A8.137 - Trogon
A8.138 - Tropic Birds
A8.139 - Turnstone
A8.140 - Twinspots
A8.141 - Vultures
A8.142 - Wagtails
A8.143 - Warblers
A8.144 - Waxhills

A8.145 - Weavers
A8.146 - Wheatears
A8.147 - Whimbrel
A8.148 - White-eyes
A8.149 - Whydahs
A8.150 - Widow Finches
A8.151 - Widows
A8.152 - Woodpeckers
A8.153 - Wryneck

A9 - Size (provides a single flag for selection)

A9.1 - Larger than a Turtle Dove
A9.2 - About the size of a Turtle Dove
A9.3 - Between turtle dove and Cape Sparrow
A9.4 - About the size of a Cape Sparrow
A9.5 - Smaller than a Cape Sparrow

A10 - Feeding Habits (provides a single flag for selection)

A10.1 - Flying
A10.2 - Perching
A10.3 - On Ground
A10.4 - Wet Areas
A10.5 - Water
A10.6 - Climbing and Creeping

A11 - Features (max. of 6 logically ANDed options)

A11.1 - Long legs	--flag #1
A11.2 - Long beak	--flag #2
A11.3 - Long neck	--flag #3
A11.4 - Long tail	--flag #4
A11.5 - Fork tail	--flag #4
A11.6 - Square tail	--flag #4
A11.7 - Bill heavy or hooked	--flag #5
A11.8 - Bill short and conical	--flag #5
A11.9 - Head crested	--flag #6

A12 - Coloring (max. of 9 logically ANDed options)

A12.1 - Mostly white	--flag #1
A12.2 - Mostly black	--flag #2
A12.3 - Black and dark or white and gray	--flag #3
A12.4 - Mostly brown	--flag #4
A12.5 - Yellow or orange present	--flag #5
A12.6 - Green or blue present	--flag #6
A12.7 - Red present	--flag #7
A12.8 - Rust or buff present	--flag #8
A12.9 - Beak, eye or feet distinctively marked	#9

A13 - Markings (max. of 6 logically ANDed options)

A13.1 - Underparts plain	--flag #1
A13.2 - Underparts spotted	--flag #1
A13.3 - Underparts stripped	--flag #1
A13.4 - Underparts barred	--flag #1
A13.5 - Upperparts marked	--flag #1
A13.6 - Stripe through or over eye	--flag #2
A13.7 - Top of head distinct	--flag #3
A13.8 - Eye ring distinct	--flag #4
A13.9 - Boldly marked sitting or standing	--flag #5
A13.10 - Boldly marked in flight	--flag #5
A13.11 - Tail longitudinally marked	--flag #6
A13.12 - Tail cross-marked	--flag #6

A14 - Utilities (no flags)

A14.1 - Set initial key delay (only applies to arrow keys)
A14.2 - Set scroll rate (only applies to arrow keys)
A14.3 - Enable counting in List Found Birds
A14.4 - Enable extraction in List Found Birds

APPENDIX. B- PDL DOCUMENTATION OF THE BIRD IDENTIFIER

Birds

Revision.2 (12/10/90)

Time 12 : 27

Date 15 10 1990

Birds
TABLE OF CONTENTS

15 10 1990 PAGE 0 - 1

TABLE OF CONTENTS.....	0 - 1
Public Constants.....	1 - 1A
Public Variables.....	1 - 1B
Private Constants.....	1 - 1C
Private Variables.....	1 - 2A
Scheduler Process.....	1 - 3
Scheduler Data Usage.....	1 - 4A
Scheduler Process.....	1 - 5A
Help Process.....	1 - 6
Help Data Usage.....	1 - 7A
Help Menu Process [P-HELP].....	1 - 8A
Attribute Processes.....	1 - 9
Attribute Menu Data Usage.....	1 - 10A
Attribute Menu Process [P-ATTR-MENU].....	1 - 11A
Utility Menu Data Usage.....	1 - 12A
Utility Menu Process [P-UTIL].....	1 - 13A
Find Processes.....	1 - 14
Find Main Menu Data Usage.....	1 - 15A
Find Main Menu Process [P-FIND-MENU].....	1 - 16A
List Found Birds Data Usage.....	1 - 17A
List Found Birds Process [P-LIST-FOUND].....	1 - 18A
Clear Found Birds Data Usage.....	1 - 19A
Clear Found Birds Process [P-CLEAR-FOUND].....	1 - 19B
List Attributes Data Usage.....	1 - 20A
List Attributes Process [P-LIST-ATTR].....	1 - 21A
Clear Attribute Data Usage.....	1 - 22A
Clear Attributes Process [P-CLEAR-ATTR].....	1 - 22B
List Matched Birds Data Usage.....	1 - 23A
List Matched Birds Process.....	1 - 24A
Bird Count Data Usage.....	1 - 25A
Count Bird Process [P-COUNT-BIRD].....	1 - 26A
Clear a Found Bird Data Usage.....	1 - 27A
Clear a Found Bird Process [P-CLEAR-BIRD].....	1 - 27B
Text Menu Resource.....	1 - 28
Data Usage.....	1 - 29A
Behavior.....	1 - 29B
O-READ-MENU-FILE.....	1 - 30A
O-WRITE-MENU-FILE.....	1 - 31A
O-READ-MENU-TITLE.....	1 - 32A
O-READ-TXT-ITEM.....	1 - 33A
O-UPDATE-ATTR-FLAG.....	1 - 34A
O-READ-NO-OF-SELECTED-ATTRIBUTES.....	1 - 35A
O-CLEAR-ALL-ATTRIBUTES.....	1 - 35B
O-CLEAR-ATTRIBUTE.....	1 - 36A
O-LIST-SELECTED-ATTRIBUTES.....	1 - 36B
O-READ-LIST-FOUND-METHOD.....	1 - 37A
O-READ-LIST-MATCHED-METHOD.....	1 - 38A
O-FILL-FILTER.....	1 - 38B
Bird Resource.....	1 - 39
Data Usage.....	1 - 40A
Behavior.....	1 - 40B
O-READ-BIRD-DATA.....	1 - 41A
O-SCAN.....	1 - 42A
O-LIST-MATCHED-BIRDS.....	1 - 43A

O-READ-COUNT-FILE.....	1 - 43B
O-WRITE-COUNT-FILE.....	1 - 44A
O-CHANGE-BIRD-COUNT.....	1 - 44B
O-READ-NO-OF-FOUND-BIRDS.....	1 - 45A
O-LIST-FOUND-BIRDS.....	1 - 45B
O-CLEAR-FOUND-BIRDS.....	1 - 46A
O-CLEAR-BIRD.....	1 - 46B
O-READ-NO-OF-MATCHED-BIRDS.....	1 - 47A
Queue Resource.....	1 - 48
Data Usage.....	1 - 49A
Behavior.....	1 - 49B
O-READ-Q-FILE.....	1 - 50A
O-WRITE-Q-FILE.....	1 - 50B
O-EXCH-Q-BLOCKS.....	1 - 51A
O-FRONT-ENQ.....	1 - 52A
O-DEQ.....	1 - 53A
Scroll Manager Resource.....	1 - 54
Data Usage.....	1 - 55A
Behavior.....	1 - 55B
O-INITIAL-TEXT.....	1 - 56A
O-MOVE-TEXT-LEFT.....	1 - 57A
O-MOVE-TEXT-RIGHT.....	1 - 58A
Screen Resource.....	1 - 59
Data Usage.....	1 - 60A
Behavior.....	1 - 60B
O-SCREEN-FORMAT.....	1 - 61A
O-WRT-W1.....	1 - 61B
O-WRT-W2.....	1 - 62A
O-WRT-W3.....	1 - 62B
O-WRT-W4.....	1 - 63A
O-WRT-W5.....	1 - 63B
O-CLR-W1.....	1 - 64A
O-CLR-W2.....	1 - 64B
O-CLR-W3.....	1 - 64C
O-CLR-W4.....	1 - 65A
O-CLR-W5.....	1 - 65B
Auxiliary Functions.....	1 - 66
O-WAIT.....	1 - 67A
Quit Program [P-QUIT-PROG].....	1 - 67B
CALLING TREE.....	2 - 1
PROCEDURE INDEX.....	3 - 1
DATA INDEX.....	4 - 1
LAST PAGE.....	5 - 1

Public Constants

-----D- 1A -D-----

D 1	ID_ATTR_M ..is the process-id of the 'Main Attribute' menu
D 2	ID_FIND_M ..is the process-id of the 'Main Find' menu
D 3	ID_HELP is the process-id of the 'Help' menu
D 4	ID_COUNTRY .is the process-id of the 'Countries' menu
D 5	ID_N_PARKS .is the process-id of the 'National Parks' menu
D 6	ID_HIKING ..is the process-id of the 'Hiking Trails' menu
D 7	ID_TOWNS ...is the process-id of the 'Towns and Cities' menu
D 8	ID_BIRD_SAN is the process-id of the 'Bird Sanctuaries' menu
D 9	ID_HABITAT .is the process-id of the 'Habitats' menu
D 10	ID_STATUS ..is the process-id of the 'Status' menu
D 11	ID_BIRD_F ..is the process-id of the 'Bird Families' menu
D 12	ID_SIZE is the process-id of the 'Bird Size' menu
D 13	ID_FEEDING .is the process-id of the 'Feeding' menu
D 14	ID_FEATURE .is the process-id of the 'Features' menu
D 15	ID_COLORING is the process-id of the 'colorings' menu
D 16	ID_MARKING .is the process-id of the 'Markings' menu
D 17	ID_UTILITY .is the process-id of the 'Utilities' menu

Public Variables

-----D- 1B -D-----

D 1	PROCESS_ID is the id of the current menu.
D 2	LAST_PROCESS_ID is the id of the of the last process

Private Constants

-----D- 1C -D-----

D 1	MENU_TITLE is the title of the current menu.
-----	--

Private Variables

-----D- 2A -D-----

D 1 TEXT_ITEM ...is the string text of the current menu item.
D 2 TEXT_DISPLAY portion of text from the TEXT_ITEM for display on screen.
D 3 CONTINUE_ ...is the boolean variable for the while loop.
D 4 STATUS_ is the status report of procedures and functions.
D 5 KEY_ is the character containing the pressed key.
D 6 C_POINTER ...points to the current entry in the menu
D 7 F_POINTER ...points to the first entry in the menu
D 8 L_POINTER ...points to the last entry in the menu
D 9 W_L_POINTER .is the window left pointer.
D 10 W_R_POINTER .is the window right pointer.
D 11 CHAR_ is a character of the text TEXT_ITEM for testing purposes.
D 12 TEXT_LENGTH .is the length of text in TEXT_ITEM.
D 13 DISPLACEMENT_ defines vertical scroll direction relative to current position
D 14 ATTRIBUTE_FLAG is an indicator for attribute selection
D 15 W1_X is the screen column position of left corner of window 1
D 16 W1_Y is the screen row position of left corner of window 1
D 17 W3_X is the screen column position of left corner of window 3
D 18 W3_Y is the screen row position of left corner of window 3
D 19 W4_X is the screen column position of left corner of window 4
D 20 W4_Y is the screen row position of left corner of window 4
D 21 W1_SIZE is th size of window 1
D 22 W2_SIZE is th size of window 2
D 23 W3_SIZE is th size of window 3
D 24 W4_SIZE is th size of window 4

Birds

15 10 1990 PAGE 1 - 3

Scheduler Process

Scheduler Data Usage

-----C- 4A -C-----

C 1 Public Constants:
C 2 Public Variables:
C 3 ...PROCESS_ID is the id of the current menu.
C 4 Private Constants:
C 5 ...ID_ATTR_M ..is the process-id of the 'Main Attribute' menu
C 6 ...ID_FIND_M ..is the process-id of the 'Main Find' menu
C 7 ...ID_HELP is the process-id of the 'Help' menu
C 8 ...ID_COUNTRY .is the process-id of the 'Countries' menu
C 9 ...ID_N_PARKS .is the process-id of the 'National Parks' menu
C 10 ...ID_HIKING ..is the process-id of the 'Hiking Trails' menu
C 11 ...ID_TOWNS ...is the process-id of the 'Towns and Cities' menu
C 12 ...ID_BIRD_SAN is the process-id of the 'Bird Sanctuaries' menu
C 13 ...ID_HABITAT .is the process-id of the 'Habitats' menu
C 14 ...ID_STATUS ..is the process-id of the 'Status' menu
C 15 ...ID_BIRD_F ..is the process-id of the 'Bird Families' menu
C 16 ...ID_SIZE is the process-id of the 'Bird Size' menu
C 17 ...ID_FEEDING .is the process-id of the 'Feeding' menu
C 18 ...ID_FEATURE .is the process-id of the 'Features' menu
C 19 ...ID_COLORING is the process-id of the 'colorings' menu
C 20 ...ID_MARKING .is the process-id of the 'Markings' menu
C 21 ...ID_UTILITY .is the process-id of the 'Utilities' menu
C 22 ...KEY_ is the character containing the pressed key
C 23 PDL Description:
C 24 ...

Scheduler Process

```

-----P- 5A -P-----
P 1      if SYSTEM_ON is false
61A P 2      format the screen [O-SCREEN-FORMA:]
41A P 3      read bird database from file [O-READ-BIRD-DATA]
P 4      read text data from file [O-READ-TXT-DATA]
P 5      if STATUS is not succesfull [<=0]
P 6          case STATUS_
P 7              of [1], Text file not found;
P 8                  TEXT_ := 'Text file not found'
P 9              of [2], % Charater expected
P 10                 TEXT_ := '% Character expected'
P 11              of [3], %M Expected
P 12                 TEXT_ := '%M Expected'
P 13              of [4], %H Expected
P 14                 TEXT_ := '%H Expected'
P 15          endcase
63A P 16      write TEXT_ to window 4 [O-WRT-W4]
67B P 17      quit program [P-QUIT-PROG]
P 18      else
P 19          read queue data from file [O-READ-Q-DATA]
P 20          SYSTEM_ON := true
38B P 21      compile attribute filter [O-FILL-FILTER]
42A P 22      scan database [O-SCAN]
47A P 23      read number of matched birds [O-READ-NO-OF-MATCHED-BIRDS]
63B P 24      write number to window 5 [O-WRT-W5]
P 25      endif
P 26      endif
P 27      while STOP_ is false
53A P 28          dequeue process-id [O-DEQ]
P 29          if STATUS_ is not succesful [=1]
63A P 30              write "Queue Empty" to window 4 [O-WRT-W4]
67A P 31              wait for a keypress [O-WAIT]
65A P 32              clear window 4 [O-CLR-W4]
P 33          else
P 34              case PROCESS_ID
P 35                  of help
8A P 36                      execute Help Menu Process [P-HELP]
P 37                  of attribute menu
11A P 38                      execute Attribute Menu Process [P-ATTR-MENU]
P 39                  of utilities
13A P 40                      execute Utility Menu Process [P-UTIL]
P 41                  of find main menu
16A P 42                      execute Find Main Menu Process [P-FIND-MENU]
P 43                  of list found birds
18A P 44                      execute List Found Birds Process [P-LIST-FOUND]
P 45                  of clear found birds
19B P 46                      execute Clear Found Birds Process [P-CLEAR-FOUND]
P 47                  of list attributes
21A P 48                      execute List Attributes Process [P-LIST-ATTR]
P 49                  of clear attribute
22B P 50                      execute Clear Attributes Process [P-CLEAR-ATTR]
P 51                  of list matched birds

```

```

24A P 52          execute List Matched Birds Process [P-LIST-MATCHED]
      P 53          of count bird
26A P 54          execute Count Bird Process [P-COUNT-BIRD]
      P 55          of clear bird
27B P 56          execute Clear a Found Bird Process [P-CLEAR-BIRD]
      P 57          endcase
      P 58          endif
      P 59          endwhile

```

Help Process

Help Data Usage

-----C- 7A -C-----

C 1 Public Variables:
C 2 ...PROCESS_ID is the id of the current menu.
C 3 Private Variables:
C 4 ...DISPLACEMENT_ defines vertical scroll direction relative to current position
C 5 ...MENU_TITLE is the title of the current menu.
C 6 ...TEXT_ITEM is the string text of the current menu item.
C 7 ...TEXT_DISPLAY portion of text from the TEXT_ITEM for display on screen.
C 8 ...CONTINUE_ is the boolean variable for the while loop.
C 9 ...STATUS_ is the status report of procedures and functions.
C 10 ...KEY_ is the character containing the pressed key.
C 11 PDL Description:
C 12 ...

Help Menu Process [P-HELP]

```
-----P- 8A -P-----
61B P 1    write "Help" to window 1 [O-WRT-W1]
      P 2    DISPLACEMENT_ := 0
33A P 3    read an item from menu [O-READ-TXT-ITEM]
56A P 4    initialize text [O-INITIAL-TEXT]
62A P 5    write to window 2 [O-WRT-W2]
62B P 6    write to window 3 [O-WRT-W3]
63A P 7    write TEXT_DISPLAY to window 4 [O-WRT-W4]
      P 8    CONTINUE := true
      P 9    while CONTINUE_
      P 10   repeat
      P 11   read keyboard
      P 12   KEY_ := pressed key
      P 13   until KEY_ is (right arrow) (left arrow) or (escape)
      P 14   case KEY_
      P 15   of KEY_LEFT_ARROW
      P 16   move text left [O-MOVE-TXT-LEFT]
62A P 17   write to window 2 [O-WRT-W2]
62B P 18   write to window 3 [O-WRT-W3]
63A P 19   write TEXT_DISPLAY to window 4 [O-WRT-W4]
      P 20   of KEY_RIGHT_ARROW
56A P 21   move text right [O-MOVE-TEXT-RIGHT]
62A P 22   write to window 2 [O-WRT-W2]
62B P 23   write to window 3 [O-WRT-W3]
63A P 24   write TEXT_DISPLAY to window 4 [O-WRT-W4]
      P 25   of KEY_ESCAPE
      P 26   CONTINUE_ := false,
      P 27   endcase
      P 28   endwhile
```

Birds

15 10 1990 PAGE 1 - 9

Attribute Processes

Attribute Menu Data Usage

-----C- 10A -C-----

C 1 Public Variables:
C 2 ...PROCESS_ID == is the id of the current process.
C 3 Private Variables:
C 4 ...DISPLACEMENT_ defines vertical scroll direction relative to current position
C 5 ...MENU_TITLE is the title of the current menu.
C 6 ...TEXT_ITEM is the string text of the current menu item.
C 7 ...TEXT_DISPLAY portion of text from the TEXT_ITEM for display on screen.
C 8 ...CONTINUE_ is the boolean variable for the while loop.
C 9 ...STATUS_ is the status report of procedures and functions.
C 10 ...KEY_ is the character containing the pressed key.
C 11 PDL Description:
C 12 ...
C 13

Attribute Menu Process [P-ATTR-MENU]

```

-----P- 11A -P-----
32A P 1      read title of menu, [O-READ-MENU-TITLE]
61B P 2      write MENU_TITLE to window 1 [O-WRT-W1]
      P 3      DISPLACEMENT_ := 0
33A P 4      read an item from menu [O-READ-TXT-ITEM]
56A P 5      initialize text [O-INITIAL-TEXT]
62A P 6      write to window 2 [O-WRT-W2]
62B P 7      write to window 3 [O-WRT-W3]
63A P 8      write TEXT_DISPLAY to window 4 [O-WRT-W4]
      P 9      CONTINUE_ := TRUE
      P 10     while CONTINUE_
      P 11         repeat
      P 12             read keyboard
      P 13             KEY_ := pressed key
      P 14             until KEY_ is (help) or (mode) or (select) or (left arrow)
      P 15             or (right arrow) or (up arrow) or (down arrow)
      P 16             or (escape) or (quit)
      P 17             case KEY_
      P 18             of KEY_HELP
52A P 19                 enqueue process-id [O-FRONT-ENQ]
      P 20                 PROCESS_ID := HELP_ID
52A P 21                 enqueue process-id [O-FRONT-ENQ]
      P 22                 CONTINUE_ := false
      P 23             of KEY_MODE
52A P 24                 enqueue process-id [O-FRONT-ENQ]
51A P 25                 exchange queue blocks [O-EXCH-Q-BLOCKS]
      P 26                 CONTINUE_ := false
      P 27             of KEY_SELECT
      P 28                 ...enqueue the id of current process in case selected item is another menu
52A P 29                 enqueue process-id [O-FRONT-ENQ]
34A P 30                 update attribute flag [O-UPDATE-ATTR-FLAG]
      P 31                 case STATUS_
      P 32                 of 1
      P 33                     ...selected item points to another menu
52A P 34                     enqueue process-id [O-FRONT-ENQ]
      P 35                     CONTINUE_ := false
      P 36                 of 0
      P 37                     ...selected item was a flag type
53A P 38                     dequeue process-id [O-DEQ]
38B P 39                     compile attribute filter [O-FILL-FILTER]
42A P 40                     scan database [O-SCAN]
47A P 41                     read number of matched birds [O-READ-NO-OF-MATCHED-BIRDS]
53B P 42                     write number to window 5 [O-WRT-W5]
      P 43                     DISPLACEMENT_ := 0
33A P 44                     read an item from menu [O-READ-TXT-ITEM]
56A P 45                     initialize text [O-INITIAL-TEXT]
62A P 46                     write to window 2 [O-WRT-W2]
62B P 47                     write to window 3 [O-WRT-W3]
63A P 48                     write TEXT_DISPLAY to window 4 [O-WRT-W4]
      P 49                 endcase
      P 50             of KEY_UP_ARROW
      P 51                 DISPLACEMENT_ := -1

```

```

33A P 52      read item an from menu [O-READ-TXT-ITEM]
P 53          if STATUS_ = 0
56A P 54              initialise text [O-INITIAL-TEXT]
62A P 55              write to window 2 [O-WRT-W2]
62B P 56              write to window 3 [O-WRT-W3]
63A P 57              write TEXT_DISPLAY to window 4 [O-WRT-W4]
P 58          else
63A P 59              write "Pointers Not Found" to window 4 [O-WRT-W4]
67A P 60              wait for a keypress [O-WAIT]
P 61          endif
P 62      of KEY_DN_ARROW
P 63          DISPLACEMENT_ := +1
33A P 64          read an item from menu [O-READ-TXT-ITEM]
P 65          if STATUS_ is 0
56A P 66              initialise text [O-INITIAL-TEXT]
62A P 67              write to window 2 [O-WRT-W2]
62B P 68              write to window 3 [O-WRT-W3]
63A P 69              write TEXT_DISPLAY to window 4 [O-WRT-W4]
P 70          else
63A P 71              write "Pointers Not Mound" to window 4 [O-WRT-W4]
67A P 72              wait for a keypress [O-WAIT]
P 73          endif
P 74      of KEY_LEFT_ARROW
57A P 75          move text left [O-MOVE-TEXT-LEFT]
62A P 76          write to window 2 [O-WRT-W2]
62B P 77          write to window 3 [O-WRT-W3]
63A P 78          write TEXT_DISPLAY to window 4 [O-WRT-W4]
P 79      of KEY_RIGHT_ARROW
58A P 80          move text right [O-MOVE-TEXT-RIGHT]
62A P 81          write to window 2 [O-WRT-W2]
62B P 82          write to window 3 [O-WRT-W3]
63A P 83          write TEXT_DISPLAY to window 4 [O-WRT-W4]
P 84      of KEY_ESCAPE
P 85          if PROCESS_ID = attribute main menu
P 86              ...do nothing
P 87          else
P 88              ...restore control the main menu
P 89              CONTINUE_ = false
P 90          endif
P 91      of KEY_QUIT
67B P 92          quit program [P-QUIT-PROG]
P 93          CONTINUE_ := false
P 94          STOP_ := true
P 95      endcase
P 96      endwhile

```

Utility Menu Data Usage

-----C- 12A -C-----

C 1 Public Variables:
C 2 ...PROCESS_ID is the id of the current process.
C 3 Private Variables:
C 4 ...DISPLACEMENT_ defines vertical scroll direction relative to current position
C 5 ...MENU_TITLE is the title of the current menu.
C 6 ...TEXT_ITEM is the string text of the current menu item.
C 7 ...TEXT_DISPLAY portion of text from the TEXT_ITEM for display on screen.
C 8 ...CONTINUE_ is the boolean variable for the while loop.
C 9 ...STATUS_ is the status report of procedures and functions.
C 10 ...KEY_ is the character containing the pressed key.
C 11 PDL Description:
C 12 ...

Utility Menu Process [P-UTIL]

```
-----P- 13A -P-----
32A P 1      read title of menu,[O-READ-MENU-TITLE]
61B P 2      write MENU_TITLE to window 1 [O-WRT-W1]
      P 3      DISPLACEMENT_ := 0
33A P 4      read an item from menu [O-READ-TXT-ITEM]
56A P 5      initialize text [O-INITIAL-TEXT]
62A P 6      write to window 2 [O-WRT-W2]
62B P 7      write to window 3 [O-WRT-W3]
63A P 8      write TEXT_DISPLAY to window 4 [O-WRT-W4]
      P 9      CONTINUE_ := TRUE
      P 10     while CONTINUE_
      P 11         repeat
      P 12             read keyboard
      P 13             KEY_ := pressed key
      P 14             until KEY_ is (help) or (mode) or (select) or (left arrow)
      P 15             or (right arrow) or (up arrow) or (down arrow)
      P 16             or (escape) or (quit)
      P 17             case KEY_
      P 18             of KEY_HELP
52A P 19                 enqueue process-id [O-FRONT-ENQ]
      P 20                 PROCESS_ID := HELP_ID
52A P 21                 enqueue process-id [O-FRONT-ENQ]
      P 22                 CONTINUE_ := false
      P 23             of KEY_MODE
52A P 24                 enqueue process-id [O-FRONT-ENQ]
51A P 25                 exchange queue blocks [O-EXCH-Q-BLOCKS]
      P 26                 CONTINUE_ := false
      P 27             of KEY_SELECT
52A P 28                 enqueue process-id [O-FRONT-ENQ]
34A P 29                 update attribute flag [O-UPDATE-ATTR-FLAG]
      P 30                 case STATUS_
      P 31                 of 1
      P 32                     ...selected item points to another menu
52A P 33                     enqueue process-id [O-FRONT-ENQ]
      P 34                     CONTINUE_ := false
      P 35                 of 0
      P 36                     ...selected item was a flag type
53A P 37                     dequeue process-id [O-DEQ]
      P 38                     DISPLACEMENT_ := 0
33A P 39                     read an item from menu [O-READ-TXT-ITEM]
56A P 40                     initialize text [O-INITIAL-TEXT]
62A P 41                     write to window 2 [O-WRT-W2]
62B P 42                     write to window 3 [O-WRT-W3]
63A P 43                     write TEXT_DISPLAY to window 4 [O-WRT-W4]
      P 44                     endcase
      P 45             of KEY_UP_ARROW
      P 46                 DISPLACEMENT_ := -1
33A P 47                 read item an from menu [O-READ-TXT-ITEM]
56A P 48                 initialise text [O-INITIAL-TEXT]
62A P 49                 write to window 2 [O-WRT-W2]
62B P 50                 write to window 3 [O-WRT-W3]
63A P 51                 write TEXT_DISPLAY to window 4 [O-WRT-W4]
```

```

P 52      of KEY_DN_ARROW
P 53          DISPLACEMENT_ := +1
33A P 54      read an item from menu [O-READ-TXT-ITEM]
56A P 55      initialise text [O-INITIAL-TEXT]
62A P 56      write to window 2 [O-WRT-W2]
62B P 57      write to window 3 [O-WRT-W3]
63A P 58      write TEXT_DISPLAY to window 4 [O-WRT-W4]
P 59      of KEY_LEFT_ARROW
57A P 60          move text left [O-MOVE-TEXT-LEFT]
62A P 61          write to window 2 [O-WRT-W2]
62B P 62          write to window 3 [O-WRT-W3]
63A P 63          write TEXT_DISPLAY to window 4 [O-WRT-W4]
P 64      of KEY_RIGHT_ARROW
58A P 65          move text right [O-MOVE-TEXT-RIGHT]
62A P 66          write to window 2 [O-WRT-W2]
62B P 67          write to window 3 [O-WRT-W3]
63A P 68          write TEXT_DISPLAY to window 4 [O-WRT-W4]
P 69      of KEY_ESCAPE
P 70          CONTINUE_ = false
P 71      of KEY_QUIT
67B P 72          quit program [P-QUIT-PROG]
P 73          CONTINUE_ := false
P 74      endcase
P 75      endwhile

```

Find Processes

Find Main Menu Data Usage

-----C- 15A -C-----

C 1 Public Variables:
C 2 ...PROCESS_ID is the id of the current process.
C 3 Private Variables:
C 4 ...DISPLACEMENT_ defines vertical scroll direction relative to current position
C 5 ...MENU_TITLE is the title of the current menu.
C 6 ...TEXT_ITEM is the string text of the current menu item.
C 7 ...TEXT_DISPLAY portion of text from the TEXT_ITEM for display on screen.
C 8 ...CONTINUE_ is the boolean variable for the while loop.
C 9 ...STATUS_ is the status report of procedures and functions.
C 10 ...KEY_ is the character containing the pressed key.
C 11 PDL Description:
C 12 ...
C 13

Find Main Menu Process [P-FIND-MENU]

```

-----P- 16A -P-----
47A P 1      read number of matched birds [O-READ-NO-OF-MATCHED-BIRDS]
63B P 2      write number to window 5 [O-WRT-W5]
32A P 3      read title of menu, [O-READ-MENU-TITLE]
61B P 4      write MENU_TITLE to window 1 [O-WRT-W1]
P 5          DISPLACEMENT_ := 0
33A P 6      read an item from menu [O-READ-TXT-ITEM]
56A P 7      initialize text [O-INITIAL-TEXT]
62A P 8      write to window 2 [O-WRT-W2]
62B P 9      write to window 3 [O-WRT-W3]
63A P 10     write TEXT_DISPLAY to window 4 [O-WRT-W4]
P 11         CONTINUE_ = true
P 12         while CONTINUE_
P 13             repeat
P 14                 read keyboard
P 15                 KEY_ := pressed key
P 16                 until KEY_ is (help) or (mode) or (select) or (left arrow)
P 17                 or (right arrow) or (up arrow) or (down arrow) or (quit)
P 18                 case KEY_
P 19                     of KEY_HELP
52A P 20                         enqueue process-id [O-FRONT-ENQ]
P 21                         PROCESS_ID := HELP_ID
52A P 22                         enqueue process-id [O-FRONT-ENQ]
P 23                         CONTINUE_ := false
P 24                     of KEY_MODE
52A P 25                         enqueue process-id [O-FRONT-ENQ]
51A P 26                         exchange queue blocks [O-EXCH-Q-BLOCKS]
P 27                         CONTINUE_ := false
P 28                     of KEY_SELECT
P 29                         ...enqueue the id of current process in case selected item is another menu
52A P 30                         enqueue process-id [O-FRONT-ENQ]
34A P 31                         update attribute flag [O-UPDATE-ATTR-FLAG]
P 32                         case STATUS_
P 33                             of 1
P 34                                 ...selected item points to another menu
52A P 35                                 enqueue process-id [O-FRONT-ENQ]
P 36                                 CONTINUE_ := false
P 37                             of 0
P 38                                 ...selected .cm was a flag type
53A P 39                                 dequeue process-id [O-DEQ]
38B P 40                                 compile attribute filter [O-FILL-FILTER]
42A P 41                                 scan database [O-SCAN]
47A P 42                                 read number of matched birds [O-READ-NO-OF-MATCHED-BIRDS]
63B P 43                                 write number to window 5 [O-WRT-W5]
P 44                                 DISPLACEMENT_ := 0
33A P 45                                 read an item from menu [O-READ-TXT-ITEM]
56A P 46                                 initialize text [O-INITIAL-TEXT]
62A P 47                                 write to window 2 [O-WRT-W2]
62B P 48                                 write to window 3 [O-WRT-W3]
63A P 49                                 write TEXT_DISPLAY to window 4 [O-WRT-W4]
P 50                                 endcase
P 51                         of KEY_UP_ARROW

```

```

P 52      DISPLACEMENT_ := -1
33A P 53      read item an from menu [O-READ-TXT-ITEM]
56A P 54      initialise text [O-INITIAL-TEXT]
62A P 55      write to window 2 [O-WRT-W2]
62B P 56      write to window 3 [O-WRT-W3]
63A P 57      write TEXT_DISPLAY to window 4 [O-WRT-W4]
P 58      of KEY_DN_ARROW
P 59      DISPLACEMENT_ := +1
33A P 60      read an item from menu [O-READ-TXT-ITEM]
56A P 61      initialise text [O-INITIAL-TEXT]
62A P 62      write to window 2 [O-WRT-W2]
62B P 63      write to window 3 [O-WRT-W3]
63A P 64      write TEXT_DISPLAY to window 4 [O-WRT-W4]
P 65      of KEY_LEFT_ARROW
57A P 66      move text left [O-MOVE-TEXT-LEFT]
62A P 67      write to window 2 [O-WRT-W2]
62B P 68      write to window 3 [O-WRT-W3]
63A P 69      write TEXT_DISPLAY to window 4 [O-WRT-W4]
P 70      of KEY_RIGHT_ARROW
58A P 71      move text right [O-MOVE-TEXT-RIGHT]
62A P 72      write to window 2 [O-WRT-W2]
62B P 73      write to window 3 [O-WRT-W3]
63A P 74      write TEXT_DISPLAY to window 4 [O-WRT-W4]
P 75      of KEY_ESCAPE
P 76      if PROCESS_ID = attribute main menu
P 77      ...do nothing
P 78      else
P 79      ...restore control the main menu
P 80      CONTINUE_ = false
P 81      endif
P 82      of KEY_QUIT
67B P 83      quit program [P-QUIT-PROG]
P 84      CONTINUE_ := false
P 85      endcase
P 86      endwhile

```

List Found Birds Data Usage

-----C- 17A -C-----

C 1 Public Variables:
C 2 ...PROCESS_ID is the id of the current process.
C 3 Private Variables:
C 4 ...DISPLACEMENT_ defines vertical scroll direction relative to current position
C 5 ...MENU_TITLE is the title of the current menu.
C 6 ...TEXT_ITEM is the string text of the current menu item.
C 7 ...TEXT_DISPLAY portion of text from the TEXT_ITEM for display on screen.
C 8 ...CONTINUE_ is the boolean variable for the while loop.
C 9 ...STATUS_ is the status report of procedures and functions.
C 10 ...KEY_ is the character containing the pressed key.
C 11 ...NO_OF_FOUND_BIRDS is number of found birds
C 12 PDL Description:
C 13 ...
C 14

List Found Birds Process (P-LIST-FOUND)

-----P- 18A -P-----

```

45A P 1      read number of found birds [O-READ-NO-OF-FOUND-BIRDS]
63B P 2      write number to window 5 [O-WRT-W5]
P 3          if NO_OF_FOUND_BIRDS = 0
61B P 4              write 'List is Clear' to window 1 [O-WRT-W1]
63A P 5              write 'Esc to continue' to window 4 [O-WRT-W4]
P 6              repeat
P 7                  read keyboard
P 8              until Escape is pressed
P 9          else
P 10             if LAST_PROCESS_ID is (find) or (clear bird) or
P 11                 (bird count and bird count is zero)
P 12                 DISPLACEMENT_ := 0
45B P 13                 list found birds [O-LIST-FOUND-BIRDS]
P 14             endif
61B P 15             write BIRD_COUNT to window 1 [O-WRT-W1]
63A P 16             write BIRD_NAME to window 4 [O-WRT-W4]
37A P 17             read list found method [O-READ-LIST-FOUND-METHOD]
P 18             CONTINUE_ = true
P 19             while CONTINUE_
P 20                 repeat
P 21                     read keyboard
P 22                     KEY_ := pressed key
P 23                     until KEY_ is (help) or (mode) or (select) or (left arrow)
P 24                         or (right arrow) or (up arrow) or (down arrow) or (count)
P 25                     case KEY_
P 26                     of KEY_HELP
52A P 27                         enqueue process-id [O-FRONT-ENQ]
P 28                         PROCESS_ID := HELP_ID
52A P 29                         enqueue process-id [O-FRONT-ENQ]
P 30                         CONTINUE_ := false
P 31                     of KEY_MODE
52A P 32                         enqueue process-id [O-FRONT-ENQ]
51A P 33                         exchange queue blocks [O-EXCH-Q-BLOCKS]
P 34                         CONTINUE_ := false
P 35                     of KEY_SELECT
52A P 36                         enqueue process-id [O-FRONT-ENQ]
P 37                         case listing method in list found birds
P 38                         of count bird
P 39                             PROCESS_ID := count bird
P 40                         of CLEAR BIRD
P 41                             PROCESS_ID := clear bird
P 42                         ondease
52A P 43                         enqueue process-id [O-FRONT-ENQ]
P 44                         CONTINUE_ := false
P 45                     of KEY_UP_ARROW
P 46                         DISPLACEMENT_ := -1
45B P 47                         read list of found birds [O-LIST-FOUND-BIRDS]
61B P 48                         write BIRD_COUNT to window 1 [O-WRT-W1]
63A P 49                         write BIRD_NAME to window 4 [O-WRT-W4]
P 50                     of KEY_DN_ARROW
P 51                         DISPLACEMENT_ := +1

```

```

45B P 52      read list of found birds [O-LIST-FOUND-BIRDS]
61B P 53      write BIRD_COUNT to window 1 [O-WRT-W1]
63A P 54      write BIRD_NAME to window 4 [O-WRT-W4]
P 55          of KEY_ESCAPE
P 56          CONTINUE_ = false
P 57          of KEY_QUIT
67B P 58      quit program [P-QUIT-PRG]
P 59          CONTINUE_ := false
P 60          STOP_ := true
P 61          endcase
P 62          endwhile
P 63      endif

```

Clear Found Birds Data Usage

```
-----C- 19A -C-----
C 1    Public Variables:
C 2    ...PROCESS_ID is the id of the current process.
C 3    Private Variables:
C 4    ...MENU_TITLE is the title of the current menu.
C 5    ...TEXT_ITEM is the string text of the current menu item.
C 6    ...TEXT_DISPLAY portion of text from the TEXT_ITEM for display on screen.
C 7    ...CONTINUE_ is the boolean variable for the while loop.
C 8    ...STATUS_ is the status report of procedures and functions.
C 9    ...KEY_ is the character containing the pressed key.
C 10   PDL Description:
C 11   ...
C 12
```

Clear Found Birds Process [P-CLEAR-FOUND]

```
-----P- 19B -P-----
61B P 1    write 'Clear' to window 1 [O-WRT-W1]
63A P 2    write 'Esc=abort se' to window 4 [O-WRT-W4]
P 3    repeat
P 4        read keyboard
P 5        KEY_ := pressed key
P 6    until KEY_ is (help) or (mode) or (select)
P 7    or (left arrow) or (escape)
P 8    case KEY_
P 9    of KEY_HELP
52A P 10        enqueue process-id [O-FRONT-ENQ]
P 11        PROCESS_ID := HELP_ID
52A P 12        enqueue process-id [O-FRONT-ENQ]
P 13        CONTINUE_ := false
P 14    of KEY_MODE
52A P 15        enqueue process-id [O-FRONT-ENQ]
51A P 16        exchange queue blocks [O-EXCH-Q-BLOCKS]
P 17        CONTINUE_ := false
P 18    of KEY_SELECT
46A P 19        clear found birds [O-CLEAR-FOUND-BIRDS]
P 20    of KEY_ESCAPE
P 21        ...do nothing
P 22    endcase
```

List Attributes Data Usage

-----C- 20A -C-----

C 1 Public Variables:
C 2 ...PROCESS_ID is the id of the current process.
C 3 Private Variables:
C 4 ...DISPLACEMENT_ defines vertical scroll direction relative to current position
C 5 ...MENU_TITLE is the title of the current menu.
C 6 ...TEXT_ITEM is the string text of the current menu item.
C 7 ...TEXT_DISPLAY portion of text from the TEXT_ITEM for display on screen.
C 8 ...CONTINUE_ is the boolean variable for the while loop.
C 9 ...STATUS_ is the status report of procedures and functions.
C 10 ...KEY_ is the character containing the pressed key.
C 11 PDL Description:
C 12 ...
C 13

List Attributes Process [P-LIST-ATTR]

```

-----P- 21A -P-----
35A P 1      [O-READ-NO-OF-SELECTED-ATTRIBUTES]
63B P 2      write number to window 5 [O-WRT-W5]
      P 3      if NO_OF_SELECTED_ATTRIBUTES is zero
61B P 4          write 'none selected' to window 1 [O-WRT-W1]
63A P 5          write 'Esc to continue' to window 4 [O-WRT-W4]
      P 6          repeat
      P 7              read keyboard
      P 8              KEY_ := pressed key
      P 9              until KEY_ is (escape)
      P 10         else
      P 11             DISPLACEMENT_ := 0
36B P 12         list selected attributes [O-LIST-SELECTED-ATTRIBUTES]
61B P 13         write title to window 1 [O-WRT-W1]
63A P 14         write item to window 4 [O-WRT-W4]
      P 15         CONTINUE_ := true
      P 16         while CONTINUE_
      P 17             repeat
      P 18                 read keyboard
      P 19                 KEY_ := pressed key
      P 20                 until KEY_ is (help) or (mode) or (select) or (left arrow)
      P 21                 or (right arrow) or (up arrow) or (down arrow) or
      P 22                 or (escape) or (quit)
      P 23                 case KEY_
      P 24                 of KEY_HELP
52A P 25                     enqueue process-id [O-FRONT-ENQ]
      P 26                     PROCESS_ID := HELP_ID
52A P 27                     enqueue process-id [O-FRONT-ENQ]
      P 28                     CONTINUE_ := false
      P 29                 of KEY_MODE
52A P 30                     enqueue process-id [O-FRONT-ENQ]
51A P 31                     exchange queue blocks [O-EXCH-Q-BLOCKS]
      P 32                     CONTINUE_ := false
      P 33                 of KEY_SELECT
61B P 34                     write 'Clear' to window 1 [O-WRT-W1]
63A P 35                     write 'Esc=abort Sel=affirm' to window 4 [O-WRT-W4]
      P 36                     repeat
      P 37                         read keyboard
      P 38                         KEY_ := pressed key
      P 39                         until KEY_ is (select) or (escape)
      P 40                         case KEY_
      P 41                         of KEY_SELECT
36A P 42                             clear attribute [O-CLEAR-ATTRIBUTES]
38B P 43                             compile attribute filter [O-FILL-FILTER]
42A P 44                             scan database [O-SCAN]
35A P 45                             [O-READ-NO-OF-SELECTED-ATTRIBUTES]
63B P 46                             write number to window 5 [O-WRT-W5]
      P 47                             if NO_OF_SELECTED_ATTRIBUTES is zero
61B P 48                                 write 'none selected' to window 1 [O-WRT-W1]
63A P 49                                 write 'Esc to continue' to window 4 [O-WRT-W4]
      P 50                                 repeat
      P 51                                     read keyboard

```

```

P 52             KEY_ := pressed key
P 53             until KEY_ is (escape)
P 54             CONTINUE_ := false
P 55             else
P 56             DISPLACEMENT_ := 0
36B P 57         list selected attributes [O-LIST-SELECTED-ATTRIBUTES]
P 58             endif
P 59             if CONTINUE_ <> FALSE
61B P 60         write title to window 1 [O-WRT-W1]
63A P 61         write item to window 4 [O-WRT-W4]
P 62             endif
P 63             endcase
P 64         of KEY_UP_ARROW
P 65         DISPLACEMENT_ := -1
36B P 66         list selected attributes [O-LIST-SELECTED-ATTRIBUTES]
61B P 67         write title to window 1 [O-WRT-W1]
63A P 68         write item to window 4 [O-WRT-W4]
P 69         of KEY_DN_ARROW
P 70         DISPLACEMENT_ := +1
36B P 71         list selected attributes [O-LIST-SELECTED-ATTRIBUTES]
61B P 72         write title to window 1 [O-WRT-W1]
63A P 73         write item to window 4 [O-WRT-W4]
P 74         of KEY_LEFT_ARROW
57A P 75         move text left [O-MOVE-TEXT-LEFT]
62A P 76         write to window 2 [O-WRT-W2]
62B P 77         write to window 3 [O-WRT-W3]
63A P 78         write TEXT_DISPLAY to window 4 [O-WRT-W4]
P 79         of KEY_RIGHT_ARROW
58A P 80         move text right [O-MOVE-TEXT-RIGHT]
62A P 81         write to window 2 [O-WRT-W2]
62B P 82         write to window 3 [O-WRT-W3]
63A P 83         write TEXT_DISPLAY to window 4 [O-WRT-W4]
P 84         of KEY_ESCAPE
P 85         CONTINUE_ = false
P 86         of KEY_QUIT
67B P 87         quit program [P-QUIT-PROG]
P 88         CONTINUE_ := false
P 89         STOP_ := true
P 90             endcase
P 91         endwhile
P 92     endif

```

Clear Attribute Data Usage

```
-----C- 22A -C-----  
  
C 1    Public Variables:  
C 2    ...PROCESS_ID is the id of the current process.  
C 3    Private Variables:  
C 4    ...MENU_TITLE is the title of the current menu.  
C 5    ...TEXT_ITEM is the string text of the current menu item.  
C 6    ...TEXT_DISPLAY portion of text from the TEXT_ITEM for display on screen.  
C 7    ...CONTINUE_ is the boolean variable for the while loop.  
C 8    ...STATUS_ is the status report of procedures and functions.  
C 9    ...KEY_ is the character containing the pressed key.  
C 10   PDL Description:  
C 11   ...  
C 12
```

Clear Attributes Process [P-CLEAR-ATTR]

```
-----P- 22B -P-----  
  
61B P 1    write clear message to window 1 [O-WRT-W1]  
63A P 2    write 'Esc=abort;$el=affirm' to window 4 [O-WRT-W4]  
P 3    repeat  
P 4        read keyboard  
P 5        KEY_ := pressed key  
P 6    until KEY_ is (help) or (mode) or (select) or (escape)  
P 7    case KEY_  
P 8    of KEY_HELP  
52A P 9        enqueue process-id [O-FRONT-ENQ]  
P 10        PROCESS_ID := HELP_ID  
52A P 11        enqueue process-id [O-FRONT-ENQ]  
P 12        CONTINUE_ := false  
P 13    of KEY_MODE  
52A P 14        enqueue process-id [O-FRONT-ENQ]  
51A P 15        exchange queue blocks [O-EXCH-Q-BLOCKS]  
P 16        CONTINUE_ := false  
P 17    of KEY_SELECT  
35B P 18        clear all attributes [O-CLEAR-ALL-ATTRIBUTES]  
38B P 19        compile attribute filter [O-FILL-FILTER]  
42A P 20        scan database [O-SCAN]  
47A P 21        [O-READ-NO-OF-HATCHED-BIRDS]  
63B P 22        write number to window 5 [O-WRT-W5]  
P 23    of KEY_ESCAPE  
P 24        CONTINUE_ = false  
P 25    endcase
```

List Matched Birds Data Usage

-----C- 23A -C-----

C 1 Public Variables:
C 2 ...PROCESS_ID is the id of the current process.
C 3 Private Variables:
C 4 ...DISPLACEMENT_ defines vertical scroll direction relative to current position
C 5 ...MENU_TITLE is the title of the current menu.
C 6 ...TEXT_ITEM is the string text of the current menu item.
C 7 ...TEXT_DISPLAY portion of text from the TEXT_ITEM for display on screen.
C 8 ...CONTINUE_ is the boolean variable for the while loop.
C 9 ...STATUS_ is the status report of procedures and functions.
C 10 ...KEY_ is the character containing the pressed key.
C 11 ...NO_OF_MATCHED_BIRDS is number of matched birds
C 12 PDL Descriptions:
C 13 ...
C 14

List Matched Birds Process

```

-----P- 24A -P-----
47A P 1      read number of matched birds [O-READ-NO-OF-MATCHED-BIRDS]
63B P 2      write number to window 5 [O-WRT-W5]
P 3          if NO_OF_MATCHED_BIRDS is zero
61B P 4          write 'Not found' to window 1 [O-WRT-W1]
63A P 5          write 'ESC to continue' to window 4 [O-WRT-W4]
P 6          repeat
P 7              read keyboard
P 8              KEY_ := pressed key
P 9              until KEY_ is (escape)
P 10             if (LAST_PROCESS_ID <> help) or LAST_PROCESS_ID <> (bird count)
P 11             DISPLACEMENT_ := 0
43A P 12         list matched birds [O-LIST-MATCHED-BIRDS]
P 13         endif
63A P 14         write BIRD_NAME to window 4 [O-WRT-W4]
61B P 15         write BIRD_FAMILY to window 1 [O-WRT-W1]
P 16         CONTINUE_ := false
P 17         while CONTINUE_
38A P 18             read list matched method [O-READ-LIST-MATCHED-METHOD]
P 19             repeat
P 20                 read keyboard
P 21                 KEY_ := pressed key
P 22                 until KEY_ is (help) or (mode) or (select) or (left arrow)
P 23                 or (right arrow) or (up arrow) or (down arrow) or
P 24                 or (escape) or (quit)
P 25                 case KEY_
P 26                 of KEY_HELP
52A P 27                     enqueue process-id [O-FRONT-ENQ]
P 28                     PROCESS_ID := HELP_ID
52A P 29                     enqueue process-id [O-FRONT-ENQ]
P 30                     CONTINUE_ := false
P 31                 of KEY_MODE
52A P 32                     enqueue process-id [O-FRONT-ENQ]
51A P 33                     exchange queue blocks [O-EXCH-Q-BLOCKS]
P 34                     CONTINUE_ := false
P 35                 of KEY_SELECT
52A P 36                     enqueue process-id [O-FRONT-ENQ]
P 37                     case LIST_MATCHED_METHOD
P 38                     of bird count
P 39                         PROCESS_ID := bird count
P 40                     of bird call
P 41                         PROCESS_ID := bird call
P 42                     of bird image
P 43                         PROCESS_ID := bird image
P 44                     of bird info
P 45                         PROCESS_ID := bird info
P 46                     endcase
52A P 47                     enqueue process-id [O-FRONT-ENQ]
P 48                     CONTINUE_ := false
P 49                 of KEY_UP_ARROW
P 50                     DISPLACEMENT_ := -1
43A P 51             read list of matched birds [O-LIST-MATCHED-BIRDS]

```

```

61B P 52          write BIRD_FAMILY to window 1 [O-WRT-W1]
63A P 53          write BIRD_NAME to window 4 [O-WRT-W4]
        P 54      of KEY_DN_ARROW
        P 55          DISPLACEMENT_ := +1
43A P 56          read list of matched birds [O-LIST-MATCHED-BIRDS]
61B P 57          write BIRD_FAMILY to window 1 [O-WRT-W1]
63A P 58          write BIRD_NAME to window 4 [O-WRT-W4]
        P 59      of KEY_LEFT_ARROW
57A P 60          move text left [O-MOVE-TEXT-LEFT]
62A P 61          write to window 2 [O-WRT-W2]
62B P 62          write to window 3 [O-WRT-W3]
63A P 63          write TEXT_DISPLAY to window 4 [O-WRT-W4]
        P 64      of KEY_RIGHT_ARROW
58A P 65          move text right [O-MOVE-TEXT-RIGHT]
62A P 66          write to window 2 [O-WRT-W2]
62B P 67          write to window 3 [O-WRT-W3]
63A P 68          write TEXT_DISPLAY to window 4 [O-WRT-W4]
        P 69      of KEY_ESCAPE
        P 70          CONTINUE_ = false
        P 71      of KEY_QUIT
67B P 72          quit program [P-QUIT-PROG]
        P 73          CONTINUE_ := false
        P 74          STOP_ := true
        P 75      endcase
        P 76      endwhile
        P 77      endif

```

Bird Count Data Usage

-----C- 25A -C-----

C 1 Public Variables:
C 2 ...PROCESS_ID is the id of the current process.
C 3 Private Variables:
C 4
C 5
C 6 ...DISPLACEMENT_ defines vertical scroll direction relative to current position
C 7 ...MENU_TITLE is the title of the current menu.
C 8 ...TEXT_ITEM is the string text of the current menu item.
C 9 ...TEXT_DISPLAY portion of text from the TEXT_ITEM for display on screen.
C 10 ...CONTINUE_ is the boolean variable for the while loop.
C 11 ...STATUS_ is the status report of procedures and functions.
C 12 ...KEY_ is the character containing the pressed key.
C 13 PDL Description:
C 14 ...
C 15

Count Bird Process [P-COUNT-BIRD]

-----P- 26A -P-----

```
P 1    if LAST_PROCESS_ID =(bird count) or (help)
P 2        DISPLACEMENT_ := 0
44B P 3        list bird count [O-CHANGE-BIRD-COUNT]
P 4    endif
P 5    CONTINUE_ := true
P 6    while CONTINUE_
38A P 7        read list matched method [O-READ-LIST-MATCHED-METHOD]
P 8        repeat
P 9            read keyboard
P 10           KEY_ := pressed key
P 11           until KEY_ is (help) or (mode) or (escape) or (quit)
P 12           or (up arrow) or (down arrow)
P 13           case KEY_
P 14           of KEY_HELP
52A P 15               enqueue process-id [O-FRONT-ENQ]
P 16                   PROCESS_ID := HELP_ID
52A P 17               enqueue process-id [O-FRONT-ENQ]
P 18                   CONTINUE_ := false
P 19           of KEY_MODE
52A P 20               enqueue process-id [O-FRONT-ENQ]
51A P 21               exchange queue blocks [O-EXCH-Q-BLOCKS]
P 22                   CONTINUE_ := false
P 23           of KEY_UP_ARROW
P 24               DISPLACEMENT_ := 1
44B P 25               change bird count [O-CHANGE-BIRD-COUNT]
61B P 26               write bird count to window 1 [O-WRT-W1]
P 27           of KEY_DN_ARROW
P 28               DISPLACEMENT_ := -1
44B P 29               change bird count [O-CHANGE-BIRD-COUNT]
61B P 30               write bird count to window 1 [O-WRT-W1]
P 31           of KEY_ESCAPE
P 32               CONTINUE_ := false
P 33           of KEY_QUIT
67B P 34               quit program [P-QUIT-PROG]
P 35           endcase
P 36       endwhile
```

Clear a Found Bird Data Usage

```
-----C- 27A -C-----
C 1   Public Variables:
C 2   ...PROCESS_ID is the id of the current process.
C 3   Private Variables:
C 4   ...MENU_TITLE is the title of the current menu.
C 5   ...TEXT_ITEM is the string text of the current menu item.
C 6   ...TEXT_DISPLAY portion of text from the TEXT_ITEM for display on screen.
C 7   ...CONTINUE_ is the boolean variable for the while loop.
C 8   ...STATUS_ is the status report of procedures and functions.
C 9   ...KEY_ is the character containing the pressed key.
C 10  PDL Description:
C 11  ...
C 12
```

Clear a Found Bird Process [P-CLEAR-BIRD]

```
-----P- 27B -P-----
61B P 1   write clear message to window 1 [O-WRT-W1]
63A P 2   write 'Esc=abort;Sel=affirm' to window 4 [O-WRT-W4]
P 3   repeat
P 4       read keyboard
P 5       KEY_ := pressed key
P 6   until KEY_ is (help) or (mode) or (select) or (escape)
P 7   case KEY_
P 8   of KEY_HELP
52A P 9       enqueue process-id [O-FRONT-ENQ]
P 10        PROCESS_ID := HELP_ID
52A P 11      enqueue process-id [O-FRONT-ENQ]
P 12        CONTINUE_ := false
P 13   of KEY_MODE
52A P 14      enqueue process-id [O-FRONT-ENQ]
51A P 15      exchange queue blocks [O-EXCH-Q-BLOCKS]
P 16        CONTINUE_ := false
P 17   of KEY_SELECT
46B P 18      clear bird [O-CLEAR-BIRD]
P 19        LAST_PROCESS_ID := PROCESS_ID
P 20   of KEY_ESCAPE
P 21      ...do nothing
P 22   endcase
```

Text Menu Resource

Data Usage

-----C- 29A -C-----

C 1 Public Variables:
C 2 ...PROCESS_ID is the process-id of the current/invoked process
C 3 Private Variables:
C 4 ...TXT_ARY is the array containing the text of the menus
C 5 ...FLAG_ARY is the array containing select flag /process id of next process
C 6 ...FLAG_NO_ARY is the array containing flag numbers. This information
C 7 is used to indicate if the feature belongs to a group which does
C 8 not allow multiple selections.
C 9 ...NEXT_ID is id of the next menu to which the current item is pointing
C 10 ...KEY_ARY array of type record; it serves to conserve the context of each process.
C 11 ...PROCESS_ID is the id of current menu
C 12 ...MENU_TITLE is the title of the current menu
C 13 ...HELP is a string of text containig help information
C 14 ...C_POINTER is the pointer to the current menu item supported by TXT_ARY
C 15 ...F_POINTER is the pointer to the first menu item supported by TXT_ARY
C 16 ...L_POINTER is the pointer to the last menu item supported by TXT_ARY
C 17 ...NO_OF_SELECTED_ATTRIBUTES stores the number of selected attributes
C 18

Behavior

-----C- 29B -C-----

C 1 This resource supports the data structure of the text within the various menus as +++
C 2 The resource supports the operations made to access the data structure.
C 3 List of Operations:
C 4

O-READ-MENU-FILE

```

-----P- 30A -P-----
P 1    ...1)O-READ-MENU-FILE () STATUS_
P 2    ...Data Usage:
P 3    .....External: none
P 4    .....Private:
P 5    .....Variable:
P 6    .....LINE_ is a line counter of data file TEXT_DAT.TXT
P 7    .....NO_OF_LINES is the number of lines in the data file
P 8    .....TMP_ARY is a temp array for data
P 9    .....C_POINTER ...points to the current entry in the menu
P 10   .....F_POINTER ...points to the first entry in the menu
P 11   .....L_POINTER ...points to the last entry in the menu
P 12   ...Behavior:
P 13   .....This operation retrieves the text structure from file, TEXT_DAT.TXT when pro++
P 14   ...Interface:
P 15   .....Input: None
P 16   .....Output:
P 17   .....STATUS_ has the outcome of
P 18   .....0: operation succesfull
P 19   .....2: error in file format: must start with %
P 20   .....3: error if nile format: M expected after this %
P 21   .....4: error in file format: % expected after this %
P 22   ...PDL Description:
P 23   ...
P 24   line pointer := 1 [LINE_ :=1]
P 25   while end of file is not encountered
P 26       read first line from file TEXT_DAT.TXT and write to TEXT_
P 27       write TEXT_ to temproray array at position line pointer [LINE_]
P 28       increment line poiner [LINE_]
P 29   endwhile
P 30   record pointer := 0 [REC_:=0]
P 31   number of lines := (line pointer - 1) [NO_OF_LINES := LINE_ -1]
P 32   line pointer := 1 [LINE_:=1]
P 33   CONTINUE_ := true
P 34   while (LINE_ is less than NO_OF_LINES) and (CONTINUE is true)
P 35       increment record pointer [REC_]
P 36       number of records := record pointer [NO_O_REC:=REC_]
P 37       CHAR_ := first character in temp array [TMP_ARY], position:[LINE_]
P 38       if CHAR_ is not "%"
P 39           STATUS_ := 2 & CONTINUE_ := false
P 40       else
P 41           CHAR_ := second charcter in temp array [TMP_ARY], position:[LINE_]
P 42           if CHAR_ is not "N"
P 43               STATUS_ := 3 & CONTINUE_ := false
P 44           else
P 45               STATUS_ := 0 & increment line pointer [LINE_]
P 46               PROCESS_ID := text in temp array [TMP_ARY]: position:[LINE_]
P 47               increment line pointer [LINE_]
P 48               MENU_TITLE := text in temp array [TMP_ARY]: position:[LINE_]
P 49               increment line pointer [LINE_]
P 50               C_POINTER := value of text in temp array [TMP_ARY]: position:[LINE_]
P 51               increment line number [LINE_]

```

```

P 52      F_POINTER := (line number [LINE_]
P 53      CHAR_ := first character in temp array [TMP_ARY]: position:[LINE_]
P 54      I_ := 1
P 55      while CHAR_ is not "X"
P 56          text array [TXT_ARY]: position I_ := temporary array [TMP_ARY]: pos+++
P 57          increment line number [LINE_]
P 58          flag array [FLAG_ARY]: position I_ := temporary array [TMP_ARY]: pos+++
P 59          increment I_ & increment line number [LINE_]
P 60          CHAR_ := first character of text in temporary array [TMP_ARY]: pos+++
P 61      endwhile
P 62      L_POINTER := (line number [LINE_] - F_POINTER) / 2
P 63      CHAR_ := second character of text in temporary array [TMP_ARY]: position+++
P 64      if CHAR_ is not "H"
P 65          STATUS_ := 4 & CONTINUE_ := false
P 66      else
P 67          increment line number [LINE_]
P 68          H_F_POINTER := line number [LINE_]
P 69          if line number <= number of lines [LINE_<NO_OF_LINES]
P 70              I_ := 1
P 71              CHAR_ := first character of text in temporary array [TMP_ARY]: pos+++
P 72              repeat
P 73                  help array [HELP_ARY]: position I_ := temporary array [TMP_ARY]+++
P 74                  increment line number [LINE_] & increment I_
P 75                  CHAR_ := first character of text in temporary array [TMP_ARY]+++
P 76                  until (line number [LINE_] > number of lines [NO_OF_LINES]) or+++
P 77                  H_L_POINTER := line number [LINE_] - H_F_POINTER
P 78              else
P 79                  H_F_POINTER := 0
P 80                  H_L_POINTER := 0
P 81              endif
P 82          endif
P 83      endif
P 84  endif
P 85  endwhile

```

O-WRITE-MENU-FILE

-----p- 31A -p-----

```
P 1    ...2) O-WRITE-MENU-FILE ()
P 2    ...Data Usage:
P 3    .....External: none
P 4    .....Private:
P 5    .....Variable:
P 6    .....TXT_ARY text array of menus
P 7    .....FLAG_ARY flag array of attributes
P 8    ...Behavior:
P 9    .....This operation will write the selected attributes to the file
P 10   .....TEXT_DAT.TXT, before terminating program.
P 11   ...Interface:
P 12   .....Input: None
P 13   .....Output: None
P 14   ...PDL Descriptions:
P 15   ...
P 16   record pointer [REC_] := 1
P 17   while record pointer [REC_] <= number of records [NO_OF_REC]
P 18       write "XH" to file TEXT_DAT.TXT
P 19       write PROCESS_ID to file
P 20       write MENU_TITLE to file
P 21       write C_POINTER to file
P 22       I_ := 1
P 23       while I_ <= C_POINTER
P 24           write text array [TEXT_ARY]: position I_ to file
P 25           write flag array [FLAG_ARY]: position I_ to file
P 26           increment I_
P 27       endwhile
P 28       write "XH" to file
P 29       I_ := 1
P 30       while I_ <= H_L_POINTER
P 31           write help array [HELP_ARY]: position I_ to file
P 32           increment I_
P 33       endwhile
P 34       increment record pointer [REC_]
P 35   endwhile
```

O-READ-MENU-TITLE

-----P- 32A -P-----

```
P 1    ...3) O-READ-MENU-TITLE () MENU_TITLE, STATUS_  
P 2    ...Data Usage:  
P 3    .....Extrenal: none  
P 4    .....Private: none  
P 5    ...Behavior:  
P 6    .....This operation reads the title of the current menu  
P 7    ...Interfaces:  
P 8    .....Input: none  
P 9    .....Output:  
P 10    .....MENU_TITLE title of the current menu passed to the invoking process, throu++  
P 11    .....STATUS_ has the outcome of  
P 12    .....0 - successful  
P 13    .....1 - unsuccessful / requested process-id was not found in data file  
P 14    ...PDL Description:  
P 15    ...  
P 16    record pointer [REC_] := 1  
P 17    CONTINUE_ := true  
P 18    while CONTINUE_  
P 19        if PROCESS_ID is the same as MENUS_ARY: position record pointer [REC_]  
P 20            current record := record pointer [C_REC, REC_]  
P 21            CONTINUE_ is false  
P 22        else  
P 23            increment record pointer [REC_]  
P 24        endif  
P 25    endwhile  
P 26    if record pointer [REC_] > number of records [NO_ REC]  
P 27        STATUS_ := 1  
P 28    else  
P 29        STATUS_ := 0  
P 30        MENU_TITLE := title specified by MENUS_ARY: position current record [C_REC]  
P 31    endif
```

O-READ-TXT-ITEM

```

-----P- 33A -P-----
P 1    ...4) O-READ-TXT-ITEM (DISPLACEMENT_) TEXT_ITEM, STATUS_
P 2    ...Data Usage:
P 3    .....External:
P 4    .....Variable:
P 5    .....REV_W4 is reverse video indicator of window 4 write operation performed+++
P 6    .....on this data item read operation performed in Screen Resource
P 7    .....Private:
P 8    .....Variable:
P 9    .....H_C_POINTER is the pointer to the current line of help
P 10   ...Behavior:
P 11   .....This operation reads the line of text at the current/above/below
P 12   .....text position. The relative displacement is defined by the value
P 13   .....of DISPLACEMENT_. This text is then written into the data item
P 14   .....TEXT_ITEM for access by scroll manager resource. The current
P 15   .....PROCESS_ID activates the relevant pointers.
P 16   ...Interface:
P 17   .....Input:
P 18   .....DISPLACEMENT_ specifies the requested text is at current/above/below curr+++
P 19   .....0 - requested text is at current position
P 20   .....+1 - requested text is above current position
P 21   .....-1 - requested text is below current position
P 22   .....Output:
P 23   .....TEXT_ITEM returns the line of text from the data structure
P 24   .....STATUS_ has the outcome of
P 25   .....0 - successful
P 26   ...PDL Description:
P 27   ...
P 28   if PROCESS_ID is ID_HELP
P 29       case DISPLACEMENT_
P 30       of 0
P 31           H_C_POINTER := 1
P 32       of -1
P 33           if H_C_POINTER <> H_L_POINTER
P 34               decrement H_C_POINTER
P 35           endif
P 36       of +1
P 37           if H_C_POINTER <> H_L_POINTER
P 38               increment H_C_POINTER
P 39           endif
P 40       endcase
P 41       TEXT_ITEM := line of text in help array [HELP_ARRAY]: position H_C_POINTER
P 42   else
P 43       case DISPLACEMENT_
P 44       of 0
P 45           ...do not change position
P 46       of -1
P 47           decrement C_POINTER
P 48           if C_POINTER < 1
P 49               C_POINTER := L_POINTER
P 50           endif
P 51       of +1

```

```

P 52      increment C_POINTER
P 53      if C_POINTER > L_POINTER
P 54          C_POINTER :=
P 55      endif
P 56      endcase
P 57      CHAR_ := character in flag array [FLAG_ARY]: position C_POINTER
P 58      if CHAR_ is '*'
P 59          reverse video of window 4 := true [REV_W4]
P 60      else
P 61          reverse video of window 4 := false [REV_W4]
P 62      endif
P 63      TEXT_ITEM := text in text array [TXT_ARY]: position C_POINTER
P 64  endif
P 65  STATUS_ := 0

```

O-UPDATE-ATTR-FLAG

-----p- 34A -p-----

```
P 1    ...5) O_UPDATE_ATTR_FLAG () STATUS_  
P 2    ...Data Usage:  
P 3    .....External: none  
P 4    .....Private:  
P 5    .....Variable:  
P 6    .....ATTRIBUTE_FLAG is an indicator to show if attribute is selected or not  
P 7    .....FLAG_NUMBER is a number that distinguishes a group of attributes  
P 8    ...Behavior:  
P 9    .....This operation has a binary function  
P 10   .....A) for the selectable items this operation toggles the enable/disable flag  
P 11   .....B) for drop down menus this operation enqueues the process-id of the invoked++  
P 12   ...Interface:  
P 13   .....Input: none  
P 14   .....Output:  
P 15   .....STATUS_ has the outcome of  
P 16   .....0 - selected menu item was of selectable type  
P 17   .....1 - selected menu item was of a menu type  
P 18   ...PDL Description:  
P 19   ...  
P 20   if present item is not pointing to another menu  
P 21       read ATTRIBUTE_FLAG  
P 22       case ATTRIBUTE_FLAG  
P 23       of 0  
P 24           read FLAG_NUMBER  
P 25           repeat  
P 26               read the menu for matching FLAG_NUMBER  
P 27           until end of menu  
P 28           if FLAG_NUMBER was found elsewhere and flag was set  
P 29               ...only on flag out of a group with same flag number can be selected  
P 30               release flag selection at found position  
P 31           else  
P 32               ...no restriction on flag selection  
P 33           endif  
P 34       of 1  
P 35           if FLAG_NUMBER is negative  
P 36               ...this is a flag that can not be deselected  
P 37           else  
P 38               ...this is a normal flag that can be deselected  
P 39               deselect the flag  
P 40           endif  
P 41       endcase  
P 42   else  
P 43       ...this is not a flag type but the id of the next menu  
P 44       PROCESS_ID := pointing process id  
P 45   endif
```

O-READ-NO-OF-SELECTED-ATTRIBUTES

-----P- 35A -P-----

P 1 ...6) O-READ-NO-OF-SELECTED-ATTRIBUTES () NO_OF_S_ATTR
P 2 ...Data Usage:
P 3 External: none
P 4 Private:
P 5 NO_OF_SELECTED_ATTRIBUTES
P 6 ...Behavior: Retrieves the number of selected attributes for display
P 7 ...Interface:
P 8 Input: none
P 9 Output:
P 10 NO_OF_S_ATTR is the number of selected attributes passed out
P 11 ...PDL Description:
P 12 ...
P 13 NO_OF_SELECTED_ATTRIBUTES := 0
P 14 repeat
P 15 de-select attribute
P 16 until end of attribute list
P 17 NO_OF_S_ATTR := NO_OF_SELECTED_ATTRIBUTES

O-CLEAR-ALL-ATTRIBUTES

-----P- 35B -P-----

P 1 ...7) O-CLEAR-ALL-ATTRIBUTES ()
P 2 ...Data Usage:
P 3 Extrenal:
P 4 Private:
P 5 Variable:
P 6 ATTRIBUTE_FLAG
P 7 ...Behavior:
P 8 This operation clears all the selected attributes.
P 9 ...Interface:
P 10 Input: none
P 11 Output: none
P 12 ...PDL Description:
P 13 ...
P 14 repeat
P 15 set ATTRIBUTE_FLAG to zero
P 16 until end of attribute list

O-CLEAR-ATTRIBUTE

-----P- 36A -P-----

P 1 ...8) O-CLEAR-ATTRIBUTE ()
P 2 ...Data Usage:
P 3 External: none
P 4 Private:
P 5 ATTRIBUTE_FLAG
P 6 ...Behavior: clears the current attribute from the list selected attributes
P 7 ...Interface:
P 8 Input:
P 9 Output:
P 10 ...PDL Description:
P 11 ...
P 12 clear ATTRIBUTE_FLAG at the current position

O-LIST-SELECTED-ATTRIBUTES

-----P- 36B -P-----

P 1 ...9) O-LIST-SELECTED-ATTRIBUTES (DISPLACEMENT_) MENU_TITLE, MENU_ITEM
P 2 ...Data Usage:
P 3 External:
P 4 Private:
P 5 DISPLACEMENT_ specifies the requested text is at current/above/below curr+++
P 6 ...Behavior: retrieved the list of selected attributes
P 7 ...Interface:
P 8 Input: DISPLACEMENT_ defines the direction of search
P 9 Output: MENU_TITLE, MENU_ITEM
P 10 ...PDL Description:
P 11 ...
P 12 case DISPLACEMENT_
P 13 of 0 or 1 or -1
P 14 case DISPLACEMENT_
P 15 of 0
P 16 ...first time listing
P 17 set DISPLACEMENT_ to 1
P 18 of 1 OR -1
P 19 continue up or down the list of selected attributes
P 20 endcase
P 21 move in the direction of DISPLACEMENT_
P 22 endcase

O-READ-LIST-FOUND-METHOD

-----P- 37A -P-----

```
P 1    ...10) O-READ-LIST-FOUND-METHOD () LIST_FOUND_METHOD
P 2    ...Data Usage:
P 3    .....External: none
P 4    .....Private:
P 5    .....LIST_FOUND_METHOD is the accessible function in List Found Birds
P 6    ...Behavior: retrieves the accessible function in List Found Birds
P 7    ...Interface:
P 8    .....Input: DISPLACEMENT_
P 9    .....Output:
P 10   ...PDL Description:
P 11   ...
P 12   if Count Birds is selected
P 13       ...enable counting in List Found Birds
P 14       LIST_FOUND_METHOD := 1
P 15   else
P 16       ...enable bird extraction from the list
P 17       LIST_FOUND_METHOD := 2
P 18   endif
```

O-READ-LIST-MATCHED-METHOD

-----P- 38A -P-----

```
P 1    ...11) O-READ-LIST-MATCHED-METHOD () LIST_MATCHED_METHOD
P 2    ...Data Usage:
P 3    .....External: none
P 4    .....Private:
P 5    .....LIST_MATCHED_METHOD is the accessible function in List Matched Birds
P 6    ...Behavior: retrieves the accessible function in List Matched Birds
P 7    ...Interface:
P 8    .....Input: DISPLACEMENT_
P 9    .....Output:
P 10   ...PDL Description:
P 11   ...
P 12   if Bird Count is selected
P 13       ...enable bird count
P 14       LIST_MATCHED_METHOD := 1
P 15   else
P 16       if Bird Information is selected
P 17           ...enable bird information
P 18           LIST_MATCHED_METHOD := 2
P 19       else
P 20           if Bird Call is selected
P 21               ...enable bird call
P 22               LIST_MATCHED_METHOD := 3
P 23           else
P 24               ...enable bird picture
P 25               LIST_MATCHED_METHOD := 4
P 26           endif
P 27       endif
P 28   endif
```

O-FILL-FILTER

-----P- 38B -P-----

```
P 1    ...12) O-FILL-FILTER ()
P 2    ...Data Usage:
P 3    .....External: none
P 4    .....Private:
P 5    .....SELECTED_ATTR is the selected attribute
P 6    .....SELECTED_ATTR_SET is the set of selected attributes
P 7    ...Behavior: compiles a search filter based on the selected attributes other than +++
P 8    .....This operation initializes the search filter with selected items
P 9    ...Interface:
P 10   .....Input: none
P 11   .....Output: none
P 12   ...PDL Description:
P 13   ...
P 14   SELECTED_ATTR_SET is null
P 15   repeat
P 16       add SELECTED_ATTR to SELECTED_ATTR_SET
P 17   until all attributes are scanned
```

Birds

15 10 1990 PAGE 1 - 39

Bird Resource

Data Usage

-----C- 40A -C-----

C 1 Private Constant:
C 2 External
C 3 ...Variable:
C 4 DATA_ARY
C 5 FILTER_ARY
C 6 FAMILY_
C 7 Public Variable:
C 8 ...PROCESS_ID is the id of the current menu.
C 9 ...BIRD_FAMILY is the family to which the current bird belongs
C 10 ...BIRD_NAME is the name of the current bird
C 11 ...BIRD_COUNT is the count number of the current bird
C 12 Private Variable:
C 13 ...STRATEGY_ is the search and compare strategy of selected attributes
C 14 against the bird attributes; four possible values
C 15 A- no attribute is selected; compile all birds for display
C 16 B- only bird family is selected
C 17 C- a f type attribute is selected; bird family is not selected
C 18 D- both family and flag type attributes have been selected
C 19 NO_OF_MATCHED_BIRDS is the number of birds matching the selected attributes
C 20 MATCH_LIST_NO identifies which of the four possible functions of
C 21 a)bird count, b)bird information, c)bird image or d)bird call have been s+++
C 22 NO_FOUND_BIRDS is the number of birds with a bird count greater than zero
C 23 FOUND_LIST_NO identifies wheter extraction or bird count are enabled during +++
C 24 DATA_ARY is of the type record; this is the bird database
C 25 BIR_NAME is the name bird
C 26 FAMILY_ is the family of the bird
C 27 SAOS_ is the South African bird number
C 28 PR_CODE is the bird habitat code
C 29 BIRD_ATTR contains the flag type attributes of the bird
C 30 BIRD_COUNT is the count number of the bird
C 31 MATCH_ indicates if the current record has matched attribute specificatio+++
C 32 BIRD_REC is the DATA_ARY record pointer
C 33

Behavior

-----C- 40B -C-----

C 1 This resource furnishes the bird attributes and information data structure.
C 2 Operations of the resource allows reading of bird data and scanning
C 3 through it.
C 4

O-READ-BIRD-DATA

-----P- 41A -P-----

```
P 1    ...1) O-READ-BIRD-DATA ()
P 2    ...Data Usage:
P 3    .....Private:
P 4    .....Constant:
P 5    .....DATA_FILE
P 6    .....Variable:
P 7    .....BIRD_NAME
P 8    .....BIRD_FAMILY
P 9    .....BIRD_SAOS
P 10   .....BIRD_FLAG
P 11   ...Behavior: reads the bird database from disc file
P 12   .....This operation reads the bird attribute and info data from file
P 13   ...Interface:
P 14   .....Input: none
P 15   .....Output: none
P 16   ...PDL Description:
P 17   ...
P 18   while not end of file
P 19       read BIRD_FAMILY
P 20       read BIRD_NAME
P 21       read BIRD_INFO: BIRD_SAOS
P 22   endwhile
```

O-SCAN

-----P- 42A -P-----

```
P 1    ...2) O-SCAN (DISPLACEMENT_) BIRD_NAME, BIRD_INFO, BIRD_REC
P 2    ...Data Usage:
P 3    .....External: none
P 4    .....Private:
P 5    .....Variable:
P 6    .....STRATEGY_ is the scanning strategy
P 7    .....MATCH_ indicates if a bird has matched the set of selected attributes
P 8    .....CONTINUE_ loop condition
P 9    .....NO_OF_MATCHED_BIRDS
P 10   ...Behavior: scans the database for birds that match the selected attributes
P 11   .....Birds matching the selected attributes will be found and displayed
P 12   ...Interface:
P 13   .....Input: DISPLACEMENT_
P 14   .....Output:
P 15   .....BIRD_NAME
P 16   .....BIRD_INFO
P 17   .....BIRD_REC
P 18   ...PDL Description:
P 19   ...
P 20   NO_OF_MATCHED_BIRDS := 0
P 21   set default listing strategy to display all, STRATEGY_ := 4
P 22   if selected family is not null and SELECTED_ATTR_SET is null
P 23       ...family search only
P 24       STRATEGY_ := 1
P 25   endif
P 26   if selected family is null and SELECTED_ATTR_SET is not null
P 27       ...filter search on other attributes
P 28       STRATEGY_ := 2
P 29   endif
P 30   if selected family is not null and SELECTED_ATTR_SET is not null
P 31       ...family and filter search
P 32       STRATEGY_ := 3
P 33   endif
P 34   case STRATEGY_
P 35   of 1
P 36       ...family search only
P 37       BIRD_REC := 1
P 38       while BIRD_REC < NO_OF_BIRDS
P 39           do a family search
P 40           if there was a match
P 41               increment NO_OF_MATCHED_BIRDS
P 42           endif
P 43       endwhile
P 44   of 2
P 45       ...filter search only
P 46       do a search on filter spec
P 47       if there was a match
P 48           increment NO_OF_MATCHED_BIRDS
P 49       endif
P 50   of 3
P 51       ...family and filter search
```

```

P 52      BIRD_REC := 1
P 53      while BIRD_REC < NO_OF_BIRDS
P 54          do a family search
P 55          if there was a match
P 56              do a search on filter
P 57              if there was a match
P 58                  increment NO_OF_MATCHED_BIRDS
P 59              endif
P 60          endif
P 61      endwhile
P 62  of 4
P 63      ...display all birds
P 64      NO_OF_MATCHED_BIRDS := NO_OF_BIRDS
P 65  endcase

```

O-LIST-MATCHED-BIRDS

-----P- 43A -P-----

```
P 1    ...3) O-LIST-MATCHED-BIRDS (DISPLACEMENT_)
P 2    ...Data Usage:
P 3    .....External: none
P 4    .....Private:
P 5    .....BIRD_NAME
P 6    .....BIRD_FAMILY
P 7    ...Behavior: retrieves the list of birds that match the selected attributes
P 8    ...Interface:
P 9    .....Input: DISPLACEMENT_
P 10   .....Output: none
P 11   ...PDL Description:
P 12   ...
P 13   case DISPLACEMENT_
P 14   of 0
P 15       get the first item in the list
P 16   of -1
P 17       get the previous item in the list
P 18   of +1
P 19       get the next item in the list
P 20   endcase
P 21   update BIRD_NAME
P 22   update BIRD_FAMILY
```

O-READ-COUNT-FILE

-----P- 43B -P-----

```
P 1    ...4) O-READ-COUNT-FILE ()
P 2    ...Data Usage:
P 3    .....External: none
P 4    .....Private:
P 5    .....NO_OF_BIRDS
P 6    ...Behavior: reads the count file from disc
P 7    ...Interface:
P 8    .....Input: DISPLACEMENT_
P 9    .....Output:
P 10   ...PDL Description:
P 11   ...
P 12   while NO_OF_BIRDS is not reached
P 13       read bird counts from file
P 14   endwhile
```

O-WRITE-COUNT-FILE

-----P- 44A -P-----

```
P 1    ...5) O-WRITE-COUNT-FILE ()
P 2    ...Data Usage:
P 3    .....External: none
P 4    .....Private:
P 5    .....NO_OF_BIRDS
P 6    ...Behavior: writes the bird count information to disc file
P 7    ...Interface:
P 8    .....Input: DISPLACEMENT_
P 9    .....Output:
P 10   ...PDL Description:
P 11   ...
P 12   while NO_OF_BIRDS is not reached
P 13       write bird counts to file
P 14   endwhile
```

O-CHANGE-BIRD-COUNT

-----P- 44B -P-----

```
P 1    ...6) O-CHANGE-BIRD-COUNT (DISPLACEMENT_)
P 2    ...Data Usage:
P 3    .....External: none
P 4    .....Private:
P 5    .....BIRD_COUNT
P 6    ...Behavior: modifies the count of the current bird
P 7    ...Interface:
P 8    .....Input:
P 9    .....DISPLACEMENT_ indicates bird count is to be incremented or decremented
P 10   .....-1 count down
P 11   .....+1 count up
P 12   .....Output:
P 13   ...PDL Description:
P 14   ...
P 15   case DISPLACEMENT_
P 16   of -1
P 17       increment BIRD_COUNT
P 18       if BIRD_COUNT is < 0
P 19           set BIRD_COUNT to 0
P 20       endif
P 21   of +1
P 22       decrement BIRD_COUNT
P 23       if BIRD_COUNT is at max allowable value
P 24           set BIRD_COUNT to max allowable value
P 25       endif
P 26   endcase
```

O-READ-NO-OF-FOUND-BIRDS

-----P- 45A -P-----

```
P 1    ...7) O-READ-NO-OF-FOUND-BIRDS ( ) NO_OF_FOUND_BIRDS_PRIVATE
P 2    ...Data Usage:
P 3    .....External: none
P 4    .....Private:
P 5    .....NO_OF_FOUND_BIRDS
P 6    ...Behavior: retrieves the number of found birds for display
P 7    ...Interface:
P 8    .....Input: none
P 9    .....Output: NO_OF_FOUND_BIRDS_PRIVATE is the number of found birds
P 10   ...PDL Description:
P 11   ...
P 12   NO_OF_FOUND_BIRDS := 0
P 13   while NO_OF_BIRDS is not reached
P 14       read BIRD_COUNT
P 15       if BIRD_COUNT <> 0
P 16           increment NO_OF_FOUND_BIRDS
P 17       endif
P 18   endwhile
P 19   NO_OF_FOUND_BIRDS_PRIVATE := NO_OF_FOUND_BIRDS
```

O-LIST-FOUND-BIRDS

-----P- 45B -P-----

```
P 1    ...8) O-LIST-FOUND-BIRDS (DISPLACEMENT_)
P 2    ...Data Usage:
P 3    .....External: none
P 4    .....Private:
P 5    .....BIRD_NAME
P 6    .....BIRD_FAMILY
P 7    ...Behavior: retrieves the list of found birds
P 8    ...Interface:
P 9    .....Input: DISPLACEMENT_
P 10   .....Output:
P 11   ...PDL Description:
P 12   ...
P 13   case DISPLACEMENT_
P 14   of 0
P 15       get the first item in the list
P 16   of -1
P 17       get the previous item in the list
P 18   of +1
P 19       get the next item in the list .
P 20   endcase
P 21   update BIRD_NAME
P 22   update BIRD_FAMILY
```

O-CLEAR-FOUND-BIRDS

-----P- 46A -P-----

P 1 ...9) O-CLEAR-FOUND-BIRDS ()
P 2 ...Data Usage:
P 3 External: none
P 4 Private:
P 5 BIRD_COUNT
P 6 NO_OF_BIRDS
P 7 ...Behavior: clears all found birds from the list of found birds
P 8 ...Interface:
P 9 Input: DISPLACEMENT_
P 10 Output:
P 11 ...PDL Description:
P 12 ...
P 13 while NO_OF_BIRDS is not reached
P 14 set BIRD_COUNT to zero
P 15 endwhile

O-CLEAR-BIRD

-----P- 46B -P-----

P 1 ...10) O-CLEAR-BIRD ()
P 2 ...Data Usage:
P 3 External: none
P 4 Private:
P 5 BIRD_COUNT
P 6 ...Behavior: clears the current bird from the list of found birds
P 7 ...Interface:
P 8 Input: DISPLACEMENT_
P 9 Output:
P 10 ...PDL Description:
P 11 ...
P 12 set the current BIRD_COUNT to zero

O-READ-NO-OF-MATCHED-BIRDS

-----P- 47A -P-----

P 1 ...11) O-READ-NO-OF-MATCHED-BIRDS () NO_OF_FOUND_BIRDS_PRIVATE
P 2 ...Data Usage:
P 3 External: none
P 4 Private:
P 5 NO_OF_MATCHED_BIRDS
P 6 ...Behavior: retrieves the number of matched birds for display
P 7 ...Interface:
P 8 Input: DISPLACEMENT_
P 9 Output:
P 10 ...PDL Description:
P 11 ...
P 12 NO_OF_MATCHED_BIRDS_PRIVATE := NO_OF_MATCHED_BIRDS

Birds

15 10 1990 PAGE 1 - 48

Queue Resource

Data Usage

-----C- 49A -C-----

C 1 Public:
C 2 ...Variable:
C 3 PROCESS_ID is the id of the current menu.
C 4 Private:
C 5 ...Variable:
C 6 I_ is sloop counter
C 7 STATUS_ is the status report of procedures and functions.
C 8 Q_ARY is the array emulating the queue
C 9 Q_TMP_ARY is the temp queue array, used for context switching
C 10 Q_MIDL is the marker separating the find and attribute activities
C 11 Q_TAIL is the pointer marking the position of the last item in the queue
C 12 ...Constant:
C 13 Q_SIZE is the size of the queue set at 10
C 14

Behavior

-----C- 49B -C-----

C 1 This resource provides the facility of queuing the main activities
C 2 namely; ATTRIBUTE and FIND mode
C 3

O-READ-Q-FILE

```
-----P- 50A -P-----
P 1    ...1) O-READ-Q-FILE ()
P 2    ...Data Usage:
P 3    .....External: none
P 4    .....Private: none
P 5    ...Behavior:
P 6    .....this operation restrives the queue information from file Q_DAT.TXT
P 7    .....when the main program is first run
P 8    ...Inteface:
P 9    .....Input: none
P 10   .....Output: none
P 11   ...PDL Description:
P 12   ...
P 13   read text from file, Q_DAT.TXT into TEXT_
P 14   queue middle pointer [Q_MIDL]:= value of TEXT_
P 15   read text from file into TEXT_
P 16   queue tail pointer [Q_TAIL] := TEXT_
P 17   I_ := 1
P 18   while I_ <= queue tail pointer [Q_TAIL]
P 19       queue array [Q_ARY] : position I_ := text from file
P 20       increment I_
P 21   endwhile
```

O-WRITE-Q-FILE

```
-----P- 50B -P-----
P 1    ...2) O-WRITE-Q-FILE ()
P 2    ...Data Usage:
P 3    .....External: none
P 4    .....Private: none
P 5    ...Behavior:
P 6    .....This operation will write the queue data into file Q_DAT.TXT
P 7    .....when quitting the program
P 8    ...Inteface:
P 9    .....Input: none
P 10   .....Output: none
P 11   ...PDL Description
P 12   ...
P 13   TEXT_ := queue middle pointer [Q_MIDL]
P 14   write TEXT_ to file
P 15   TEXT_ := queue tail pointer [Q_TAIL]
P 16   write TEXT_ to file
P 17   I_ := 1
P 18   while I_ <= queue tail [Q_TAIL]
P 19       write queue array [Q_ARY]: position I_ to file
P 20       increment I_
P 21   endwhile
```

Q-EXCH-Q-BLOCKS

-----P- 51A -P-----

```
P 1    ...3) EXCHANGE-Q-BLOCKS
P 2    ...Data Usage:
P 3    .....External: none
P 4    .....Private: none
P 5    ...Behavior:
P 6    .....this operation will swap the segments of queue corresponding to the
P 7    .....Attribute mode with segment corresponding to the Find mode
P 8    .....Thus putting the relevant process-id at the head of the queue
P 9    ...Interface:
P 10   .....Input: none
P 11   .....Output: none
P 12   ...PDL Description:
P 13   ...
P 14   I_ := 1
P 15   while I_ <= queue middle [Q_MIDL]
P 16       queue temp array [Q_TMP_ARY]: position I_ := queue array [Q_ARY]: position I_
P 17       increment I_
P 18   endwhile
P 19   I_ := 1
P 20   while I_ <= (queue tail [Q_TAIL]) - (queue middle [Q_MIDL])
P 21       queue array [Q_ARY]: position I_ := queue array [Q_ARY]:position (queue middle++
P 22       increment I_
P 23   endwhile
P 24   I_ := 1
P 25   while I_ <= queue middle [Q_MIDL]
P 26       queue array [Q_ARY]: position Q_TAIL - Q_MIDL + I_ := Q_TMP_ARY position I_
P 27       increment I_
P 28   endwhile
P 29   Q_MIDL := Q_TAIL - Q_MIDL
```

O-FRONT-ENQ

```
-----P- 52A -P-----
P 1    ...4) O-FRONT-ENQ (), STATUS_
P 2    ...Data Usage:
P 3    .....External:
P 4    .....Private:
P 5    .....Q_ARY is the queue of waiting processes
P 6    .....Q_TAIL is the end of queue pointer
P 7    .....Q_MIDL is the pointer separating the attribute processes from the find pr+++
P 8    .....PROCESS_ID is the id of the process at the head of the queue
P 9    ...Behavior:
P 10   .....This operation will enqueue the PROCESS_ID at the head of the queue
P 11   ...Interface:
P 12   .....Input: none
P 13   .....Output: STATUS_ has the outcome of
P 14   .....0 - successful
P 15   .....1 - unsuccessful / queue is full
P 16   ...PDL Description:
P 17   ...
P 18   if Q_TAIL is equal to size of queue [Q_SIZE]
P 19       STATUS_ := 1
P 20   else
P 21       if Q_TAIL is 0
P 22           queue array [Q_ARY]: position 1 := PROCESS_ID
P 23           Q_MIDL := 1
P 24           Q_TAIL := 1
P 25       else
P 26           I_ := Q_TAIL
P 27           while I_ >= 1
P 28               queue array [Q_ARY]: position I_ +1 := queue array [Q_ARY]: position I_
P 29               increment I_
P 30           endwhile
P 31           queue array [Q_ARY]: position 1 := PROCESS_ID
P 32           increment Q_TAIL
P 33           INCREMENT Q_MIDL
P 34           STATUS_ := 0
P 35       endif
P 36   endif
```

O-DEQ

-----P- 53A -P-----

```
P 1    ...5) O-DEQ ( ) STATUS_  
P 2    ...Data Usage:  
P 3    .....External:  
P 4    .....Private:  
P 5    .....Q_ARY is the queue of waiting processes  
P 6    .....Q_TAIL is the end of queue pointer  
P 7    .....Q_MIDL is the pointer separating the attribute processes from the find pr+++  
P 8    ...Behavior:  
P 9    .....This operation will consume the item at the head of the queue, and  
P 10    .....writes it to the PROCESS_ID  
P 11    ...Interface:  
P 12    .....STATUS_ has the outcome of  
P 13    .....0 - successful  
P 14    .....1 - unsuccessful / queue empty  
P 15    ...PDL Description:  
P 16    ...  
P 17    decrement Q_TAIL  
P 18    decrement Q_MIDL  
P 19    if Q_MIDL is less than 0  
P 20        Q_MIDL := 0  
P 21    endif  
P 22    if Q_TAIL is less than 0  
P 23        ...queue is empty  
P 24        Q_TAIL := 0  
P 25        STATUS_ := 1  
P 26    else  
P 27        PROCESS_ID := queue array [Q_ARY]: position 1  
P 28        STATUS_ := 0  
P 29        I_ := 2  
P 30        while I_ <= Q_TAIL+1  
P 31            queue array [Q_ARY]: position I_-1 := queue array [Q_ARY]: position I_  
P 32            increment I_  
P 33        endwhile  
P 34    endif
```

Scroll Manager Resource

Data Usage

-----C- 55A -C-----

C 1 Public:
C 2 ...Variable:
C 3 TEXT_ITEM ...is the string text of the current menu item
C 4 REV_W4 is the reverse video indicator of window 4
C 5 W1_SIZE is the size of window 1
C 6 W4_SIZE is the size of window 4
C 7 GUIDE_ARROW_R
C 8 GUIDE_ARROW_L
C 9 W_NO is the window number of the active window, either 1 or 4
C 10 Private:
C 11 ...Variables:
C 12 W_L_POINTER .is the window left pointer.
C 13 W_R_POINTER .is the window right pointer.
C 14 TEXT_DISPLAY is the portion of text from the TEXT_ITEM to be displayed on th++
C 15 TEXT_LENGTH .is the length of text in TEXT_ITEM.
C 16

Behavior

-----C- 55B -C-----

C 1 This resource facilitates the function of word scrolling within the
C 2 current line of text, which is stored in the variable TEXT_ITEM.
C 3 This is achieved by displaying a window of this text.
C 4 List of operations:
C 5

O-INITIAL-TEXT

-----P- 56A -P-----

```
P 1    ...1) O-INITIAL-TEXT (TEXT_ITEM), TEXT_DISPLAY
P 2    ...Data Usage:
P 3    .....External:
P 4    .....TEXT_ITEM
P 5    .....Private:
P 6    .....W_L_POINTER left pointer of viewing window
P 7    .....W_R_POINTER right pointer of viewing window
P 8    ...Behavior:
P 9    .....This operation extracts the first x characters in the text
P 10   .....contained in TEXT_ITEM and writes it to TEXT_DISPLAY
P 11   ...Interface:
P 12   .....input:
P 13   .....TEXT_ITEM contains the current line of text in the data structure
P 14   .....TEXT_DISPLAY contains a substring of text within TEXT_ITEM, for
P 15   .....displaying on the screen
P 16   .....Output:
P 17   .....TEXT_DISPLAY is the truncated text from the current line to be displayed
P 18   .....on the current window
P 19   ...PDL Description:
P 20   ...
P 21   W_L_POINTER := 0
P 22   W_R_POINTER := W_SIZE+1
P 23   TEXT_DISPLAY := TEXT_ITEM: from W_L_POINTER+1 to W_R_POINTER-1
P 24   if TEXT_LENGTH <= W_SIZE
P 25       GUIDE_ARROW_R := false
P 26   else
P 27       GUIDE_ARROW_R := true
P 28   endif
P 29   GUIDE_ARROW_L := false
```

O-MOVE-TEXT-LEFT

```
-----P- 57A -P-----
P 1    ...2) O-MOVE-TEXT-LEFT (TEXT_ITEM), TEXT_DISPLAY
P 2    ...Behavior:
P 3    .....This operation moves the displayed window of the text in MENU_ITEM one word +++
P 4    ...Interface:
P 5    .....MENU_ITEM; contains the current line of text in the data structure
P 6    .....W_R_POINTER; right pointer of the text window
P 7    .....TEXT_DISPLAY contains a substring of text within MENU_ITEM, for displaying o+++
P 8    ...PDL Description:
P 9    ...
P 10   if first character of TEXT_ITEM at W_L_POINTER is blank
P 11       while first character of TEXT_ITEM at W_L_POINTER is blank
P 12           decrement W_L_POINTER
P 13       endwhile
P 14   endif
P 15   CONTINUE_ := true
P 16   while first character of TEXT_ITEM at W_L_POINTER is not blank and CONTINUE_ is tr+++
P 17       decrement W_L_POINTER
P 18       if W_L_POINTER <= 0
P 19           W_L_POINTER := 0
P 20           CONTINUE_ := false
P 21       endif
P 22   endwhile
P 23   W_R_POINTER := W_L_POINTER + W_SIZE+1
P 24   case W_L_POINTER
P 25   of 0
P 26       GUIDE_ARROW_L := false
P 27       if length of TEXT_ITEM <= W_SIZE
P 28           GUIDE_ARROW_R := false
P 29       else
P 30           GUIDE_ARROW_R := true
P 31       endif
P 32   default
P 33       GUIDE_ARROW_L := true
P 34       GUIDE_ARROW_R := true
P 35   endcase
P 36   TEXT_DISPLAY := portion of TEXT_ITEM from W_L_POINTER +1; of length W_SIZE
```

MOVE-TEXT-RIGHT

```
-----P- 58A -P-----
P 1    ...3) O-MOVE-TEXT-RIGHT (MENU_ITEM), TEXT_DISPLAY
P 2    ...Behavior:
P 3    .....This operation moves the displayed window of the text in MENU_ITEM one word +++
P 4    ...Interface:
P 5    .....MENU_ITEM; contains the current line of text in the data structure
P 6    .....W_R_POINTER; right pointer of the text window
P 7    .....TEXT_DISPLAY; contains a substring of text within MENU_ITEM, for displaying +++
P 8    ...PDL Descriptions:
P 9    ...
P 10   if first character of TEXT_ITEM at W_R_POINTER is blank
P 11       while first character of TEXT_ITEM at W_R_POINTER is blank
P 12           increment W_R_POINTER
P 13       endwhile
P 14   endif
P 15   CONTINUE_ := true
P 16   while first character of TEXT_ITEM at W_R_POINTER is not blank and CONTINUE_ is tr+++
P 17       increment W_R_POINTER
P 18       if length of TEXT_ITEM+1 <= W_SIZE
P 19           W_R_POINTER := W_SIZE +1
P 20           CONTINUE_ := false
P 21       else
P 22           if length of TEXT_ITEM+1 < W_R_POINTER
P 23               W_R_POINTER := length of TEXT_ITEM +1
P 24               CONTINUE_ := false
P 25           endif
P 26       endif
P 27   endwhile
P 28   W_L_POINTER := W_R_POINTER - W_SIZE -1
P 29   if W_L_POINTER <= 0
P 30       if W_R_POINTER := length of TEXT_ITEM+1
P 31           GUIDE_ARROW_R := false
P 32           GUIDE_ARROW_L := true
P 33       else
P 34           GUIDE_ARROW_R := true
P 35           GUIDE_ARROW_L := true
P 36       endif
P 37   endif
P 38   TEXT_DISPLAY := portion of TEXT_ITEM from W_L_POINTER+1; of length W_SIZE
```

Birds

15 10 1990 PAGE 1 - 59

Screen Resource

Data Usage

-----C- 60A -C-----

```
C 1      Public:
C 2      ...Variables:
C 3      .....TEXT_DISPLAY is the display text passed in to be displayed on screen
C 4      .....REV_W4
C 5      .....W1_SIZE
C 6      .....W4_SIZE
C 7      .....GUIDE_ARROW_L
C 8      .....GUIDE_ARROW_R
C 9      .....
C 10     Private:
C 11     ...Variables:
C 12     .....W1_X horizontal position of left most corner of window 1
C 13     .....W1_Y vertical position of left most corner of window 1
C 14     .....W4_X horizontal position of left most corner of window 4
C 15     .....W4_Y vertical position of left most corner of window 4
C 16     ...Constant:
C 17     .....W2_X horizontal position of left most corner of window 2
C 18     .....W2_Y vertical position of left most corner of window 2
C 19     .....W3_X horizontal position of left most corner of window 3
C 20     .....W3_Y vertical position of left most corner of window 3
C 21     .....W5_X horizontal position of left most corner of window 5
C 22     .....W5_Y vertical position of left most corner of window 5
C 23     .....W2_SIZE length of window 2
C 24     .....W3_SIZE length of window 3
C 25     .....W5_SIZE length of window 5
C 26
```

Behavior

-----C- 60B -C-----

```
C 1      This resource provides the screen emulation of the bird identifier in
C 2      addition to the writing and clearing operations of the different windows
C 3      of the screen.
C 4      List of Operations:
C 5
```

O-SCREEN-FORMAT

-----P- 61A -P-----

P 1 ...1) O-SCREEN-FORMAT
P 2 ...Data Usage:
P 3 External:
P 4 Private:
P 5 ...Behavior:
P 6 This operation provides the screen display and the keypads of the
P 7 identifier.
P 8 ...Interface:
P 9 Input: none
P 10 Output: none
P 11 ...PDL Description:
P 12 ...
P 13 position keypads on the screen [O-PUT-KEYPAD]

O-WRT-W1

-----P- 61B -P-----

P 1 ...3) O-WRT-W1 (TEXT_DISPLAY)
P 2 ...Data Usage:
P 3 External:
P 4 Variable:
P 5 TEXT_DISPLAY
P 6 Private: none
P 7 ...Behavior:
P 8 This operation writes to window 1
P 9 ...Interface:
P 10 Input:
P 11 TEXT_DISPLAY
P 12 Output: none
P 13 ...PDL Description:
P 14 ...
64A P 15 clear window 1 [O-CLR-W1]
P 16 position cursor at W1_X, W1_Y
P 17 write TEXT_DISPLAY to window 1

O-WRT-W2

```
-----P- 62A -P-----  
  
P 1      ...4)O-WRT-W2 ()  
P 2      ...Data Usage:  
P 3      .....External:  
P 4      .....Private:  
P 5      ...Behavior:  
P 6      ...Interface:  
P 7      .....Input: none  
P 8      .....Output: none  
P 9      ...PDL Description:  
P 10     ...  
P 11     case GUIDE_ARROW_L  
P 12     of false  
64B P 13     clear window 2 [-O-CLR-W2]  
P 14     of true  
P 15     position cursor at W2_X, W2_Y  
P 16     write TEXT_DISPLAY to window 2  
P 17     endcase
```

O-WRT-W3

```
-----P- 62B -P-----  
  
P 1      ...5)O-WRT-W3 ()  
P 2      ...Data Usage:  
P 3      .....External:  
P 4      .....Private:  
P 5      ...Behavior:  
P 6      ...Interface:  
P 7      .....Input: none  
P 8      .....Output: none  
P 9      ...PDL Description:  
P 10     ...  
P 11     case GUIDE_ARROW_R  
P 12     of false  
64C P 13     clear window 3 [-O-CLR-W3]  
P 14     of true  
P 15     position cursor at W3_X, W3_Y  
P 16     write TEXT_DISPLAY to window 3  
P 17     endcase
```

O-WRT-W4

```
-----P- 63A -P-----  
  
P 1    ...6)O-WRT-W4 (TEXT_DISPLAY)  
P 2    ...Data Usage:  
P 3    .....External:  
P 4    .....Private:  
P 5    ...Behavior:  
P 6    ...Interface:  
P 7    .....Input: TEXT_DISPLAY  
P 8    .....Output: none  
P 9    ...PDL Description:  
P 10   ...  
P 11   if REV_W4 is true  
P 12       set foreground and background color to normal  
P 13   else  
P 14       set foreground and background color to reverse  
P 15   endif  
65A P 16 clear window 4 [O-CLR-W4]  
P 17   position cursor at W4_X, W4_Y  
P 18   write TEXT_DISPLAY to window 4  
P 19   set foreground and background color to normal
```

O-WRT-W5

```
-----P- 63B -P-----  
  
P 1    ...7)O-WRT-W5 (W5_TEXT)  
P 2    ...Data Usage:  
P 3    .....External:  
P 4    .....Private:  
P 5    ...Behavior:  
P 6    ...Interface:  
P 7    .....Input: none  
P 8    .....Output: none  
P 9    ...PDL Description:  
P 10   ...  
65B P 11 clear window 5 [O-CLR-W5]  
P 12   position cursor at W4_X, W4_Y  
P 13   write to W5_TEXT to window 5
```

O-CLR-W1

-----P- 64A -P-----

P 1 ...8)O-CLR-W1 ()
P 2 ...Data Usage:
P 3 External:
P 4 Private:
P 5 ...Behavior:
P 6 ...Interface:
P 7 Input: none
P 8 Output: none
P 9 ...PDL Description:
P 10 ...
P 11 position cursor at W1_X, W1_Y
P 12 write empty line to window 1

O-CLR-W2

-----P- 64B -P-----

P 1 ...9)O-CLR-W2 ()
P 2 ...Data Usage:
P 3 External:
P 4 Private:
P 5 ...Behavior:
P 6 ...Interface:
P 7 Input: none
P 8 Output: none
P 9 ...PDL Description:
P 10 ...
P 11 position cursor at W2_X, W2_Y
P 12 write empty line to window 2

O-CLR-W3

-----P- 64C -P-----

P 1 ...10)O-CLR-W3 ()
P 2 ...Data Usage:
P 3 External:
P 4 Private:
P 5 ...Behavior:
P 6 ...Interface:
P 7 Input: none
P 8 Output: none
P 9 ...PDL Description:
P 10 ...
P 11 position cursor at W3_X, W3_Y
P 12 write empty line to window 3

O-CLR-W4

-----P- 65A -P-----

P 1	...11)O-CLR-W4 ()
P 2	...Data Usage:
P 3	External:
P 4	Private:
P 5	...Behavior:
P 6	...Interface:
P 7	Input: none
P 8	Output: none
P 9	...PDL Description:
P 10	...
P 11	position cursor at W4_X, W4_Y
P 12	write empty line to window 4

O-CLR-W5

-----P- 65B -P-----

P 1	...12)O-CLR-W5 ()
P 2	...Data Usage:
P 3	External:
P 4	Private:
P 5	...Behavior:
P 6	...Interface:
P 7	Input: none
P 8	Output: none
P 9	...PDL Description:
P 10	...
P 11	position cursor at W5_X, W5_Y
P 12	write empty line to window 5

Auxiliary Functions

O-WAIT

-----P- 67A -P-----

P 1 ...Data Usage:
P 2 External: KEY_
P 3 Private:
P 4 ...Behavior:
P 5 ...Interface:
P 6 Input: KEY_
P 7 Output: none
P 8 ...PDL Description:
P 9 ...
P 10 repeat
P 11 read keyboard
P 12 KEY_ := pressed key
P 13 until KEY_ is not set to null

Quit Program [P-QUIT-PROG]

-----P- 67B -P-----

P 1 ...Data Usage:
P 2 External:
P 3 O-WRITE-TXT-DATA
P 4 O-FRONT-ENQ
P 5 O-WRITE-Q-DATA
P 6 SYSTEM_ON
P 7 Private:
P 8 Variable:
P 9 STATUS_
P 10 ...Behavior:
P 11 ...Interface:
P 12 Input: none
P 13 Output: none
P 14 ...PDL Description:
P 15 ...
52A P 16 enqueue process-id [O-FRONT-ENQ]
P 17 write text data to file [O-WRITE-TXT-DATA]
P 18 write queue data to file [O-WRITE-Q-DATA]
P 19 SYSTEM_ON := false

PROCEDURES

5A	1	Scheduler Process
61A	2	. O-SCREEN-FORHAT
41A	3	. O-READ-BIRD-DATA
63A	4	. O-WRT-W4
65A	5	. . O-CLR-W4
67B	6	. Quit Program [P-QUIT-PROG]
52A	7	. . O-FRONT-ENQ
38B	8	. O-FILL-FILTER
42A	9	. O-SCAN
47A	10	. O-READ-NO-OF-MATCHED-BIRDS
63B	11	. O-WRT-W5
65B	12	. . O-CLR-W5
53A	13	. O-DEQ
63A	14	. O-WRT-W4 (4)
67A	15	. O-WAIT
65A	16	. O-CLR-W4 (5)
8A	17	. Help Menu Process [P-HELP]
61B	18	. . O-WRT-W1
64A	19	. . . O-CLR-W1
33A	20	. . O-READ-TXT-ITEM
56A	21	. . O-INITIAL-TEXT
62A	22	. . O-WRT-W2
64B	23	. . . O-CLR-W2
62B	24	. . O-WRT-W3
64C	25	. . . O-CLR-W3
63A	26	. . O-WRT-W4 (4)
62A	27	. . O-WRT-W2 (22)
62B	28	. . O-WRT-W3 (24)
63A	29	. . O-WRT-W4 (4)
58A	30	. . O-MOVE-TEXT-RIGHT
62A	31	. . O-WRT-W2 (22)
62B	32	. . O-WRT-W3 (24)
63A	33	. . O-WRT-W4 (4)
11A	34	. Attribute Menu Process [P-ATTR-MENU]
32A	35	. . O-READ-MENU-TITLE
61B	36	. . O-WRT-W1 (18)
33A	37	. . O-READ-TXT-ITEM (20)
56A	38	. . O-INITIAL-TEXT (21)
62A	39	. . O-WRT-W2 (22)
62B	40	. . O-WRT-W3 (24)
63A	41	. . O-WRT-W4 (4)
52A	42	. . O-FRONT-ENQ (7)
52A	43	. . O-FRONT-ENQ (7)
52A	44	. . O-FRONT-ENQ (7)
51A	45	. . O-EXCH-Q-BLOCKS
52A	46	. . O-FRONT-ENQ (7)
34A	47	. . O-UPDATE-ATTR-FLAG
52A	48	. . O-FRONT-ENQ (7)
53A	49	. . O-DEQ (13)
38B	50	. . O-FILL-FILTER (8)
42A	51	. . O-SCAN (9)
47A	52	. . O-READ-NO-OF-MATCHED-BIRDS (10)

PROCEDURES

63B	53	.	.	O-WRT-W5 (11)	
33A	54	.	.	O-READ-TXT-ITEM (20)	
56A	55	.	.	O-INITIAL-TEXT (21)	
62A	56	.	.	O-WRT-W2 (22)	
62B	57	.	.	O-WRT-W3 (24)	
63A	58	.	.	O-WRT-W4 (4)	
33A	59	.	.	O-READ-TXT-ITEM (20)	
56A	60	.	.	O-INITIAL-TEXT (21)	
62A	61	.	.	O-WRT-W2 (22)	
62B	62	.	.	O-WRT-W3 (24)	
63A	63	.	.	O-WRT-W4 (4)	
63A	64	.	.	O-WRT-W4 (4)	
67A	65	.	.	O-WAIT (15)	
33A	66	.	.	O-READ-TXT-ITEM (20)	
56A	67	.	.	O-INITIAL-TEXT (21)	
62A	68	.	.	O-WRT-W2 (22)	
62B	69	.	.	O-WRT-W3 (24)	
63A	70	.	.	O-WRT-W4 (4)	
63A	71	.	.	O-WRT-W4 (4)	
67A	72	.	.	O-WAIT (15)	
57A	73	.	.	O-MOVE-TEXT-LEFT	
62A	74	.	.	O-WRT-W2 (22)	
62B	75	.	.	O-WRT-W3 (24)	
63A	76	.	.	O-WRT-W4 (4)	
58A	77	.	.	O-MOVE-TEXT-RIGHT (30)	
62A	78	.	.	O-WRT-W2 (22)	
62B	79	.	.	O-WRT-W3 (24)	
63A	80	.	.	O-WRT-W4 (4)	
67B	81	.	.	Quit Program [P-QUIT-PROG] (6)	
13A	82	.	.	Utility Menu Process [P-UTIL]	
32A	83	.	.	O-READ-MENU-TITLE (35)	
61B	84	.	.	O-WRT-W1 (18)	
33A	85	.	.	O-READ-TXT-ITEM (20)	
56A	86	.	.	O-INITIAL-TEXT (21)	
62A	87	.	.	O-WRT-W2 (22)	
62B	88	.	.	O-WRT-W3 (24)	
63A	89	.	.	O-WRT-W4 (4)	
52A	90	.	.	O-FRONT-ENQ (7)	
52A	91	.	.	O-FRONT-ENQ (7)	
52A	92	.	.	O-FRONT-ENQ (7)	
51A	93	.	.	O-EXCH-Q-BLOCKS (45)	
52A	94	.	.	O-FRONT-ENQ (7)	
34A	95	.	.	O-UPDATE-ATTR-FLAG (47)	
52A	96	.	.	O-FRONT-ENQ (7)	
53A	97	.	.	O-DEQ (13)	
33A	98	.	.	O-READ-TXT-ITEM (20)	
56A	99	.	.	O-INITIAL-TEXT (21)	
62A	100	.	.	O-WRT-W2 (22)	
62B	101	.	.	O-WRT-W3 (24)	
63A	102	.	.	O-WRT-W4 (4)	
33A	103	.	.	O-READ-TXT-ITEM (20)	
56A	104	.	.	O-INITIAL-TEXT (21)	

PROCEDURES

62A	105	.	.	O-WRT-W2 (22)
62B	106	.	.	O-WRT-W3 (24)
63A	107	.	.	O-WRT-W4 (4)
33A	108	.	.	O-READ-TXT-ITEM (20)
56A	109	.	.	O-INITIAL-TEXT (21)
62A	110	.	.	O-WRT-W2 (22)
62B	111	.	.	O-WRT-W3 (24)
63A	112	.	.	O-WRT-W4 (4)
57A	113	.	.	O-MOVE-TEXT-LEFT (73)
62A	114	.	.	O-WRT-W2 (22)
62B	115	.	.	O-WRT-W3 (24)
63A	116	.	.	O-WRT-W4 (4)
58A	117	.	.	O-MOVE-TEXT-RIGHT (30)
62A	118	.	.	O-WRT-W2 (22)
62B	119	.	.	O-WRT-W3 (24)
63A	120	.	.	O-WRT-W4 (4)
67B	121	.	.	Quit Program [P-QUIT-PROG] (6)
16A	122	.	.	Find Main Menu Process [P-FIND-MENU]
47A	123	.	.	O-READ-NO-OF-MATCHED-BIRDS (10)
63B	124	.	.	O-WRT-W5 (11)
32A	125	.	.	O-READ-MENU-TITLE (35)
61B	126	.	.	O-WRT-W1 (18)
33A	127	.	.	O-READ-TXT-ITEM (20)
56A	128	.	.	O-INITIAL-TEXT (21)
62A	129	.	.	O-WRT-W2 (22)
62B	130	.	.	O-WRT-W3 (24)
63A	131	.	.	O-WRT-W4 (4)
52A	132	.	.	O-FRONT-ENG (7)
52A	133	.	.	O-FRONT-ENG (7)
52A	134	.	.	O-FRONT-ENG (7)
51A	135	.	.	O-EXCH-Q-BLOCKS (45)
52A	136	.	.	O-FRONT-ENG (7)
34A	137	.	.	O-UPDATE-ATTR-FLAG (47)
52A	138	.	.	O-FRONT-ENG (7)
53A	139	.	.	O-DEQ (13)
38B	140	.	.	O-FILL-FILTER (8)
42A	141	.	.	O-SCAN (9)
47A	142	.	.	O-READ-NO-OF-MATCHED-BIRDS (10)
63B	143	.	.	O-WRT-W5 (11)
33A	144	.	.	O-READ-TXT-ITEM (20)
56A	145	.	.	O-INITIAL-TEXT (21)
62A	146	.	.	O-WRT-W2 (22)
62B	147	.	.	O-WRT-W3 (24)
63A	148	.	.	O-WRT-W4 (4)
33A	149	.	.	O-READ-TXT-ITEM (20)
56A	150	.	.	O-INITIAL-TEXT (21)
62A	151	.	.	O-WRT-W2 (22)
62B	152	.	.	O-WRT-W3 (24)
63A	153	.	.	O-WRT-W4 (4)
33A	154	.	.	O-READ-TXT-ITEM (20)
56A	155	.	.	O-INITIAL-TEXT (21)
62A	156	.	.	O-WRT-W2 (22)

PROCEDURES

62B	157	.	.	O-WRT-W3 (24)
63A	158	.	.	O-WRT-W4 (4)
57A	159	.	.	O-MOVE-TEXT-LEFT (73)
62A	160	.	.	O-WRT-W2 (22)
62B	161	.	.	O-WRT-W3 (24)
63A	162	.	.	O-WRT-W4 (4)
58A	163	.	.	O-MOVE-TEXT-RIGHT (30)
62A	164	.	.	O-WRT-W2 (22)
62B	165	.	.	O-WRT-W3 (24)
63A	166	.	.	O-WRT-W4 (4)
67B	167	.	.	Quit Program [P-QUIT-PROG] (6)
18A	168	.	.	List Found Birds Process [P-LIST-FOUND]
45A	169	.	.	O-READ-NO-OF-FOUND-BIRDS
63B	170	.	.	O-WRT-W5 (11)
61B	171	.	.	O-WRT-W1 (18)
63A	172	.	.	O-WRT-W4 (4)
45B	173	.	.	O-LIST-FOUND-BIRDS
61B	174	.	.	O-WRT-W1 (18)
63A	175	.	.	O-WRT-W4 (4)
37A	176	.	.	O-READ-LIST-FOUND-METHOD
52A	177	.	.	O-FRONT-ENQ (7)
52A	178	.	.	O-FRONT-ENQ (7)
52A	179	.	.	O-FRONT-ENQ (7)
51A	180	.	.	O-EXCH-Q-BLOCKS (45)
52A	181	.	.	O-FRONT-ENQ (7)
52A	182	.	.	O-FRONT-ENQ (7)
45B	183	.	.	O-LIST-FOUND-BIRDS (173)
61B	184	.	.	O-WRT-W1 (18)
63A	185	.	.	O-WRT-W4 (4)
45B	186	.	.	O-LIST-FOUND-BIRDS (173)
61B	187	.	.	O-WRT-W1 (18)
63A	188	.	.	O-WRT-W4 (4)
67B	189	.	.	Quit Program [P-QUIT-PROG] (6)
19B	190	.	.	Clear Found Birds Process [P-CLEAR-FOUND]
61B	191	.	.	O-WRT-W1 (18)
63A	192	.	.	O-WRT-W4 (4)
52A	193	.	.	O-FRONT-ENQ (7)
52A	194	.	.	O-FRONT-ENQ (7)
52A	195	.	.	O-FRONT-ENQ (7)
51A	196	.	.	O-EXCH-Q-BLOCKS (45)
46A	197	.	.	O-CLEAR-FOUND-BIRDS
21A	198	.	.	List Attributes Process [P-LIST-ATTR]
35A	199	.	.	O-READ-NO-OF-SELECTED-ATTRIBUTES
63B	200	.	.	O-WRT-W5 (11)
61B	201	.	.	O-WRT-W1 (18)
63A	202	.	.	O-WRT-W4 (4)
36B	203	.	.	O-LIST-SELECTED-ATTRIBUTES
61B	204	.	.	O-WRT-W1 (18)
63A	205	.	.	O-WRT-W4 (4)
52A	206	.	.	O-FRONT-ENQ (7)
52A	207	.	.	O-FRONT-ENQ (7)
52A	208	.	.	O-FRONT-ENQ (7)

PROCEDURES

51A	209	. .	O-EXCH-Q-BLOCKS (45)
61B	210	. .	O-WRT-W1 (18)
63A	211	. .	O-WRT-W4 (4)
36A	212	. .	O-CLEAR-ATTRIBUTE
38B	213	. .	O-FILL-FILTER (8)
42A	214	. .	O-SCAN (9)
35A	215	. .	O-READ-NO-OF-SELECTED-ATTRIBUTES (199)
63B	216	. .	O-WRT-W5 (11)
61B	217	. .	O-WRT-W1 (18)
63A	218	. .	O-WRT-W4 (4)
36B	219	. .	O-LIST-SELECTED-ATTRIBUTES (203)
61B	220	. .	O-WRT-W1 (18)
63A	221	. .	O-WRT-W4 (4)
36B	222	. .	O-LIST-SELECTED-ATTRIBUTES (203)
61B	223	. .	O-WRT-W1 (18)
63A	224	. .	O-WRT-W4 (4)
36B	225	. .	O-LIST-SELECTED-ATTRIBUTES (203)
61B	226	. .	O-WRT-W1 (18)
63A	227	. .	O-WRT-W4 (4)
57A	228	. .	O-MOVE-TEXT-LEFT (73)
62A	229	. .	O-WRT-W2 (22)
62B	230	. .	O-WRT-W3 (24)
63A	231	. .	O-WRT-W4 (4)
58A	232	. .	O-MOVE-TEXT-RIGHT (30)
62A	233	. .	O-WRT-W2 (22)
62B	234	. .	O-WRT-W3 (24)
63A	235	. .	O-WRT-W4 (4)
67B	236	. .	Quit Program [P-QUIT-PROG] (6)
22B	237	. .	Clear Attributes Process [P-CLEAR-ATTR]
61B	238	. .	O-WRT-W1 (18)
63A	239	. .	O-WRT-W4 (4)
52A	240	. .	O-FRONT-ENG (7)
52A	241	. .	O-FRONT-ENG (7)
52A	242	. .	O-FRONT-ENG (7)
51A	243	. .	O-EXCH-Q-BLOCKS (45)
35B	244	. .	O-CLEAR-ALL-ATTRIBUTES
38B	245	. .	O-FILL-FILTER (8)
42A	246	. .	O-SCAN (9)
47A	247	. .	O-READ-NO-OF-MATCHED-BIRDS (10)
63B	248	. .	O-WRT-W5 (11)
24A	249	. .	List Matched Birds Process
47A	250	. .	O-READ-NO-OF-MATCHED-BIRDS (10)
63B	251	. .	O-WRT-W5 (11)
61B	252	. .	O-WRT-W1 (18)
63A	253	. .	O-WRT-W4 (4)
43A	254	. .	O-LIST-MATCHED-BIRDS
63A	255	. .	O-WRT-W4 (4)
61B	256	. .	O-WRT-W1 (18)
38A	257	. .	O-READ-LIST-MATCHED-METHOD
52A	258	. .	O-FRONT-ENG (7)
52A	259	. .	O-FRONT-ENG (7)
52A	260	. .	O-FRONT-ENG (7)

PROCEDURES

51A	261	. .	O-EXCH-Q-BLOCKS (45)
52A	262	. .	O-FRONT-ENQ (7)
52A	263	. .	O-FRONT-ENQ (7)
43A	264	. .	O-LIST-MATCHED-BIRDS (254)
61B	265	. .	O-WRT-W1 (18)
63A	266	. .	O-WRT-W4 (4)
43A	267	. .	O-LIST-MATCHED-BIRDS (254)
61B	268	. .	O-WRT-W1 (18)
63A	269	. .	O-WRT-W4 (4)
57A	270	. .	O-MOVE-TEXT-LEFT (73)
62A	271	. .	O-WRT-W2 (22)
62B	272	. .	O-WRT-W3 (24)
63A	273	. .	O-WRT-W4 (4)
58A	274	. .	O-MOVE-TEXT-RIGHT (30)
62A	275	. .	O-WRT-W2 (22)
62B	276	. .	O-WRT-W3 (24)
63A	277	. .	O-WRT-W4 (4)
67B	278	. .	Quit Program [P-QUIT-PROG] (6)
26A	279	. .	Count Bird Process [P-COUNT-BIRD]
44B	280	. .	O-CHANGE-BIRD-COUNT
38A	281	. .	O-READ-LIST-MATCHED-METHOD (257)
52A	282	. .	O-FRONT-ENQ (7)
52A	283	. .	O-FRONT-ENQ (7)
52A	284	. .	O-FRONT-ENQ (7)
51A	285	. .	O-EXCH-Q-BLOCKS (45)
44B	286	. .	O-CHANGE-BIRD-COUNT (280)
61B	287	. .	O-WRT-W1 (18)
44B	288	. .	O-CHANGE-BIRD-COUNT (280)
61B	289	. .	O-WRT-W1 (18)
67B	290	. .	Quit Program [P-QUIT-PROG] (6)
27B	291	. .	Clear a Found Bird Process [P-CLEAR-BIRD]
61B	292	. .	O-WRT-W1 (18)
63A	293	. .	O-WRT-W4 (4)
52A	294	. .	O-FRONT-ENQ (7)
52A	295	. .	O-FRONT-ENQ (7)
52A	296	. .	O-FRONT-ENQ (7)
51A	297	. .	O-EXCH-Q-BLOCKS (45)
46B	298	. .	O-CLEAR-BIRD
30A	299	. .	O-READ-MENU-FILE
31A	300	. .	O-WRITE-MENU-FILE
43B	301	. .	O-READ-COUNT-FILE
44A	302	. .	O-WRITE-COUNT-FILE
50A	303	. .	O-READ-Q-FILE
50B	304	. .	O-WRITE-Q-FILE

Birds
PROCEDURE INDEX

PROCEDURE DEFINED
REFERENCED IN PROCEDURE
LINES

11A Attribute Menu Process [P-ATTR-MENU]
5A Scheduler Process
38

27B Clear a Found Bird Process [P-CLEAR-BIRD]
5A Scheduler Process
56

22B Clear Attributes Process [P-CLEAR-ATTR]
5A Scheduler Process
50

19B Clear Found Birds Process [P-CLEAR-FOUND]
5A Scheduler Process
46

26A Count Bird Process [P-COUNT-BIRD]
5A Scheduler Process
54

16A Find Main Menu Process [P-FIND-MENU]
5A Scheduler Process
42

8A Help Menu Process [P-HELP]
5A Scheduler Process
36

21A List Attributes Process [P-LIST-ATTR]
5A Scheduler Process
48

18A List Found Birds Process [P-LIST-FOUND]
5A Scheduler Process
44

24A List Matched Birds Process
5A Scheduler Process
52

44B O-CHANGE-BIRD-COUNT
26A Count Bird Process [P-COUNT-BIRD]
3 25 29

35B O-CLEAR-ALL-ATTRIBUTES
22B Clear Attributes Process [P-CLEAR-ATTR]
18

36A O-CLEAR-ATTRIBUTE
21A List Attributes Process [P-LIST-ATTR]
42

46B O-CLEAR-BIRD
27B Clear a Found Bird Process [P-CLEAR-BIRD]
18

46A O-CLEAR-FOUND-BIRDS
19B Clear Found Birds Process [P-CLEAR-FOUND]
19

64A O-CLR-W1
61B O-WRT-W1
15

64B O-CLR-W2
62A O-WRT-W2
13

64C O-CLR-W3

Birds
PROCEDURE INDEX

```

PROCEDURE DEFINED
  REFERENCED IN PROCEDURE
    LINES
62B O-WRT-W3
    13
65A O-CLR-W4
    5A Scheduler Process
        32
    63A O-WRT-W4
        16
65B O-CLR-W5
    63B O-WRT-W5
        11
53A O-DEQ
    5A Scheduler Process
        28
    11A Attribute Menu Process [P-ATTR-MENU]
        38
    13A Utility Menu Process [P-UTIL]
        37
    16A Find Main Menu Process [P-FIND-MENU]
        39
51A O-EXCH-Q-BLOCKS
    11A Attribute Menu Process [P-ATTR-MENU]
        25
    13A Utility Menu Process [P-UTIL]
        25
    16A Find Main Menu Process [P-FIND-MENU]
        26
    18A List Found Birds Process [P-LIST-FOUND]
        33
    19B Clear Found Birds Process [P-CLEAR-FOUND]
        16
    21A List Attributes Process [P-LIST-ATTR]
        31
    22B Clear Attributes Process [P-CLEAR-ATTR]
        15
    24A List Matched Birds Process
        33
    26A Count Bird Process [P-COUNT-BIRD]
        21
    27B Clear a Found Bird Process [P-CLEAR-BIRD]
        15
38B O-FILL-FILTER
    5A Scheduler Process
        21
    11A Attribute Menu Process [P-ATTR-MENU]
        39
    16A Find Main Menu Process [P-FIND-MENU]
        40
    21A List Attributes Process [P-LIST-ATTR]
        43
    22B Clear Attributes Process [P-CLEAR-ATTR]
        19
52A O-FRONT-ENG

```

Birds
PROCEDURE INDEX

15 10 1990 PAGE 3 - 3

PROCEDURE DEFINED

REFERENCED IN PROCEDURE

LINES

- 11A Attribute Menu Process [P-ATTR-MENU]
19 21 24 29 34
- 13A Utility Menu Process [P-UTIL]
19 21 24 28 33
- 16A Find Main Menu Process [P-FIND-MENU]
20 22 25 30 35
- 18A List Found Birds Process [P-LIST-FOUND]
27 29 32 36 43
- 19B Clear Found Birds Process [P-CLEAR-FOUND]
10 12 15
- 21A List Attributes Process [P-LIST-ATTR]
25 27 30
- 22B Clear Attributes Process [P-CLEAR-ATTR]
9 11 14
- 24A List Matched Birds Process
27 29 32 36 47
- 26A Count Bird Process [P-COUNT-BIRD]
15 17 20
- 27B Clear a Found Bird Process [P-CLEAR-BIRD]
9 11 14
- 67B Quit Program [P-QUIT-PROG]
16
- 56A O-INITIAL-TEXT
 - 8A Help Menu Process [P-HELP]
4
 - 11A Attribute Menu Process [P-ATTR-MENU]
5 45 54 66
 - 13A Utility Menu Process [P-UTIL]
5 40 48 55
 - 16A Find Main Menu Process [P-FIND-MENU]
7 46 54 61
- 45B O-LIST-FOUND-BIRDS
 - 18A List Found Birds Process [P-LIST-FOUND]
13 47 52
- 43A O-LIST-MATCHED-BIRDS
 - 24A List Matched Birds Process
12 51 56
- 36B O-LIST-SELECTED-ATTRIBUTES
 - 21A List Attributes Process [P-LIST-ATTR]
12 57 66 71
- 57A O-MOVE-TEXT-LEFT
 - 11A Attribute Menu Process [P-ATTR-MENU]
75
 - 13A Utility Menu Process [P-UTIL]
60
 - 16A Find Main Menu Process [P-FIND-MENU]
66
 - 21A List Attributes Process [P-LIST-ATTR]
75
 - 24A List Matched Birds Process
60
- 58A O-MOVE-TEXT-RIGHT

Birds
PROCEDURE INDEX

15 10 1990 PAGE 3 - 4

PROCEDURE DEFINED
REFERENCES IN PROCEDURE
LINES

- 9A Help Menu Process [P-HELP]
21
- 11A Attribute Menu Process [P-ATTR-MENU]
80
- 13A Utility Menu Process [P-UTIL]
65
- 16A Find Main Menu Process [P-FIND-MENU]
71
- 21A List Attributes Process [P-LIST-ATTR]
80
- 24A List Matched Birds Process
65
- 41A O-READ-BIRD-DATA
5A Scheduler Process
3
- 43B O-READ-COUNT-FILE
- 37A O-READ-LIST-FOUND-METHOD
18A List Found Birds Process [P-LIST-FOUND]
17
- 38A O-READ-LIST-MATCHED-METHOD
24A List Matched Birds Process
18
- 26A Count Bird Process [P-COUNT-BIRD]
7
- 30A O-READ-MENU-FILE
- 32A O-READ-MENU-TITLE
11A Attribute Menu Process [P-ATTR-MENU]
1
- 13A Utility Menu Process [P-UTIL]
1
- 16A Find Main Menu Process [P-FIND-MENU]
3
- 45A O-READ-NO-OF-FOUND-BIRDS
18A List Found Birds Process [P-LIST-FOUND]
1
- 47A O-READ-NO-OF-MATCHED-BIRDS
5A Scheduler Process
23
- 11A Attribute Menu Process [P-ATTR-MENU]
41
- 16A Find Main Menu Process [P-FIND-MENU]
1 42
- 220 Clear Attributes Process [P-CLEAR-ATTR]
21
- 24A List Matched Birds Process
1
- 35A O-READ-NO-OF-SELECTED-ATTRIBUTES
21A List Attributes Process [P-LIST-ATTR]
1 45
- 50A O-READ-Q-FILE
- 53A O-READ-TXT-ITEM

Birds
PROCEDURE INDEX

15 10 1990 PAGE 3 - 5

PROCEDURE DEFINED
REFERENCED IN PROCEDURE
LINES

8A Help Menu Process [P-HELP]
3

11A Attribute Menu Process [P-ATTR-MENU]
4 44 52 64

13A Utility Menu Process [P-UTIL]
4 39 47 54

16A Find Main Menu Process [P-FIND-MENU]
6 45 53 60

42A O-SCAN
5A Scheduler Process
22

11A Attribute Menu Process [P-ATTR-MENU]
40

16A Find Main Menu Process [P-FIND-MENU]
41

21A List Attributes Process [P-LIST-ATTR]
44

22B Clear Attributes Process [P-CLEAR-ATTR]
20

61A O-SCREEN-FORMAT
5A Scheduler Process
2

34A O-UPDATE-ATTR-FLAG
11A Attribute Menu Process [P-ATTR-MENU]
30

13A Utility Menu Process [P-UTIL]
29

16A Find Main Menu Process [P-FIND-MENU]
31

67A O-WAIT
5A Scheduler Process
31

11A Attribute Menu Process [P-ATTR-MENU]
60 72

44A O-WRITE-COUNT-FILE

31A O-WRITE-MENU-FILE

50B O-WRITE-Q-FILE

61B O-WRT-W1
8A Help Menu Process [P-HELP]
1

11A Attribute Menu Process [P-ATTR-MENU]
2

13A Utility Menu Process [P-UTIL]
2

16A Find Main Menu Process [P-FIND-MENU]
4

18A List Found Birds Process [P-LIST-FOUND]
4 15 48 53

19B Clear Found Birds Process [P-CLEAR-FOUND]
1

21A List Attributes Process [P-LIST-ATTR]
4

Birds
PROCEDURE INDEX

15 10 1990 PAGE 3 - 6

PROCEDURE DEFINED

REFERENCED IN PROCEDURE

LINES

- 21A List Attributes Process [P-LIST-ATTR]
13 34 48 60 67 72
- 22B Clear Attributes Process [P-CLEAR-ATTR]
1
- 24A List Matched Birds Process
4 15 52 57
- 26A Count Bird Process [P-COUNT-BIRD]
26 30
- 27B Clear a Found Bird Process [P-CLEAR-BIRD]
1
- 62A O-WRT-W2
 - 8A Help Menu Process [P-HELP]
5 17 22
 - 11A Attribute Menu Process [P-ATTR-MENU]
6 46 55 67 76 81
 - 13A Utility Menu Process [P-UTIL]
6 41 49 56 61 66
 - 16A Find Main Menu Process [P-FIND-MENU]
8 47 55 62 67 72
 - 21A List Attributes Process [P-LIST-ATTR]
76 81
 - 24A List Matched Birds Process
- 62B O-WRT-W3
 - 8A Help Menu Process [P-HELP]
6 18 23
 - 11A Attribute Menu Process [P-ATTR-MENU]
7 47 56 68 77 82
 - 13A Utility Menu Process [P-UTIL]
7 42 50 57 62 67
 - 16A Find Main Menu Process [P-FIND-MENU]
9 48 56 63 68 73
 - 21A List Attributes Process [P-LIST-ATTR]
77 82
 - 24A List Matched Birds Process
62 67
- 63A O-WRT-W4
 - 5A Scheduler Process
16 30
 - 8A Help Menu Process [P-HELP]
7 19 24
 - 11A Attribute Menu Process [P-ATTR-MENU]
8 48 57 59 69 71 78 83
 - 13A Utility Menu Process [P-UTIL]
8 43 51 58 63 68
 - 16A Find Main Menu Process [P-FIND-MENU]
10 49 57 64 69 74
 - 18A List Found Birds Process [P-LIST-FOUND]
5 16 49 54
 - 19B Clear Found Birds Process [P-CLEAR-FOUND]
2
 - 21A List Attributes Process [P-LIST-ATTR]
5

Birds
PROCEDURE INDEX

15 10 199 PAGE 3 - 7

PROCEDURE DEFINED

REFERENCED IN PROCEDURE

LINES

21A List Attributes Process [P-LIST-ATTR]
14 35 49 61 68 73 78 83
22B Clear Attributes Process [P-CLEAR-ATTR]
2
24A List Matched Birds Process
5 14 53 58 63 68
27B Clear a Found Bird Process [P-CLEAR-BIRD]
2
63B O-WRT-W5
5A Scheduler Process
24
11A Attribute Menu Process [P-ATTR-MENU]
42
16A Find Main Menu Process [P-FIND-MENU]
2 43
18A List Found Birds Process [P-LIST-FOUND]
2
21A List Attributes Process [P-LIST-ATTR]
2 46
22B Clear Attributes Process [P-CLEAR-ATTR]
22
24A List Matched Birds Process
2
67B Quit Program [P-QUIT-PROG]
5A Scheduler Process
17
11A Attribute Menu Process [P-ATTR-MENU]
92
13A Utility Menu Process [P-UTIL]
72
16A Find Main Menu Process [P-FIND-MENU]
83
18A List Found Birds Process [P-LIST-FOUND]
58
21A List Attributes Process [P-LIST-ATTR]
87
24A List Matched Birds Process
72
26A Count Bird Process [P-COUNT-BIRD]
34
5A Scheduler Process
13A Utility Menu Process [P-UTIL]
5A Scheduler Process
40

Birds
DATA INDEX

15 10 1990 PAGE 4 - 1

DATA ITEM
 REFERENCED IN SEGMENT
 LINES

ATTRIBUTE_FLAG
 2A Private Variables
 14
 34A O-UPDATE-ATTR-FLAG
 21
 35B O-CLEAR-ALL-ATTRIBUTES
 15
 36A O-CLEAR-ATTRIBUTE
 12

BIRD_COUNT
 18A List Found Birds Process [P-LIST-FOUND]
 15 48 53
 44B O-CHANGE-BIRD-COUNT
 17 18 19 22 23 24
 45A O-READ-NO-OF-FOUND-BIRDS
 14 15
 46A O-CLEAR-FOUND-BIRDS
 14
 46B O-CLEAR-BIRD
 12

BIRD_FAMILY
 24A List Matched Birds Process
 15 52 57
 41A O-READ-BIRD-DATA
 19
 43A O-LIST-MATCHED-BIRDS
 22
 45B O-LIST-FOUND-BIRDS
 22

BIRD_INFO
 41A O-READ-BIRD-DATA
 21

BIRD_NAME
 18A List Found Birds Process [P-LIST-FOUND]
 16 49 54
 24A List Matched Birds Process
 14 53 58
 41A O-READ-BIRD-DATA
 20
 43A O-LIST-MATCHED-BIRDS
 21
 45B O-LIST-FOUND-BIRDS
 21

BIRD_REC
 42A O-SCAN
 37 38 52 53

BIRD_SAOS
 41A O-READ-BIRD-DATA
 21

CHAR_
 2A Private Variables
 11

Birds
DATA INDEX

15 10 1990 PAGE 4 - 2

DATA ITEM
 REFERENCED IN SEGMENT
 LINES
30A O-READ-MENU-FILE
 37 38 41 42 53 55 60 63 64 71 75 76
33A O-READ-TXT-ITEM
 57 58

CONTINUE_
 2A Private Variables
 3
 8A Help Menu Process [P-HELP]
 9 26
11A Attribute Menu Process [P-ATTR-MENU]
 9 10 22 26 35 89 93
13A Utility Menu Process [P-UTIL]
 9 10 22 26 34 70 73
16A Find Main Menu Process [P-FIND-MENU]
 11 12 23 27 36 80 84
18A List Found Birds Process [P-LIST-FOUND]
 18 19 30 34 44 56 59
19B Clear Found Birds Process [P-CLEAR-FOUND]
 13 17
21A List Attributes Process [P-LIST-ATTR]
 15 16 28 32 54 59 85 88
22B Clear Attributes Process [P-CLEAR-ATTR]
 12 16 24
24A List Matched Birds Process
 16 17 30 34 48 70 73
26A Count Bird Process [P-COUNT-BIRD]
 5 6 18 22 32
27B Clear a Found Bird Process [P-CLEAR-BIRD]
 12 16
30A O-READ-MENU-FILE
 33 39 43 65
32A O-READ-MENU-TITLE
 17 18 21
57A O-MOVE-TEXT-LEFT
 15 16 20
58A O-MOVE-TEXT-RIGHT
 15 16 20 24

C_POINTER
 2A Private Variables
 6
30A O-READ-MENU-FILE
 50
31A O-WRITE-MENU-FILE
 21
33A O-READ-TXT-ITEM
 47 48 49 52 53 54 57 63

C_REC
 32A O-READ-MENU-TITLE
 20 30

DISPLACEMENT_
 2A Private Variables
 13

Birds
DATA INDEX

15 10 1990 PAGE 4 - 3

DATA ITEM

	REFERENCED IN SEGMENT
	LINES
8A	Help Menu Process [P-HELP] 2
11A	Attribute Menu Process [P-ATTR-MENU] 3 43 51 63
13A	Utility Menu Process [P-UTIL] 3 38 46 53
16A	Find Main Menu Process [P-FIND-MENU] 5 44 52 59
18A	List Found Birds Process [P-LIST-FOUND] 12 46 51
21A	List Attributes Process [P-LIST-ATTR] 11 56 65 70
24A	List Matched Birds Process 11 50 55
26A	Count Bird Process [P-COUNT-BIRD] 2 24 28
33A	O-READ-TXT-ITEM 29 43
36B	O-LIST-SELECTED-ATTRIBUTES 12 14 17 21
43A	O-LIST-MATCHED-BIRDS 13
44B	O-CHANGE-BIRD-COUNT 15
45B	O-LIST-FOUND-BIRDS 13
false_	
24A	List Matched Birds Process 30
FLAG_ARY	
30A	O-READ-MENU-FILE 58
31A	O-WRITE-MENU-FILE 25
33A	O-READ-TXT-ITEM 57
FLAG_NUMBER	
34A	O-UPDATE-ATTR-FLAG 24 26 28 35
F_POINTER	
2A	Private Variables 7
30A	O-READ-MENU-FILE 52 62
GUIDE_ARROW_L	
56A	O-INITIAL-TEXT 29
57A	O-MOVE-TEXT-LEFT 26 33
58A	O-MOVE-TEXT-RIGHT 32 35
62A	O-WRT-W2 11

Birds
DATA INDEX

15 10 1990 PAGE 4 - 4

DATA ITEM
 REFERENCED IN SEGMENT
 LINES

GUIDE_ARROW_R
 56A O-INITIAL-TEXT
 25 27
 57A O-MOVE-TEXT-LEFT
 28 30 34
 58A O-MOVE-TEXT-RIGHT
 31 34
 62B O-WRT-W3
 11

HELP_ARY
 30A O-READ-MENU-FILE
 73
 31A O-WRITE-MENU-FILE
 31
 33A O-READ-TXT-ITEM
 41

HELP_ID
 11A Attribute Menu Process [P-ATTR-MENU]
 20
 15A Utility Menu Process [P-UTIL]
 20
 16A Find Main Menu Process [P-FIND-MENU]
 21
 18A List Found Birds Process [P-LIST-FOUND]
 28
 19B Clear Found Birds Process [P-CLEAR-FOUND]
 11
 21A List Attributes Process [P-LIST-ATTR]
 26
 22B Clear Attributes Process [P-CLEAR-ATTR]
 10
 24A List Matched Birds Process
 28
 26A Count Bird Process [P-COUNT-BIRD]
 16
 27B Clear a Found Bird Process [P-CLEAR-BIRD]
 10

H_C_POINTER
 33A O-READ-TXT-ITEM
 31 33 34 37 38 41

H_F_POINTER
 30A O-READ-MENU-FILE
 68 79

H_F_POINTER
 30A O-READ-MENU-FILE
 77

H_L_POINTER
 30A O-READ-MENU-FILE
 77 80
 31A O-WRITE-MENU-FILE
 30
 33A O-READ-TXT-ITEM
 33

Birds
DATA INDEX

15 10 1970 PAGE 4 - 5

DATA ITEM	REFERENCED IN SEGMENT
	LINE
33A O-READ-TXT-ITEM	37
ID_ATTR_M	1A Public Constants 1
ID_BIRD_F	1A Public Constants 11
ID_BIRD_SAN	1A Public Constants 8
ID_COLORING	1A Public Constants 15
ID_COUNTRY	1A Public Constants 4
ID_FEATURE	1A Public Constants 14
ID_FEEDING	1A Public Constants 13
ID_FIND_H	1A Public Constants 2
ID_HABITAT	1A Public Constants 9
ID_HELP	1A Public Constants 3 33A O-READ-TXT-ITEM 26
ID_HOKING	1A Public Constants 6
ID_MARKING	1A Public Constants 16
ID_N_PARKS	1A Public Constants 5
ID_SIZE	1A Public Constants 12
ID_STATUS	1A Public Constants 10
ID_TOWNS	1A Public Constants 7

DATA ITEM
REFERENCED IN SEGMENT
LINES

ID_UTILITY
1A Public Constants
17

I_
30A O-READ-MENU-FILE
54 56 58 59 70 73 74
31A O-WRITE-MENU-FILE
22 23 24 25 26 29 30 31 32
50A O-READ-Q-FILE
17 18 19 20
50B O-WRITE-Q-FILE
17 18 19 20
51A O-EXCH-Q-BLOCKS
14 15 16 16 17 19 20 21 21 22 24 25 26 26 27
52A O-FRONT-ENQ
26 27 28 28 29
53A O-DEQ
29 30 31 31 32

KEY_
2A Private Variables
5
8A Help Menu Process [P-HELP]
12 13 14
11A Attribute Menu Process [P-ATTR-MENU]
13 14 17
13A Utility Menu Process [P-UTIL]
13 14 17
16A Find Main Menu Process [P-FIND-MENU]
15 16 18
18A List Found Birds Process [P-LIST-FOUND]
22 23 25
19B Clear Found Birds Process [P-CLEAR-FOUND]
5 6 8
21A List Attributes Process [P-LIST-ATTR]
8 9 19 20 23 38 39 40 52 53
22B Clear Attributes Process [P-CLEAR-ATTR]
5 6 7
24A List Matched Birds Process
8 9 21 22 25
26A Count Bird Process [P-COUNT-BIRD]
10 11 13
27B Clear a Found Bird Process [P-CLEAR-BIRD]
5 6 7
67A O-WAIT
12 13

KEY_DH_ARROW
11A Attribute Menu Process [P-ATTR-MENU]
62
13A Utility Menu Process [P-UTIL]
52
16A Find Main Menu Process [P-FIND-MENU]
58

DATA ITEM

REFERENCED IN SEGMENT

LINES

18A List Found Birds Process [P-LIST-FOUND]
50
21A List Attributes Process [P-LIST-ATTR]
69
24A List Matched Birds Process
54
26A Count Bird Process [P-COUNT-BIRD]
27

KEY_ESCAPE

8A Help Menu Process [P-HELP]
25
11A Attribute Menu Process [P-ATTR-MENU]
84
13A Utility Menu Process [P-UTIL]
69
16A Find Main Menu Process [P-FIND-MENU]
75
18A List Found Birds Process [P-LIST-FOUND]
55
19B Clear Found Birds Process [P-CLEAR-FOUND]
20
21A List Attributes Process [P-LIST-ATTR]
84
22B Clear Attributes Process [P-CLEAR-ATTR]
23
24A List Matched Birds Process
69
26A Count Bird Process [P-COUNT-BIRD]
31
27B Clear a Found Bird Process [P-CLEAR-BIRD]
20

KEY_HELP

11A Attribute Menu Process [P-ATTR-MENU]
18
13A Utility Menu Process [P-UTIL]
18
16A Find Main Menu Process [P-FIND-MENU]
19
18A List Found Birds Process [P-LIST-FOUND]
26
19B Clear Found Birds Process [P-CLEAR-FOUND]
9
21A List Attributes Process [P-LIST-ATTR]
24
22B Clear Attributes Process [P-CLEAR-ATTR]
8
24A List Matched Birds Process
26
26A Count Bird Process [P-COUNT-BIRD]
14
27B Clear a Found Bird Process [P-CLEAR-BIRD]
8

DATA ITEM
 REFERENCED IN SEGMENT
 LINES

KEY_LEFT_ARROW
 8A Help Menu Process [P-HELP]
 15
 11A Attribute Menu Process [P-ATTR-MENU]
 74
 13A Utility Menu Process [P-UTIL]
 59
 16A Find Main Menu Process [P-FIND-MENU]
 65
 21A List Attributes Process [P-LIST-ATTR]
 74
 24A List Matched Birds Process
 59

KEY_MODE
 11A Attribute Menu Process [P-ATTR-MENU]
 23
 13A Utility Menu Process [P-UTIL]
 23
 16A Find Main Menu Process [P-FIND-MENU]
 24
 18A List Found Birds Process [P-LIST-FOUND]
 31
 19B Clear Found Birds Process [P-CLEAR-FOUND]
 14
 21A List Attributes Process [P-LIST-ATTR]
 29
 22B Clear Attributes Process [P-CLEAR-ATTR]
 13
 24A List Matched Birds Process
 31
 26A Count Bird Process [P-COUNT-BIRD]
 19
 27B Clear a Found Bird Process [P-CLEAR-BIRD]
 13

KEY_QUIT
 11A Attribute Menu Process [P-ATTR-MENU]
 91
 13A Utility Menu Process [P-UTIL]
 71
 16A Find Main Menu Process [P-FIND-MENU]
 82
 18A List Found Birds Process [P-LIST-FOUND]
 57
 21A List Attributes Process [P-LIST-ATTR]
 86
 24A List Matched Birds Process
 71
 26A Count Bird Process [P-COUNT-BIRD]
 33

KEY_RIGHT_ARROW
 8A Help Menu Process [P-HELP]
 20

DATA ITEM

REFERENCED IN SEGMENT

LINES

11A Attribute Menu Process [P-ATTR-MENU]
79

13A Utility Menu Process [P-UTIL]
64

16A Find Main Menu Process [P-FIND-MENU]
70

21A List Attributes Process [P-LIST-ATTR]
79

24A List Matched Birds Process
64

KEY_SELECT

11A Attribute Menu Process [P-ATTR-MENU]
27

13A Utility Menu Process [P-UTIL]
27

16A Find Main Menu Process [P-FIND-MENU]
28

18A List Found Birds Process [P-LIST-FOUND]
35

19B Clear Found Birds Process [P-CLEAR-FOUND]
18

21A List Attributes Process [P-LIST-ATTR]
33 41

22B Clear Attributes Process [P-CLEAR-ATTR]
17

24A List Matched Birds Process
35

27B Clear a Found Bird Process [P-CLEAR-BIRD]
17

KEY_UP_ARROW

11A Attribute Menu Process [P-ATTR-MENU]
50

13A Utility Menu Process [P-UTIL]
45

16A Find Main Menu Process [P-FIND-MENU]
51

18A List Found Birds Process [P-LIST-FOUND]
45

21A List Attributes Process [P-LIST-ATTR]
64

24A List Matched Birds Process
49

26A Count Bird Process [P-COUNT-BIRD]
23

LAST_PROCESS_ID

1B Public Variables
2

18A List Found Birds Process [P-LIST-FOUND]
10

24A List Matched Birds Process
10 10

26A Count Bird Process [P-COUNT-BIRD]
1

DATA ITEM REFERENCED IN SEGMENT
 LINES

27B Clear a Found Bird Process [P-CLEAR-BIRD]
19

LINE_
30A O-READ-MENU-FILE
24 27 28 31 32 34 37 41 45 46 47 48 49 50 51 52 53 56 57 58 59 60 62
63 67 68 69 71 75 76 77

LIST_FOUND_METHOD
37A O-READ-LIST-FOUND-METHOD
14 17

LIST_MATCHED_METHOD
24A List Matched Birds Process
37
38A O-READ-LIST-MATCHED-METHOD
14 18 22 25

L_POINTER
2A Private Variables
8
30A O-READ-MENU-FILE
62
31A O-WRITE-MENU-FILE
23
33A O-READ-TXT-ITEM
49 53

MENUS_ARY
32A O-READ-MENU-TITLE
19 30

MENU_TITLE
1C Private Constants
1
11A Attribute Menu Process [P-ATTR-MENU]
2
13A Utility Menu Process [P-UTIL]
2
16A Find Main Menu Process [P-FIND-MENU]
4
30A O-READ-MENU-FILE
48
31A O-WRITE-MENU-FILE
20
32A O-READ-MENU-TITLE
30

NO_OF_BIRDS
42A O-SCAN
38 53 64
43B O-READ-COUNT-FILE
12
44A O-WRITE-COUNT-FILE
12
45A O-READ-NO-OF-FOUND-BIRDS
13
46A O-CLEAR-FOUND-BIRDS
13

Birds
DATA INDEX

15 10 1990 PAGE 4 - 11

DATA ITEM

 REFERENCED IN SEGMENT

 LINES

NO_OF_FOUND_BIRDS

 18A List Found Birds Process [P-LIST-FOUND]

 3

 45A O-READ-NO-OF-FOUND-BIRDS

 12 16 19

NO_OF_FOUND_BIRDS_PRIVATE

 45A O-READ-NO-OF-FOUND-BIRDS

 19

NO_OF_LINES

 30A O-READ-MENU-FILE

 31 34 69 76

NO_OF_MATCHED_BIRDS

 24A List Matched Birds Process

 3

 42A O-SCAN

 20 41 48 58 64

 47A O-READ-NO-OF-MATCHED-BIRDS

 12

NO_OF_MATCHED_BIRDS_PRIVATE

 47A O-READ-NO-OF-MATCHED-BIRDS

 12

NO_OF_REC

 31A O-WRITE-MENU-FILE

 17

 32A O-READ-MENU-TITLE

 26

NO_OF_SELECTED_ATTRIBUTES

 21A List Attributes Process [P-LIST-ATTR]

 3 47

 35A O-READ-NO-OF-SELECTED-ATTRIBUTES

 13 17

NO_OF_S_ATTR

 35A O-READ-NO-OF-SELECTED-ATTRIBUTES

 17

NO_O_REC

 30A O-READ-MENU-FILE

 36

PROCESS_ID

 18 Public Variables

 1

 5A Scheduler Process

 34

 11A Attribute Menu Process [P-ATTR-MENU]

 20 85

 13A Utility Menu Process [P-UTIL]

 20

 16A Find Main Menu Process [P-FIND-MENU]

 21 76

 18A List Found Birds Process [P-LIST-FOUND]

 28 39 41

 19B Clear Found Birds Process [P-CLEAR-FOUND]

 11

Birds
DATA INDEX

15 10 1990 PAGE 4 - 12

DATA ITEM

REFERENCED IN SEGMENT

LINES

21A List Attributes Process [P-LIST-ATTR]
26
22B Clear Attributes Process [P-CLEAR-ATTR]
10
24A List Matched Birds Process
28 39 41 43 45
26A Count Bird Process [P-COUNT-BIRD]
16
27B Clear a Found Bird Process [P-CLEAR-BIRD]
10 19
30A O-READ-MENU-FILE
46
31A O-WRITE-MENU-FILE
19
32A O-READ-MENU-TITLE
19
33A O-READ-TXT-ITEM
28
34A O-UPDATE-ATTR-FLAG
44
52A O-FRONT-ENQ
22 31
53A O-DEQ
27

Q_ARY

50A O-READ-Q-FILE
19
50B O-WRITE-Q-FILE
19
51A O-EXCH-Q-BLOCKS
16 21 21 26
52A O-FRONT-ENQ
22 28 28 31
53A O-DEQ
27 31 31

Q_DAT

50A O-READ-Q-FILE
13

Q_MIDL

50A O-READ-Q-FILE
14
50B O-WRITE-Q-FILE
13
51A O-EXCH-Q-BLOCKS
15 20 21 25 26 29 29
52A O-FRONT-ENQ
23 33
53A O-DEQ
18 19 20

Q_SIZE

52A O-FRONT-ENQ
18

DATA ITEM	REFERENCED IN SEGMENT LINES
Q_TAIL	
50A O-READ-Q-FILE	16 18
50B O-WRITE-Q-FILE	15 18
51A O-EXCH-Q-BLOCKS	20 26 29
52A O-FRONT-ENG	18 21 24 26 32
53A O-DEG	17 22 24 30
Q_TMP_ARY	
51/ O-EXCH-Q-BLOCKS	16 26
REC_	
30A O-READ-MENU-FILE	30 35 36
31A O-WRITE-MENU-FILE	16 17 34
32A O-READ-MENU-TITLE	16 19 20 23 26
REV_W4	
33A O-READ-TXT-ITEM	59 61
63A O-T-W4	11
SELECTED_ATTR	
38B O-FILL-FILTER	16
SELECTED_ATTR_SET	
38B O-FILL-FILTER	14 16
42A O-SCAN	22 26 30
STATUS_	
2A Private Variables	4
5A Scheduler Process	6 29
11A Attribute Menu Process [P-ATTR-MENU]	31 53 65
13A Utility Menu Process [P-UTIL]	30
16A Find Main Menu Process [P-FIND-MENU]	32
30A O-READ-MENU-FILE	39 43 45 65
32A O-READ-MENU-TITLE	27 29
33A O-READ-TXT-ITEM	65
52A O-FRONT-ENG	19

DATA ITEM	REFERENCED IN SEGMENT
	LINES
52A O-FRONT-ENG	34
53A O-DEQ	25 28
STOP_	
5A Scheduler Process	27
11A Attribute Menu Process [P-ATTR-MENU]	94
18A List Found Birds Process [P-LIST-FOUND]	60
21A List Attributes Process [P-LIST-ATTR]	89
24A List Matched Birds Process	74
STRATEGY_	
42A O-SCAN	24 28 32 34
SYSTEM_ON	
5A Scheduler Process	1 20
67B Quit Program [P-QUIT-PROG]	19
TEXT_	
5A Scheduler Process	8 10 12 14 16
30A O-READ-MENU-FILE	26 27
50A O-READ-Q-FILE	13 14 15 16
50B O-WRITE-Q-FILE	13 14 15 16
TEXT_ARY	
31A O-WRITE-MENU-FILE	24
TEXT_DAT	
30A O-READ-MENU-FILE	26
31A O-WRITE-MENU-FILE	18
TEXT_DISPLAY	
2A Private Variables	2
8A Help Menu Process [P-HELP]	7 19 24
11A Attribute Menu Process [P-ATTR-MENU]	8 48 57 69 78 83
13A Utility Menu Process [P-UTIL]	8 43 51 58 63 68
16A Find Main Menu Process [P-FIND-MENU]	10 49 57 64 69 74
21A List Attributes Process [P-LIST-ATTR]	78

DATA ITEM
 REFERENCED IN SEGMENT
 LINES
21A List Attributes Process [P-LIST-ATTR]
 83
24A List Matched Birds Process
 63 68
56A O-INITIAL-TEXT
 23
57A O-MOVE-TEXT-LEFT
 36
58A O-MOVE-TEXT-RIGHT
 38
61B O-WRT-W1
 17
62A O-WRT-W2
 16
62B O-WRT-W3
 16
63A O-WRT-W4
 18
TEXT_ITEM
 2A Private Variables
 1
33A O-READ-TXT-ITEM
 41 63
56A O-INITIAL-TEXT
 23
57A O-MOVE-TEXT-LEFT
 10 11 16 27 36
58A O-MOVE-TEXT-RIGHT
 10 11 16 18 22 23 30 38
TEXT_LENGTH
 2A Private Variables
 12
56A O-INITIAL-TEXT
 24
TNP_ARY
 30A O-READ-MENU-FILE
 37 41 46 48 50 53 56 58 60 63 71 73 75
TXT_ARY
 30A O-READ-MENU-FILE
 56
33A O-READ-TXT-ITEM
 63
W1_SIZE
 2A Private Variables
 21
W1_X
 2A Private Variables
 15
61B O-WRT-W1
 16
64A O-CLR-W1
 11

Birds
DATA INDEX

15 10 1990 PAGE 4 - 16

DATA ITEM
REFERENCED IN SEGMENT
LINES

W1_Y

2A Private Variables

16

61B O-WRT-W1

16

64A O-CLR-W1

11

W2_SIZE

2A Private Variables

22

W2_X

62A O-WRT-W2

15

64B O-CLR-W2

11

W2_Y

62A O-WRT-W2

15

64B O-CLR-W2

11

W3_SIZE

2A Private Variables

23

W3_X

2A Private Variables

17

62B O-WRT-W3

15

64C O-CLR-W3

11

W3_Y

2A Private Variables

18

62B O-WRT-W3

15

64C O-CLR-W3

11

W4_SIZE

2A Private Variables

24

W4_X

2A Private Variables

19

63A O-WRT-W4

17

63B O-WRT-W5

12

65A O-CLR-W4

11

W4_Y

2A Private Variables

20

Birds
DATA INDEX

15 10 1990 PA:

DATA ITEM	REFERENCED IN SEGMENT	LINES
63A	O-WRT-W4	17
63B	O-WRT-W5	12
65A	O-CLR-W4	11
W5_TEXT		
63B	O-WRT-W5	13
W5_X		
65B	O-CLR-W5	11
W5_Y		
65B	O-CLR-W5	11
W_L_POINTER		
2A	Private Variables	9
56A	O-INITIAL-TEXT	21 23
57A	O-MOVE-TEXT-LEFT	10 11 12 16 17 18 19 23 24 36
58A	O-MOVE-TEXT-RIGHT	28 29 38
W_R_POINTER		
2A	Private Variables	10
56A	O-INITIAL-TEXT	22 23
57A	O-MOVE-TEXT-LEFT	23
58A	O-MOVE-TEXT-RIGHT	10 11 12 16 17 19 22 23 28 3
W_SIZE		
56A	O-INITIAL-TEXT	22 24
57A	O-MOVE-TEXT-LEFT	23 27 36
58A	O-MOVE-TEXT-RIGHT	18 19 28 38

APPENDIX. C- LIST OF MODULES AND CODE SIZE

Module Name	Code Size in Lines	% of Total Code Size
1-Data Environment	84	2.2
2-Scheduler Process	140	4.1
3-Attribute Menus Process	223	5.9
4-Utility Menu Process	200	5.3
5-Find Main Menu Process	210	6.6
6-List Found Birds Process	206	5.4
7-Clear Found Birds Process	99	2.6
8-List Attributes Process	204	5.4
9-Clear Attributes Process	108	2.9
10-List Matched Birds Process	198	5.2
11-Count Birds Process	125	3.3
12-Clear Bird From Found Birds Process	90	2.4
13-Help Process	109	2.9
14-Screen Resource	226	6.0
15-Scroll Resource	155	4.1
16-Text Resource	647	17.1
17-Bird Resource	527	14.0
18-Process Queue Resource	227	6.0
Total Code	3778	100.0

Author: Orooji-heravi Victor.

Name of thesis: Software Support For A Hand-held Bird Identification Aid.

PUBLISHER:

University of the Witwatersrand, Johannesburg

©2015

LEGALNOTICES:

Copyright Notice: All materials on the University of the Witwatersrand, Johannesburg Library website are protected by South African copyright law and may not be distributed, transmitted, displayed or otherwise published in any format, without the prior written permission of the copyright owner.

Disclaimer and Terms of Use: Provided that you maintain all copyright and other notices contained therein, you may download material (one machine readable copy and one print copy per page) for your personal and/or educational non-commercial use only.

The University of the Witwatersrand, Johannesburg, is not responsible for any errors or omissions and excludes any and all liability for any errors in or omissions from the information on the Library website.